

Nolan Associates						MultiREBAR Schedule ref:		006		01		Rev. P1	
Site ref: GF Energy Timet, Swansea						Date prepared: 30.06.15		Date revised:					
Location: Trench Details						Prepared By: KH		Checked by: ARW					
Job No: 2015-193-													
Member	Bar mark	Type & size	No of mbrs	No of bars in each	Total no	Length of each bar † mm	Shape code	A mm*	B mm*	C mm*	D mm*	E/R mm*	
Trench 1	01	H10	1	32	32	2550	21	460	1650	(460)			
	02	H10	1	32	32	5500	21	1850	1830	(1850)			
	03	H10	1	64	64	1750	24	600	530	(600)	380		
	04	H10	1	12	12	1850	21	500	885	(500)			
	05	H10	1	400	400	6000	00	(6000)					
	06	H10	1	810	810	1200	11	450	(750)				
	07	H10	1	370	370	1600	11	450	(1150)				
	08	H10	1	5	5	2100	32	710	720	310	(400)		
	09	H16	1	77	77	500	00	(500)					
	10	H10	1	8	8	1850	11	700	(1150)				
Trench 2	01	H10	2	8	16	2550	21	460	1650	(460)			
	02	H10	2	8	16	5500	21	1850	1830	(1850)			
	03	H10	2	16	32	1750	24	600	530	(600)	380		
	04	H10	2	12	24	1850	21	500	885	(500)			
	05	H10	2	80	160	6000	00	(6000)					
	09	H16	2	11	22	500	00	(500)					
	06	H10	2	200	400	1200	11	450	(750)				
	07	H10	2	100	200	1600	11	450	(1150)				
	08	H10	2	5	10	2100	32	710	720	310	(400)		
	10	H10	2	8	16	1850	11	700	(1150)				

This schedule complies with the requirements of BS 8666:2005

* Specified in multiples of 5mm

+ Specified in multiples of 25mm