

Permit Reference Number: MP3431SP

Operator: Alembic Manufacturing Ltd.

Installation: Form Number: L1

Reporting of Compliance with Low Impact Installation criteria for 2021

Criteria	Description	Demonstration of Compliance
Management techniques:	All of the criteria described below must be met without having to rely on significant management effort. In other words, the installation intrinsically must have only a low environmental impact.	<i>No changes have occurred to operations since issuing of low impact status permit, Installation still has intrinsically low environmental impact.</i>
Raw materials:	The installation must not release more than 50 m ³ of water per day as waste water or effluent. No account need be taken of the volume of water exported from the installations as product.	<i>Over 2021 we produced 7114 tonnes of liquid with a minimum water content of 57% = 4,055m³ of water. Our total water use over this time calculated from attached water bills was 6055m³ so our discharge volume is <2000m³ pa or < 5.48m³. per day..</i>
Techniques to prevent and reduce waste arisings and emissions:	The installation must comply with the criteria in this guidance without having to rely on active abatement. In particular, releases must not be dependent on continuing or correct operation of equipment.	<i>No active abatement is in use or required at our facility</i>
Groundwater Regulations:	There must be no planned release into the ground.	<i>There are no planned releases into ground (and there have been no unplanned releases)</i>
Waste Production:	The installation must not give rise to more than 1 tonne of controlled waste per day, averaged over a year, with not more than 20 tonnes being released in any one day. No more than 1% should be special waste.	<i>No Hazardous waste was produced . A total of 9.94 tonnes of general office and packaging waste was produced (Normal Disposal one wheely bin per week@ 3.568 tpa waste; 6.372t was sent for recycling). Granular waste and filter papers amounted to 13.92t tonnes per annum overall average 0.038 t per day. Annual total 23.86 tonnes of which 0% was special/hazardous waste . All waste now handled by Biffa, bar charts attached.</i>
Energy Consumption:	The installation must not consume energy at a rate greater than either 1MW or, if the installation uses a combined heat and power installation to supply any internal process heat, 10 MW, or 3MW if fuelled by waste oil.	<i>As shown by attached electricity bills total electricity used was 80,395KWhrs pa= 0.0092 MW. No fuel oil used this year.</i>

Accident Prevention:	The inventory of any substance at any time is not more than 5% of that in the COMAH Directive (lower tier) as set out in the Control of Major Accident Hazards Regulations 1999, Schedule 1. Updated version L111 2015 now in force has changes for nitric acid.	<i>Substances relevant to COMAH are nitric acid and fuel oil kerosene, diesel and propane. These have been kept within the Maximum Storage quantities as in p29 and 30 of our permit application (attached) which are within 5% limit. Previous COMAH lower tier individual category for nitric acid has been removed and replaced by smaller level of 50t "Oxidising liquids". To stay within 5% of this we have reduced maximum inventory to 2 t nitric acid =4%. (kerosene diesel and propane inventories are unchanged at 0.44%, 0.2% and 1.1% respectively)of lower tier COMAH.</i>
Noise:	As judged by the criterion set out in BS 4142 the installation must be unlikely to give rise to any complaint of a discernible increase in noise. This implies that in any case the rating level should not be more than 5dB(A) below the residual noise at any point on the boundary of the installation, whenever the installation is operating. This level may have to be reduced when: • background noise levels as defined in BS4142 are below 30dB; or • the spectrum of noise from the installation contains discernible tones or impulses.	<i>There is no discernible increase in noise at the boundary of installation compared to local environment.</i>
Emissions of polluting substances:	There must be no likelihood of a release of a mass of any particular substance from the whole installation to the environment at a rate more than is set out in the Agency's IPPC H1 guidance note¹ as "significant" (or as set out in any subsequent modification issued by the Agency).	<i>Installation is operated within agreed limits, as per our permit application, there have been no incidents or fugitive emissions.</i>

Odour:	There must be only a low potential for offence due to odour. An installation will not be considered as a low impact installation if it may give rise to an offensive smell noticeable outside the premises where the installation is operated.	<i>The installation does not give rise to any offensive odours.</i>
---------------	--	---

Signed
 (authorised to sign as representative of the Operator)

Date.....*21/1/22*

ⁱ IPPC H1 "Environmental Assessment and Appraisal of BAT"