



NOTES

1. Do not scale off this drawing.
2. Refer to dwg Nos. CH1701-AMEY-HGN-XX-DR-CH-2513-01-02 for General Arrangement.
3. All works in watercourses shall be carried out with care to minimise the risk of pollution adhering to the guidance for pollution prevention.
4. All dimensions are specified in millimeters and levels are in meters above ordnance datum.
5. Any discrepancies shall be noted immediately to the supervisor.
6. The location of any services shown on this drawing are approximate and for guidance only.
7. Primary armourestone to be sourced from standard European Grading 3-6t and secondary armourestone (filter layer) to be sourced from standard European Grading 0.3-1t in accordance with BS EN 13393-1:2002.
8. Rock armour layer thickness based on a source rock density of 2.3m/3t and surveyed using a highest point survey method. Prior to construction, the contractor shall confirm source material and proposed survey method to Designer to ensure presented dimensions in the drawing are appropriate.
9. Existing rock armour to be reused in the filter or lower primary armour layer providing it meets the dimensional requirements outlined in the specification.
10. All rock armour units are to be formed such that each layer is keyed into one another with a minimum of 5 joints of contact.
11. Tie-in details to be confirmed on site prior to construction.
12. Details of existing coastal defences unknown, care to be taken when dismantling and excavating around them.
13. Surplus rock armour from existing defences to be re-used in the repair and reinstatement of the existing rock groynes.
14. Surplus beach arisings to be spread within existing groyne bay.

Drawing No	Rev
CH1701-AMEY-HGN-XX-DR-CH-2514	P01.1