

DRAFT Permit with introductory note

The Environmental Permitting (England & Wales) Regulations 2016

Enfinium Parc Adfer Operations Ltd

**Parc Adfer Energy Recovery Facility
Deeside Industrial Park
Deeside
Flintshire
CH5 2LL**

Permit number

EPR/AB3092CV

Draft for consultation

Parc Adfer Energy Recovery Facility

Permit number EPR/AB3092CV

Introductory note

This introductory note does not form a part of the permit

This permit controls the operation of a waste incineration plant. The relevant listed activities are Section 5.1 A1 (b) and Section 5.4 A1 (b) (iii). The permit implements the requirements of the EU Directives on Industrial Emissions and Waste.

The main features of the permit are as follows:

The Energy Recovery Facility accepts up to 232,000 tonnes per annum of municipal, industrial and commercial waste for incineration in a combined heat and power (CHP) enabled Incinerator. Waste will be received in the waste reception hall where it will be discharged into a bunker for the temporary storage of waste. Waste will be mixed in the bunker and then fed into a feed hopper using an overhead crane.

The facility will process waste using air cooled, moving grate technology. The energy recovered from the combustion of waste will be utilised (in the form of high pressure steam) to produce electrical power through a steam turbine and generator unit. The facility will also have combined heat and power (CHP) capability through a blanking flange and heat/steam export from the turbine which can be utilised upon securing a suitable customer.

The key components of the technology will include, but shall not be limited to:

- A furnace/boiler unit incorporating moving grate technology and steam boiler with an energy recovery system;
- Flue gas treatment (FGT) system comprising selective non catalytic reduction (SNCR), dry reactor and bag house filters;
- Steam turbine/generator set with the capability for CHP operation;
- Condensate system, including air cooled condensers (ACC);
- Residue handling and storage facilities;
- Electrical equipment associated with the facility and its connection to the national grid;
- Continuous emissions monitoring system (CEMS); and
- Auxiliary equipment.

The combustion of waste will release flue gases which will be treated in order to comply with the requirements of the Industrial Emissions Directive.

Urea will be added at various stages of the boiler's combustion chamber to reduce nitrogen oxides (NOx). Lime and powdered activated carbon (PAC) will be used within the FGT system. The lime reduces acid gas emissions while the activated carbon reduces mercury and the formation of dioxins/furans. The by-products from both reactions are captured in the fabric filter as Air Pollution Control Residues (APCR).

The facility is designed to generate 20.22 MWe and export approximately 18.320 MW of electricity (assuming zero heat off-take).

Incinerator Bottom Ash (IBA) will remain after the combustion of the waste. This ash will be discharged from the end of the combustion grate directly into an ash quench bath. Ash from the first to fourth boiler pass will discharge to the IBA storage area to await removal for off-site treatment. Fly ash from the boiler fifth pass (economiser pass) is mixed with the hazardous fly ash to form the APCR and will be conveyed to silos for storage prior to being sent off site for treatment or disposal.

The site is located to the south east of the Dee Estuary within the Deeside Industrial Estate, 2 km south west of the nearest village, Puddington. The site is on an area of brownfield reclaimed land, once consisting of tidal mudflats of the Dee Estuary that was previously part of the Shotton Steelworks facility. The operator has constructed new bespoke buildings to house the proposed waste management activities. Farmland and areas of open space lie approximately 50m to the north of the proposed permit boundary. The Borderlands railway line is adjacent to the east of the site. There are Sites of Special Scientific Interest (SSSIs), Special Areas of Conservation (SACs) and Inshore Special Protection Areas with Marine Components (ISPAMs) within 2 km of the site boundary.

The site is centred on National Grid Reference SJ 310 716. The surrounding land use is predominantly industrial. Immediately adjacent to the site lies Shotton Power Station, UPM's Paper Mill and Great Bear Distribution.

Access to the site will be via Weighbridge Road which runs parallel and adjacent to the western boundary of the site. Weighbridge Road can be accessed off the A548 located north of the site. The A548 links to the A494/A550 to the east of the industrial estate.

There are existing drainage ditches on site, and surface water drains running within 20 m to the east and west of the site's boundary.

The installation has an expansion flap to the flue gas side of the boiler, this is an emergency pressure relief system and isn't in continuous operation.

Furnace Technology	Moving Grate
Number of lines	1
Waste	Municipal, industrial and commercial waste
Stack height	85m
Permitted plant capacity	232,000
Energy Generated (capacity)	20.22 MW _e

The status log of the permit sets out the permitting history, including any changes to the permit reference number.

Status Log of the permit		
Detail	Date	Comments
Application EPR/PP3733WW/A001	Duly made 27/10/2014	Application for Energy Recovery Facility by Incineration of Municipal waste
Additional information received	20/02/2015	Additional information received relating to noise modelling queries requested 04/02/2015.
Additional information received	06/05/2015	Additional information received relating to further noise queries requested 17/04/2015.
Additional information received	19/06/2015	Additional information received relating to Schedule 5 Notice issued 15 th May 2015.

Additional information received	07/07/2015	Additional information received relating to queries regarding PCB's & calculations used in Habitats Assessment requested 29 th June 2015.
Additional information received	02/09/2015	Additional information received relating to waste types, site drainage and CEMS requested 11 th and 17 th August 2015.
Additional information received	07/09/2015	Additional information received relating to waste types and site drainage requested 4 th September 2015.
Permit issued	28/10/2015	New permit number AB3092CV
Transfer application EPR/AB3092CV	Duly Made 26/04/2017	Application to transfer the permit to Parc Adfer Operations Limited
Transfer application EPR/AB3092CV/T001 Determined	08/06/2017	Permit EPR/AB3092CV issued to Parc Adfer operations limited
Variation Application EPR/AB3092CV/V002	Duly Made 24/01/2018	Numerous pre-operational changes requested
Variation Application EPR/AB3092CV/V002	20/04/2018	Permit Issued
Variation Application EPR/AB3092CV/V003	Duly Made 03/07/2020	Application submitted to change monitoring on the carbon monoxide short-term Emission Limit Value
Variation Application EPR/AB3092CV/V003	18/01/2021	Variation Issued to Parc Adfer Operations Limited
Variation Application EPR/AB3092CV/V004	Duly made 07/06/2021	Administrative variation to change operator name
Regulation 61 Notice sent to Operator	06/07/2021	Issue of a Notice under Regulation 61(1) of the EPR. Natural Resources Wales initiated review and variation to vary the permit following the publication of the revised Best Available Techniques (BAT) Reference Document (BRef) for Waste Incineration.
Variation Application EPR/AB3092CV/V004	21/07/2021	Variation Issued
Variation Application EPR/AB3092CV/V005	Duly made 02/12/2021	Application submitted to add a new EWC code
Variation Application EPR/AB3092CV/V005	20/12/2021	Variation Issued
Regulation 61 Notice response	23/12/2021	Response received from the Operator
Regulation 61 Notice response	29/03/2022	Revised response received from the Operator
Additional information received	06/10/2022	
Natural Resources Wales initiated variation determined EPR/AB3092CV/V006	19/12/2022	Varied permit issued to Operator. Natural Resources Wales initiated review and variation to vary the permit following the publication of the revised Best Available Techniques (BAT) Reference Document (BRef) for Waste Incineration
Variation Application PAN-018868 (EPR/AB3092CV/V007)	Duly made 13/02/2023	Application submitted to increase incineration capacity on existing unaltered plant from 200 ktpa to 232 ktpa.
Variation Application EPR/AB3092CV/V005	DD/MM/2023	Variation Issued [subject to final decision]

Permit

The Environmental Permitting (England and Wales) Regulations 2016

Permit number

EPR/AB3092CV

This is the consolidated permit referred to in the variation and consolidation notice for application **EPR/AB3092CV/V007** authorising:

Enfinium Parc Adfer Operations Ltd (“the operator”)

whose registered office is:

123 Victoria Street

London

SW1E 6DE

company registration number **09099184**

to operate an installation at:

Parc Adfer Energy Recovery Facility

Deeside Industrial Park

Deeside

Flintshire

CH5 2LL

to the extent authorised by and subject to the conditions of this permit.

Signed

Date

Consultation Draft – not authorised	DD/MM/2023
--	-------------------

Authorised on behalf of Natural Resources Wales

Conditions

1 Management

1.1 General management

- 1.1.1 The operator shall manage and operate the activities:
- (a) in accordance with a written management system that identifies and minimises risks of pollution, including those arising from operations, maintenance, accidents, incidents, non-conformances, closure and those drawn to the attention of the operator as a result of complaints; and
 - (b) using sufficient competent persons and resources.
- 1.1.2 Records demonstrating compliance with condition 1.1.1 shall be maintained.
- 1.1.3 Any person having duties that are or may be affected by the matters set out in this permit shall have convenient access to a copy of it kept at or near the place where those duties are carried out.

1.2 Energy efficiency

- 1.2.1 The operator shall:
- (a) take appropriate measures to ensure that energy is recovered with a high level of energy efficiency and energy is used efficiently in the activities.
 - (b) review and record at least every four years whether there are suitable opportunities to improve the energy efficiency of the activities; and
 - (c) take any further appropriate measures identified by a review.
- 1.2.2 The operator shall provide and maintain steam and/or hot water pass-outs such that opportunities for the further use of waste heat may be capitalised upon should they become practicable.
- 1.2.3 The operator shall review the viability of Combined Heat and Power (CHP) implementation at least every four years, or in response to any of the following factors, whichever comes sooner:
- (a) new plans for significant developments within 15 km of the installation;
 - (b) changes to the Local Plan;
 - (c) changes to the UK CHP Development Map or similar; and
 - (d) new financial or fiscal incentives for CHP.

The results shall be reported to Natural Resources Wales within two months of each review, including where there has been no change to the original assessment in respect of the above factors

1.3 Efficient use of raw materials

- 1.3.1 The operator shall:
- (a) take appropriate measures to ensure that raw materials and water are used efficiently in the activities;
 - (b) maintain records of raw materials and water used in the activities;

- (c) review and record at least every four years whether there are suitable alternative materials that could reduce environmental impact or opportunities to improve the efficiency of raw material and water use; and
- (d) take any further appropriate measures identified by a review.

1.4 Avoidance, recovery and disposal of wastes produced by the activities

1.4.1 The operator shall take appropriate measures to ensure that:

- (a) the waste hierarchy referred to in Article 4 of the Waste Framework Directive is applied to the generation of waste by the activities; and
- (b) any waste generated by the activities is treated in accordance with the waste hierarchy referred to in Article 4 of the Waste Framework Directive; and
- (c) where disposal is necessary, this is undertaken in a manner which minimises its impact on the environment.

1.4.2 The operator shall review and record at least every four years whether changes to those measures should be made and take any further appropriate measures identified by a review.

2 Operations

2.1 Permitted activities

- 2.1.1 The operator is only authorised to carry out the activities specified in schedule 1 table S1.1 (the “activities”).
- 2.1.2 Waste authorised by this permit shall be clearly distinguished from any other waste on the site.

2.2 The site

- 2.2.1 The activities shall not extend beyond the site, being the land shown edged in green on the site plan at schedule 7 to this permit.

2.3 Operating techniques

- 2.3.1 (a) The activities shall, subject to the conditions of this permit, be operated using the techniques and in the manner described in the documentation specified in schedule 1, table S1.2, unless otherwise agreed in writing by Natural Resources Wales.
- (b) If notified by Natural Resources Wales that the activities are giving rise to pollution, the operator shall submit to Natural Resources Wales for approval within the period specified, a revision of any plan or other documentation (“plan”) specified in schedule 1, table S1.2 or otherwise required under this permit which identifies and minimises the risks of pollution relevant to that plan, and shall implement the approved revised plan in place of the original from the date of approval, unless otherwise agreed in writing by Natural Resources Wales.
- 2.3.2 Any raw materials or fuels listed in schedule 2 table S2.1 shall conform to the specifications set out in that table.
- 2.3.3 Waste shall only be accepted if:
- (a) it is of a type and quantity listed in schedule 2 tables S2.2 and S2.3; and
 - (b) it conforms to the description in the documentation supplied by the producer and holder.

- 2.3.4 Waste paper, metal, plastic or glass that has been separately collected for the purpose of preparing for re-use or recycling shall not be accepted. Waste from the treatment of these separately collected wastes shall only be accepted if incineration delivers the best environmental outcome in accordance with regulation 12 of the Waste (England and Wales) Regulations 2011.
- 2.3.5 Separately collected fractions other than those listed in condition 2.3.4 shall not be accepted unless they are unsuitable for recovery by recycling.
- 2.3.6 The operator shall ensure that where waste produced by the activities is sent to a relevant waste operation, that operation is provided with the following information, prior to the receipt of the waste:
- (a) the nature of the process producing the waste;
 - (b) the composition of the waste;
 - (c) the handling requirements of the waste;
 - (d) the hazardous property associated with the waste, if applicable; and
 - (e) the waste code of the waste.
- 2.3.7 The operator shall ensure that where waste produced by the activities is sent to a landfill site, it meets the waste acceptance criteria for that landfill.
- 2.3.8 Waste shall not be charged if:
- (a) the combustion chamber temperature is below 850 °C,
 - (b) it is hazardous waste with a hazardous halogenated organic content of more than 1% (expressed as chlorine) and the combustion chamber temperature is below 1,100 °C.
 - (c) it is cytotoxic or cytostatic waste and the combustion chamber temperature is below 1,000 °C
 - (d) any continuous emission limit value in schedule 3 table S3.1(a) is exceeded during abnormal operation; or
 - (e) any continuous emission limit value in schedule 3 table S3.1 is exceeded, other than during abnormal operation; or
 - (f) continuous emission monitors to demonstrate compliance with any continuous emission limit value in schedule 3 table S3.1 are unavailable other than during abnormal operation; or
 - (g) there is a stoppage, disturbance or failure of the activated carbon abatement system, other than during abnormal operation.
 - (h) continuous emission monitors to demonstrate compliance with the emission limit values for particulates, TOC or CO in schedule 3 are unavailable unless alternative techniques, as agreed in writing with Natural Resources Wales, are used to demonstrate compliance with those emission limit values.
- 2.3.9 The operator shall record the beginning and end of each period of “abnormal operation”.
- 2.3.10 During a period of “abnormal operation”, the operator shall restore normal operation of the failed equipment or replace the failed equipment as soon as possible.
- 2.3.11 The operator shall interpret the start of the period of “abnormal operation” as the earliest of the following:

- (a) a technically unavoidable stoppage, disturbance, or failure of continuous emission monitors.
 - (b) a technically unavoidable stoppage, disturbance, or failure of the activated carbon abatement system
 - (c) Any other technically unavoidable stoppage, disturbance, or failure of the plant which is causing or could lead to an exceedance of an emission limit value in table S3.1.
- 2.3.12 The operator shall interpret the end of the period of “abnormal operation” as the earliest of the following:
- (a) when the failed equipment is repaired and brought back into normal operation;
 - (b) when the operator initiates a shut down of the waste combustion activity, as described in the application or as agreed in writing with Natural Resources Wales;
 - (c) The failed equipment has not been repaired and brought back into normal operation and a single period of abnormal operation reaches a duration of 4 hours after the start of abnormal operation on an incineration line
 - (d) Abnormal operation occurs on an incineration line and the cumulative duration of abnormal operation periods over 1 calendar year has reached 60 hours on that incineration line;
- 2.3.13 The operator shall have at least one auxiliary burner in each line which shall be operated at start up, shut down and as required during operation to ensure that the operating temperature specified in condition 2.3.8 is maintained as long as incompletely burned waste is present in the combustion chamber. Unless the temperature specified in condition 2.3.8 is maintained in the combustion chamber, such burner(s) shall be fed only with fuels which result in emissions no higher than those arising from the use of gas oil, liquefied gas or natural gas.
- 2.3.14 Bottom ash and APC residues shall not be mixed.
- 2.3.15 For the following activity referenced in schedule 1, table S1.1 (AR6) the activity shall be operated using the techniques and, in the manner, described in schedule 1, table S1.2A.

2.4 Improvement programme

- 2.4.1 The operator shall complete the improvements specified in schedule 1 table S1.3 by the date specified in that table unless otherwise agreed in writing by Natural Resources Wales.
- 2.4.2 Except in the case of an improvement which consists only of a submission to Natural Resources Wales, the operator shall notify Natural Resources Wales within 14 days of completion of each improvement.

2.5 Pre-operational conditions

- 2.5.1 The activities shall not be brought into operation until the measures specified in schedule 1 table S1.4A have been completed.
- 2.5.2 The operations specified in schedule 1 table S1.4B shall not commence until the measures specified in that table have been completed.

3 Emissions and monitoring

3.1 Emissions to water, air or land

- 3.1.1 There shall be no point source emissions to water, air or land except from the sources and emission points listed in schedule 3 tables S3.1 and S3.2.
- 3.1.2 The limits given in schedule 3, subject to 3.2.1, shall not be exceeded.
- 3.1.3 Wastes produced at the site shall, as a minimum, be sampled and analysed in accordance with schedule 3 table S3.4. Additional samples shall be taken and tested and appropriate action taken, whenever:
- (a) disposal or recovery routes change; or
 - (b) it is suspected that the nature or composition of the waste has changed such that the route currently selected may no longer be appropriate.
- 3.1.4 Periodic monitoring shall be carried out at least once every 5 years for groundwater and 10 years for soil; to the protocol agreed in writing with Natural Resources Wales under PO5, unless such monitoring is based on a systematic appraisal of the risk of contamination
- 3.1.5 For the following activity referenced in schedule 1, table S1.1 (AR6) Limited Operating Hours MCPs shall:
- (a) Not exceed 500 hours operation in a 12-month period as a rolling average over a 3-year period, and thereafter assessed annually
 - (b) Not operate for more than 750 hours in any single year

3.2 Emissions limits and monitoring for emission to air for incineration plant

- 3.2.1 The limits for emissions to air apply as follows:
- (a) The limits in table S3.1 shall not be exceeded except during periods of abnormal operation; and
 - (b) The limits in table S3.1(a) shall not be exceeded
- 3.2.2 Where Continuous Emission Monitors are installed to comply with the monitoring requirements in schedule 3 table S3.1 and S3.1(a); the Continuous Emission Monitors shall be used such that;
- (a) the values of the 95% confidence intervals of a single measured result at the daily emission limit value shall not exceed the following percentages of the emission limit values:

• Carbon monoxide	10%
• Sulphur dioxide	20%
• Oxides of nitrogen (NO & NO ₂ expressed as NO ₂)	20%
• Particulate matter	30%
• Total organic carbon (TOC)	30%
• Hydrogen chloride	40%
• Hydrogen fluoride	40%
• Ammonia	40%

- Mercury (Hg) 40%
- (b) valid half-hourly average values or 10-minute averages shall be determined within the effective operating time (excluding the start-up and shut-down periods) from the measured values after having subtracted the value of the confidence intervals in condition 3.2.2 (a).
 - (c) where it is necessary to calibrate or maintain the monitor and this means that data are not available for a complete half-hour or 10 minute period, the half-hourly average or 10-minute average shall in any case be considered valid if measurements are available for a minimum of 20 minutes or 7 minutes during the half-hour or 10-minute period respectively. The number of half-hourly or 10-minute averages so validated shall not exceed 5 or 15 respectively per day.
 - (d) daily average values shall be calculated as follows: the average of valid half hourly averages or 10 minute averages over a calendar day excluding half hourly averages or 10 minute averages during periods of abnormal operation. The daily average value shall be considered valid if no more than five half-hourly average or fifteen 10-minute average values in any day have been determined not to be valid;
 - (e) no more than ten daily average values per year shall be determined not to be valid:

3.3 Emissions of substances not controlled by emission limits

- 3.3.1 Emissions of substances not controlled by emission limits (excluding odour) shall not cause pollution. The operator shall not be taken to have breached this condition if appropriate measures, including, but not limited to, those specified in any approved emissions management plan, have been taken to prevent or where that is not practicable, to minimise, those emissions.
- 3.3.2 The operator shall:
 - (a) if notified by Natural Resources Wales that the activities are giving rise to pollution, submit to Natural Resources Wales for approval within the period specified, an emissions management plan which identifies and minimises the risks of pollution from emissions of substances not controlled by emission limits;
 - (b) implement the approved emissions management plan, from the date of approval, unless otherwise agreed in writing by Natural Resources Wales.
- 3.3.3 All liquids in containers, whose emission to water or land could cause pollution, shall be provided with secondary containment, unless the operator has used other appropriate measures to prevent or where that is not practicable, to minimise, leakage and spillage from the primary container.

3.4 Odour

- 3.4.1 Emissions from the activities shall be free from odour at levels likely to cause pollution outside the site, as perceived by an authorised officer of Natural Resources Wales, unless the operator has used appropriate measures, including, but not limited to, those specified in any approved odour management plan, to prevent or where that is not practicable to minimise the odour.
- 3.4.2 The operator shall:
 - (a) if notified by Natural Resources Wales that the activities are giving rise to pollution outside the site due to odour, submit to Natural Resources Wales for approval within the period specified, an odour management plan which identifies and minimises the risks of pollution from odour;

- (b) implement the approved odour management plan, from the date of approval, unless otherwise agreed in writing by Natural Resources Wales.

3.5 Noise and vibration

- 3.5.1 Emissions from the activities shall be free from noise and vibration at levels likely to cause pollution outside the site, as perceived by an authorised officer of Natural Resources Wales, unless the operator has used appropriate measures, including, but not limited to, those specified in any approved noise and vibration management plan to prevent or where that is not practicable to minimise the noise and vibration.
- 3.5.2 The operator shall:
 - (a) if notified by Natural Resources Wales that the activities are giving rise to pollution outside the site due to noise and vibration, submit to Natural Resources Wales for approval within the period specified, a noise and vibration management plan which identifies and minimises the risks of pollution from noise and vibration;
 - (b) implement the approved noise and vibration management plan, from the date of approval, unless otherwise agreed in writing by Natural Resources Wales.

3.6 Monitoring

- 3.6.1 The operator shall, unless otherwise agreed in writing by Natural Resources Wales, undertake the monitoring specified in the following tables in schedule 3 to this permit:
 - (a) point source emissions specified in tables S3.1, S3.1(a) and S3.2;
 - (b) process monitoring specified in table S3.3;
 - (c) residue quality in table S3.4
- 3.6.2 The operator shall maintain records of all monitoring required by this permit including records of the taking and analysis of samples, instrument measurements (periodic and continual), calibrations, examinations, tests and surveys and any assessment or evaluation made on the basis of such data.
- 3.6.3 Monitoring equipment, techniques, personnel and organisations employed for the emissions monitoring programme and the environmental or other monitoring specified in condition 3.6.1 shall have either MCERTS certification or MCERTS accreditation (as appropriate), where available, unless otherwise agreed in writing by Natural Resources Wales. Newly installed CEMs, or CEMs replacing existing CEMs, shall have MCERTS certification and have an MCERTS certified range which is not greater than 1.5 times the daily emission limit value (ELV) specified in schedule 3 table S3.1. The CEM shall also be able to measure instantaneous values over the ranges which are to be expected during all operating conditions. If it is necessary to use more than one range setting of the CEM to achieve this requirement, the CEM shall be verified for monitoring supplementary, higher ranges. Newly installed Data handling and acquisition systems (DAHS), or DAHS replacing existing DAHS, shall have MCERTS certification.
- 3.6.4 Permanent means of access shall be provided to enable sampling/monitoring to be carried out in relation to the emission points specified in schedule 3 tables S3.1, S3.1(a) and S3.2 unless otherwise agreed in writing by Natural Resources Wales.
- 3.6.5 For the following activities referenced in schedule 1, table S1.1 (AR6) the first monitoring measurements shall be carried out within four months of the issue date of the variation V006 or the date when the MCP is first put into operation, whichever is later.

3.7 Pests

- 3.7.1 The activities shall not give rise to the presence of pests which are likely to cause pollution, hazard or annoyance outside the boundary of the site. The operator shall not be taken to have breached this condition if appropriate measures, including, but not limited to, those specified in any approved pests management plan, have been taken to prevent or where that is not practicable, to minimise the presence of pests on the site.
- 3.7.2 The operator shall:
- (a) if notified by Natural Resources Wales, submit to Natural Resources Wales for approval within the period specified, a pests management plan which identifies and minimises risks of pollution, hazard or annoyance from pests;
 - (b) implement the pests management plan, from the date of approval, unless otherwise agreed in writing by Natural resources Wales

4 Information

4.1 Records

- 4.1.1 All records required to be made by this permit shall:
- (a) be legible;
 - (b) be made as soon as reasonably practicable;
 - (c) if amended, be amended in such a way that the original and any subsequent amendments remain legible, or are capable of retrieval; and
 - (d) be retained, unless otherwise agreed in writing by Natural Resources Wales, for at least 6 years from the date when the records were made, or in the case of the following records until permit surrender:
 - (i) off-site environmental effects; and
 - (ii) matters which affect the condition of the land and groundwater.
- 4.1.2 The operator shall keep on site all records, plans and the management system required to be maintained by this permit, unless otherwise agreed in writing by Natural Resources Wales.
- 4.1.3 The operator shall maintain a record of the type and quantity of fuel used and the total annual hours of operation for each MCP and/or Specified Generator.

4.2 Reporting

- 4.2.1 The operator shall send all reports and notifications required by the permit to Natural Resources Wales using the contact details supplied in writing by Natural Resources Wales.
- 4.2.2 A report or reports on the performance of the activities over the previous year shall be submitted to Natural Resources Wales by 31 January (or other date agreed in writing by Natural Resources Wales) each year. The report(s) shall include as a minimum:

- (a) a review of the results of the monitoring and assessment carried out in accordance with the permit including an interpretive review of that data;
 - (b) the annual production / treatment data set out in schedule 4 table S4.2; and
 - (c) the performance parameters set out in schedule 4 table S4.3 using the forms specified in table S4.4 of that schedule.
 - (d) the functioning and monitoring of the incineration plant in a format agreed with Natural Resources Wales. The report shall, as a minimum requirement (as required by Chapter IV of the Industrial Emissions Directive) give an account of the running of the process and the emissions into air and water compared with the emission standards in the IED.
- 4.2.3 Within 28 days of the end of the reporting period the operator shall, unless otherwise agreed in writing by Natural Resources Wales, submit reports of the monitoring and assessment carried out in accordance with the conditions of this permit, as follows:
- (a) in respect of the parameters and emission points specified in schedule 4 table S4.1;
 - (b) for the reporting periods specified in schedule 4 table S4.1 and using the forms specified in schedule 4 table S4.4 ; and
 - (c) giving the information from such results and assessments as may be required by the forms specified in those tables.
- 4.2.4 The operator shall, unless notice under this condition has been served within the preceding four years, submit to Natural Resources Wales, within six months of receipt of a written notice, a report assessing whether there are other appropriate measures that could be taken to prevent, or where that is not practicable, to minimise pollution.
- 4.2.5 Within 1 month of the end of each quarter, the operator shall submit to Natural Resources Wales using the form made available for the purpose, the information specified on the form relating to the site and the waste accepted and removed from it during the previous quarter.

4.3 Notifications

- 4.3.1 (a) In the event that the operation of the activities gives rise to an incident or accident which significantly affects or may significantly affect the environment, the operator must immediately—
- (i) inform Natural Resources Wales,
 - (ii) take the measures necessary to limit the environmental consequences of such an incident or accident, and
 - (iii) take the measures necessary to prevent further possible incidents or accidents;
- (b) in the event of a breach of any permit condition the operator must immediately—
- (i) inform Natural Resources Wales, and
 - (ii) take the measures necessary to ensure that compliance is restored within the shortest possible time;
- (c) in the event of a breach of permit condition which poses an immediate danger to human health or threatens to cause an immediate significant adverse effect on the environment, the operator must immediately suspend the operation of the activities or the relevant part of it until compliance with the permit conditions has been restored.
- 4.3.2 Any information provided under condition 4.3.1 (a)(i), or 4.3.1 (b)(i) where the information relates to the breach of a limit specified in the permit, shall be confirmed by sending the information listed in schedule 5 to this permit within the time period specified in that schedule.

- 4.3.3 Where Natural Resources Wales has requested in writing that it shall be notified when the operator is to undertake monitoring and/or spot sampling, the operator shall inform Natural Resources Wales when the relevant monitoring and/or spot sampling is to take place. The operator shall provide this information to Natural Resources Wales at least 14 days before the date the monitoring is to be undertaken.
- 4.3.4 Natural Resources Wales shall be notified within 14 days of the occurrence of the following matters, except where such disclosure is prohibited by Stock Exchange rules:

Where the operator is a registered company:

- (a) any change in the operator's trading name, registered name or registered office address; and
- (b) any steps taken with a view to the operator going into administration, entering into a company voluntary arrangement or being wound up.

Where the operator is a corporate body other than a registered company:

- (a) any change in the operator's name or address; and
- (b) any steps taken with a view to the dissolution of the operator.

In any other case:

- (a) the death of any of the named operators (where the operator consists of more than one named individual);
- (b) any change in the operator's name(s) or address(es); and
- (c) any steps taken with a view to the operator, or any one of them, going into bankruptcy, entering into a composition or arrangement with creditors, or, in the case of them being in a partnership, dissolving the partnership.

- 4.3.5 Where the operator proposes to make a change in the nature or functioning, or an extension of the activities, which may have consequences for the environment and the change is not otherwise the subject of an application for approval under the Regulations or this permit:
- (a) Natural Resources Wales shall be notified at least 14 days before making the change; and
 - (b) the notification shall contain a description of the proposed change in operation.
- 4.3.6 Natural Resources Wales shall be given at least 14 days notice before implementation of any part of the site closure plan.

4.4 Interpretation

- 4.4.1 In this permit the expressions listed in schedule 6 shall have the meaning given in that schedule.
- 4.4.2 In this permit references to reports and notifications mean written reports and notifications, except where reference is made to notification being made "immediately", in which case it may be provided by telephone.

Schedule 1 - Operations

Table S1.1 activities

Activity reference	Activity listed in Schedule 1 of the EP Regulations	Description of specified activity	Limits of specified activity
AR1	S5.1 A1 (b)	The incineration of non-hazardous waste in a waste incineration plant or waste co-incineration plant with a capacity exceeding 3 tonnes per hour.	<p>The incineration of mixed municipal waste and commercial and industrial waste in a single air cooled moving grate incineration plant.</p> <p>From receipt of waste to emission of exhaust gas and disposal of waste arising.</p> <p>Waste types and quantities as specified in Table S2.2 of this permit.</p>
AR2	S5.4 A1 (b) (iii)	<p>Recovery or a mix of recovery and disposal of non-hazardous waste with a capacity exceeding 75 tonnes per day involving one or more of the following activities, and excluding activities covered by Council Directive 91/271/EEC— treatment of slags and ashes</p> <p>Metal recovery by eddy current separators and magnetic separation. Screening and crushing of recovered ash into aggregates.</p> <p>R4: Recycling/reclamation of metals and metal compounds</p> <p>R5: Recycling/reclamation of other inorganic materials.</p> <p>R13: Storage of waste pending any of the operations numbered R1 to R12 (excluding temporary storage, pending collection, on the site where it is produced)</p>	<p>Receipt of Incinerator Bottom Ash (IBA) from the Parc Adfer Energy Recovery Facility to output from IBA Treatment plant.</p> <p>Waste types as specified in Table S2.3 of this permit.</p> <p>This activity has not been commissioned and the activity shall not be operated until Pre-operational measure 7 (PO7) has been completed as confirmed in writing by Natural Resources Wales</p>

Table S1.1 activities

Activity reference	Activity listed in Schedule 1 of the EP Regulations	Description of specified activity	Limits of specified activity
Directly Associated Activities			
AR3	Electricity Generation	Generation of 20.22 MWe electrical power using a steam turbine from energy recovered from the flue gases.	Electricity to be used on site and for export to the National Grid.
AR4	Discharge to controlled waters at emission point W1	Discharge of site run-off to controlled waters	Drainage of uncontaminated surface water via attenuation pond and oil interceptor.
AR5	Offsite transfer of process water and site drainage unsuitable for discharge to controlled waters at emissions point W1	Water from IBAA storage and other waste handling areas (unless proven by analysis to be uncontaminated in which case it can be discharged to controlled waters at emissions point W1)	Water to be transferred offsite via tanker (unless proven by analysis to be uncontaminated in which case it can be discharged to controlled waters at emissions point W1).
AR6	Schedule 25A – Medium Combustion Plant as detailed in Schedule 8 and Specified Generator that is excluded	Back-up diesel generator for provision of emergency electrical power 1 x 2.47MWth input gas oil fuelled generator (new Medium Combustion Plant)	The use of electricity on-site plant and equipment operation in the event of supply interruption. Operating hours limited as per condition 3.1.5

Table S1.2 Operating techniques

Description	Parts	Date Received
Application	Application form B3 section 3 and 4 and Appendices 5 and 6. Best Available Techniques and Operating Techniques Document – Version 1 (superseded by version 2). Global Warming Potential Assessment (AppendixBATOT2) Acid Gas Abatement Assessment (Appendix BATOT3) NOx Abatement Assessment (BATOT4) H1 Environmental Risk Assessment Permit application Appendix H1-1 Air Quality Dispersion Modelling	Duly Made Date 27/10/15
Additional information	Further information relating to Noise Modelling	20/02/15
Additional information	Further information relating to Noise Modelling	14/05/15
Response to Schedule 5 Notice dated 15/05/15	Parc Adfer Energy Recovery Facility – Response to Schedule 5 Notice. Best Available Techniques and Operating Techniques Document – Version 2.	07/07/15
Response to Improvement Condition IC3 as approved in writing by Natural Resources Wales	As stated in written approval (CAR_NRW0037526 , 10/02/2021) to the response to Improvement Condition IC3.	31/05/2020 (in two emails)

Table S1.2 Operating techniques

Description	Parts	Date Received
Additional information	Confirmation that containment for pollution control will be constructed in accordance Ciria guidance and that the ERF will be served by standby CEMS in case of main CEMS failure	02/09/15
Additional information	Confirmation that water discharged from IBAA storage area will be tankered off site unless proven to be uncontaminated through sampling suite submitted to NRW as part of PO6.	04/09/15
Application	Non-technical summary provided with permit application	23/02/2018
Application	W Permit Change Report - 180122_NTS_APP01_ AAL-09-71-1001-02-Permit Changes Report	23/02/2018
Response to regulation 61(1) Notice – request for information dated 15/06/2021 detailing how the Operator will comply with the BAT conclusions for Waste Incineration, under Directive 2010/75/EU of the European Parliament and of the Council	All	29/03/2022
Additional information received	All	06/10/2022
Other than normal operating conditions (OTNOC) management plan	As stated in written approval to the response to Improvement Condition IC7	Post variation V007 issue
Variation Application PAN-018868	Application form C3 section 3 and referenced supporting information: Best Available Techniques and Operating Techniques Document (410.11035.00011_BATOT) Dated August 2022. Environmental Risk Assessment (410.11035.00011_ERA) Dated August 2022. Atmospheric Dispersion Modelling – Air Emissions Risk Assessment V3 (410.V11035.00011 Rev3) Dated February 2023.	Duly Made Date 13/02/23

Table S1.2A Operating techniques for Medium Combustion Plant as detailed in Schedule 8

Description
Each MCP must be operated in accordance with the manufacturer's instructions and records must be made and retained to demonstrate this
The operator must keep periods of start up and shut down of each MCP as short as possible
There must be no persistent emission of 'dark smoke' as defined in section 3(1) of the Clean Air Act 1993

Table S1.3 Improvement programme requirements

Reference	Requirement	Date
IC1	The Operator shall submit a written report to Natural Resources Wales on the commissioning of the installation. The report shall summarise the environmental performance of the plant as installed against the design	Complete

	parameters set out in the Application and subsequent variation. The report shall also include a review of the performance of the facility against the conditions of this permit and details of procedures developed during commissioning for achieving and demonstrating compliance with permit conditions.	
IC2	The Operator shall carry out checks to verify the residence time, minimum temperature and oxygen content of the exhaust gases in the furnace whilst operating under the anticipated most unfavourable operating conditions. The results shall be submitted in writing to Natural Resources Wales	Complete
IC3	The Operator shall submit a written report to Natural Resources Wales describing the performance and optimisation of the Selective Non Catalytic Reduction (SNCR) system and combustion settings to minimise oxides of nitrogen (NOx) emissions within the emission limit values described in this permit with the minimisation of nitrous oxide emissions. The report shall include an assessment of the level of NOx and N2O emissions that can be achieved under optimum operating conditions. The report shall also provide details of the optimisation (including dosing rates) for the control of acid gases and dioxins	Complete
IC4	The Operator shall submit a written proposal to Natural Resources Wales to carry out tests to determine the size distribution of the particulate matter in the exhaust gas emissions to air from emission point A1, identifying the fractions within the PM10, and PM2.5 ranges. The proposal shall include a timetable for approval by Natural Resources Wales to carry out such tests and produce a report on the results. On receipt of written agreement by Natural Resources Wales to the proposal and the timetable, the Operator shall carry out the tests and submit to Natural Resources Wales a report on the results.	Complete
IC5	The Operator shall submit a written report to Natural Resources Wales on the implementation of its Environmental Management System and the progress made in the accreditation of the system by an external body or if appropriate submit a schedule by which the EMS will be certified.	Complete
IC6	The Operator shall submit a written summary report to Natural Resources Wales to confirm by the results of calibration and verification testing that the performance of Continuous Emission Monitors for parameters as specified in Table S3.1 and Table S3.1(a) complies with the requirements of BS EN 14181, specifically the requirements of QAL1, QAL2 and QAL3.	Complete
IC7	<p>The operator shall submit an Other than normal operating conditions (OTNOC) management plan to Natural Resources Wales for approval.</p> <p>The OTNOC management plan shall be produced in line with all relevant current guidance provided by Natural Resources Wales to the operator and shall consider the requirements of the following BAT conclusions of the Waste Incineration BREF Document (EU 2019):</p> <ul style="list-style-type: none"> • BAT 1 (xxiv) – BAT is also to incorporate the following features in the EMS: <ul style="list-style-type: none"> ◦ (xxiv) for incineration plants, an OTNOC management plan (see BAT 18) • BAT 5 – BAT is to appropriately monitor channelled emissions to air from the incineration plant during OTNOC • BAT 18 – In order to reduce the frequency of the occurrence of OTNOC and to reduce emissions to air and, where relevant, to water from the incineration plant during OTNOC, BAT is to set up and implement a risk based OTNOC management plan as part of the environmental management system (BAT 1) that includes all of the following elements: <ul style="list-style-type: none"> ◦ Identification of potential OTNOC (e.g. failure of equipment critical to the protection of the environment ('critical equipment')), of their root causes and of their potential consequences, and regular review and update of the list of identified OTNOC following the periodic assessment below; ◦ Appropriate design of critical equipment (e.g. compartmentalisation of the bag filter, techniques to 	29 September 2023 or otherwise agreed in writing with Natural Resources Wales

	<p>heat up the flue-gas and obviate the need to bypass the bag filter during start-up and shutdown, etc.);</p> <ul style="list-style-type: none"> ○ Set-up and implementation of preventative maintenance plan for critical equipment (see BAT 1(xii)) ○ Monitoring and recording of emissions during OTNOC and associated circumstances (see BAT 5) ○ Periodic assessment of the emissions during OTNOC (e.g. frequency of events, duration, amount of pollutants emitted) and implementation of corrective actions if necessary. <p>The OTNOC management plan shall be submitted to Natural Resources Wales for approval by the date specified.</p>	
IC8	<p>The operator shall perform a study to determine the extent to which the operation of the current systems in place at the plant to minimise NOx emissions can be further optimised such that emissions are reduced as far as possible below 180 mg/Nm³ as a daily average, without significantly increasing emissions of other pollutants or having a significant negative effect on plant operation, reliability or bottom ash quality. The study shall be based on the results of trials carried out at the installation. A written report of the study shall be submitted to Natural Resources Wales which shall include but not necessarily be limited to the following:</p> <ul style="list-style-type: none"> • A brief description of the currently installed measures at the installation to minimise NOx emissions, including details of how the reagent dosing system responds to emissions monitoring data and historic data which illustrates the current achievable level of daily NOx emissions. • The results of trials conducted to further reduce daily average NOx emissions using currently installed measures, including: <ul style="list-style-type: none"> ○ a description of the parameters that were varied during the trial e.g. ammonia or urea feed rates, physical form of urea injected, air flows, and the range over which they were varied ○ the levels of NOx achieved and associated levels of ammonia and nitrous oxide emissions and reagent consumption ○ observed effects and predicted long-term impacts on plant operation, reliability and maintenance regime ○ any changes to the composition of the bottom ash and boiler ash and the implications of those changes for the ability to process and use the ash, as well as for the pollution potential of the ash both during processing and its subsequent use as a secondary aggregate ○ any other relevant cross-media effects <p>The report shall also include a description of the extent to which current systems in place at the plant to minimise NOx emissions can be optimised on a permanent basis, including justification and an implementation plan where relevant.</p>	<p>30 September 2023 or otherwise as agreed in writing with Natural Resources Wales</p>
IC9	<p>The operator shall carry out a programme of mercury monitoring over a period and frequency agreed with Natural Resources Wales. The operator shall submit a report to Natural Resources Wales with an analysis of whether the waste feed to the plant can be proven to have a low and stable mercury content.</p>	<p>30 September 2023</p> <p>Complete</p>

Table S1.4A Pre-operational measures

Reference	Pre-operational measures	Status
PO1	At least 1 month prior to the commencement of commissioning, the Operator shall submit to Natural Resources Wales for approval a protocol for the sampling and testing of incinerator bottom ash for the purposes of assessing its hazard status. Sampling and testing shall be carried out in accordance with the protocol as approved.	Complete
PO2	At least 2 months prior to the Prior to the commencement of commissioning; the Operator shall provide a written commissioning plan, including timelines for completion, for approval by Natural Resources Wales. The commissioning plan shall include the expected emissions to the environment during the different stages of commissioning, the expected durations of commissioning activities and the actions to be taken to protect the environment and report to Natural Resources Wales in the event that actual emissions exceed expected emissions. Commissioning shall be carried out in accordance with the commissioning plan as approved.	Complete
PO3	At least 1 month prior to the commencement of commissioning, the Operator shall submit a written report to Natural Resources Wales detailing the waste acceptance procedure to be used at the site. The waste acceptance procedure shall include the process and systems by which wastes unsuitable for incineration at the site will be controlled. The procedure shall be implemented in accordance with the written approval from Natural Resources Wales	Complete
PO4	After completion of furnace design and at least three calendar months before any furnace operation; the operator shall submit a written report to Natural Resources Wales of the details of the computational fluid dynamic (CFD) modelling. The report shall demonstrate whether the design combustion conditions comply with the residence time and temperature requirements as defined by the Industrial Emissions Directive	Complete
PO5	At least 4 months prior to operations commencing, the Operator shall submit the written protocol referenced in condition 3.2.4 for the monitoring of soil and groundwater for approval by Natural Resources Wales. The protocol shall demonstrate how the Operator will meet the requirements of Articles 14(1)(b), 14(1)(e) and 16(2) of the IED. The procedure shall be implemented in accordance with the written approval from Natural Resources Wales.	Complete
PO6	At least 2 months prior to operations commencing an assessment is undertaken to derive appropriate limits which will be used to determine if run-off from the IBAA storage area can be considered to be proven to be uncontaminated and thus suitable for discharge from discharge point W1. The assessment will be submitted to NRW and approval obtained from NRW prior to such discharge occurring.	Complete

Table S1.4B Pre-operational measures for future development

Reference	Operation	Pre-operational measures
PO7	Activity reference AR2 in Table S1.1	Prior to the commencement of activity AR2 in Table S1.1 of this permit (which has not yet been commissioned), the Operator shall submit a written report to NRW for written approval that details how the relevant and latest BAT conclusions including both narrative BAT and BAT-AEL for that activity are achieved and for the plant processing capacity which is proposed. NRW will only issue approval to the report when it is satisfied that all BAT requirements have been met.

Schedule 2 - Waste types, raw materials and fuels

Table S2.1 Raw materials and fuels

Raw materials and fuel description	Specification
Fuel Oil	Less than 0.1% sulphur content.

Table S2.2 Permitted waste types and quantities for Energy Recovery plant

Maximum quantity	232,000 tonnes per annum
Waste code	Description
02	Wastes from Agriculture, Horticulture, Aquaculture, Forestry, Hunting and Fishing, Food Preparation and Processing
02 01	wastes from agriculture, horticulture, aquaculture, forestry, hunting and fishing
02 01 03	plant-tissue waste ^(Note 2)
02 01 04	waste plastics (except packaging) ^(Note 1)
02 01 06	animal faeces, urine and manure (including spoiled straw), effluent, collected separately and treated off-site ^(Note 2)
02 01 07	wastes from forestry
02 01 09	agrochemical wastes other than those mentioned in 02 01 08
02 02	wastes from the preparation and processing of meat, fish and other foods of animal origin
02 02 02	animal tissue waste (Catering wastes and former foodstuff only)
02 02 03	materials unsuitable for consumption or processing (Catering wastes and former foodstuff only)
02 02 04	sludges from on-site effluent treatment ^(Note 3)
02 03	wastes from fruit, vegetables, cereals, edible oils, cocoa, coffee, tea and tobacco preparation and processing; conserve production; yeast and yeast extract production, molasses preparation and fermentation
02 03 02	wastes from preserving agents
02 03 03	wastes from solvent extraction
02 03 04	materials unsuitable for consumption or processing ^(Note 2)
02 03 05	sludges from on-site effluent treatment ^(Note 3)
02 04	wastes from sugar processing
02 04 03	sludges from on-site effluent treatment ^(Note 3)
02 05	wastes from the dairy products industry
02 05 01	materials unsuitable for consumption or processing ^(Note 2)
02 05 02	sludges from on-site effluent treatment ^(Note 3)
02 06	wastes from the baking and confectionery industry
02 06 01	materials unsuitable for consumption or processing ^(Note 2)
02 06 02	wastes from preserving agents
02 06 03	sludges from on-site effluent treatment ^(Note 3)
02 07	wastes from the production of alcoholic and non-alcoholic beverages (except coffee, tea and cocoa)
02 07 01	wastes from washing, cleaning and mechanical reduction of raw materials
02 07 02	wastes from spirits distillation
02 07 03	wastes from chemical treatment
02 07 04	materials unsuitable for consumption or processing ^(Note 2)
02 07 05	sludges from on-site effluent treatment ^(Note 3)
03	Wastes from Wood Processing and the Production of Panels and Furniture, Pulp, Paper and Cardboard
03 01	wastes from wood processing and the production of panels and furniture
03 01 01	waste bark and cork
03 01 05	sawdust, shavings, cuttings, wood, particle board and veneer other than those mentioned in 03 01 04 ^(Note 1)
03 03	wastes from pulp, paper and cardboard production and processing
03 03 01	waste bark and wood ^(Note 1)
03 03 07	mechanically separated rejects from pulping of waste paper and cardboard ^(Note 1)

Table S2.2 Permitted waste types and quantities for Energy Recovery plant

Maximum quantity **232,000 tonnes per annum**

Waste code	Description
03 03 08	wastes from sorting of paper and cardboard destined for recycling ^(Note 1)
03 03 10	fibre rejects, fibre, filler and coating-sludges from mechanical separation
03 03 11	sludges from on-site treatment of effluent other than those mentioned in 03 03 10 ^(Note 3)
04	Wastes from the Leather, Fur and Textile Industries
04 01	wastes from the leather and fur industry
04 01 08	waste tanned leather (blue sheetings, shavings, cuttings, buffing dust) containing chromium
04 01 09	wastes from dressing and finishing
04 02	wastes from the textile industry
04 02 09	wastes from composite materials (impregnated textile, elastomer, plastomer)
04 02 10	organic matter from natural products (for example grease, wax) ^(Note 2)
04 02 15	wastes from finishing other than those mentioned in 04 02 14
04 02 17	dyestuffs and pigments other than those mentioned in 04 02 16
04 02 20	sludges from on-site effluent treatment other than those mentioned in 04 02 19 ^(Note 3)
04 02 21	wastes from unprocessed textile fibres
04 02 22	wastes from processed textile fibres
07	Wastes from Organic Chemical Processes
07 02	Wastes from the MFSU of Plastics, Synthetic Rubber and Man-Made Fibres
07 02 12	sludges from on-site effluent treatment other than those mentioned in 07 02 11
07 02 13	waste plastic ^(Note 1)
07 02 15	wastes from additives other than those mentioned in 07 02 14
07 02 17	wastes containing silicones other than those mentioned on 07 02 16*
07 03	Wastes from the MFSU of Organic Dyes and Pigments (except 06 11)
07 03 12	sludges from on-site effluent treatment other than those mentioned in 07 03 11
07 04	Wastes from the MFSU of Organic Plant Protection Products (except 02 01 08 and 02 01 09), Wood Preserving Agents (except 03 02) and other Biocides
07 04 12	sludges from on-site effluent treatment other than those mentioned in 07 04 11
07 05	Wastes from the MFSU of Pharmaceuticals
07 05 12	sludges from on-site effluent treatment other than those mentioned in 07 05 11
07 05 14	solid wastes other than those mentioned in 07 05 13
07 06	Wastes from the MFSU of Fats, Grease, Soaps, Detergents, Disinfectants and Cosmetics
07 06 12	sludges from on-site effluent treatment other than those mentioned in 07 06 11
07 07	Wastes from the MFSU of Fine Chemicals and Chemical Products not otherwise Specified
07 07 12	sludges from on-site effluent treatment other than those mentioned in 07 07 11 ^(Note 3)
08	Wastes from the Manufacture, Formulation, Supply and Use (MFSU) of Coatings (Paints, Varnishes and Vitreous Enamels), Adhesives, Sealants and Printing Inks)
08 01	Wastes from MFSU and Removal of Paint and Varnish
08 01 12	waste paint and varnish other than those mentioned in 08 01 11
08 01 14	sludges from paint or varnish other than those mentioned in 08 01 13
08 01 16	aqueous sludges containing paint or varnish other than those mentioned in 08 01 15
08 01 18	wastes from paint or varnish removal other than those mentioned in 08 01 17
08 03	Wastes from MFSU of Printing Inks
08 03 07	aqueous sludges containing ink
08 03 13	waste ink other than those mentioned in 08 03 12
08 03 15	Ink sludges other than those mentioned in 08 03 14
08 04	Wastes from MFSU of Adhesive and Sealants (including Waterproof Products)
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09
08 04 12	adhesive and sealant sludges other than those mentioned in 08 04 11
08 04 14	aqueous sludges containing adhesives or sealants other than those mentioned in 08 04 13
09	Wastes from the photographic industry
09 01	wastes from the photographic industry
09 01 07	photographic film and paper containing silver or silver compounds

Table S2.2 Permitted waste types and quantities for Energy Recovery plantMaximum quantity **232,000 tonnes per annum**

Waste code	Description
09 01 08	photographic film and paper free of silver or silver compounds
09 01 10	single-use cameras without batteries
12	Wastes from shaping and physical and mechanical surface treatment of metals and plastics
12 01	Wastes from Shaping and Physical and Mechanical Surface Treatment of Metals and Plastics
12 01 05	plastics shavings and turnings
12 01 15	machining sludges other than those mentioned in 12 01 14
12 01 17	waste blasting material other than those mentioned in 12 01 16
12 01 21	spent grinding bodies and grinding materials other than those mentioned in 12 01 20
15	Waste Packaging; Absorbents, Wiping Cloths, Filter Materials and Protective Clothing not otherwise specified
15 01	packaging (including separately collected municipal packaging waste)
15 01 01	paper and cardboard packaging ^(Note 1)
15 01 02	plastic packaging ^(Note 1)
15 01 03	wooden packaging ^(Note 1)
15 01 04	metallic packaging ^(Note 1)
15 01 05	composite packaging ^(Note 1)
15 01 06	mixed packaging ^(Note 1)
15 01 07	glass packaging ^(Note 1)
15 01 09	textile packaging ^(Note 1)
15 02	absorbents, filter materials, wiping cloths and protective clothing
15 02 03	absorbents, filter materials, wiping cloths and protective clothing other than those mentioned in 15 02 02
16	Wastes not otherwise specified in the list
16 01	end-of-life vehicles from different means of transport (including off-road machinery) and wastes from dismantling of end-of-life vehicles and vehicle maintenance (except 13, 14, 16 06 and 16 08)
16 01 03	end-of-life tyres ^(Note 1)
16 01 12	brake pads other than those mentioned in 16 01 11
16 01 19	Plastic ^(Note 1)
16 01 22	components not otherwise specified
16 02	wastes from electrical and electronic equipment
16 02 16	components removed from discarded equipment other than those mentioned in 16 02 15
16 03	off-specification batches and unused products
16 03 04	inorganic wastes other than those mentioned in 16 03 03
16 03 06	organic wastes other than those mentioned in 16 03 05
16 06	batteries and accumulators
16 06 04	alkaline batteries (except 16 06 03) ^(Note 1)
16 06 05	other batteries and accumulators ^(Note 1)
17	Construction and Demolition Wastes (including excavated soil from contaminated sites)
17 02	wood, glass and plastic
17 02 01	Wood ^(Note 1)
17 02 03	Plastic ^(Note 1)
17 03	Bituminous Mixtures, Coal Tar and Tarred Products
17 03 02	bituminous mixtures other than those mentioned in 17 03 01
17 06	insulation materials and asbestos-containing construction materials
17 06 04	insulation materials other than those mentioned in 17 06 01 and 17 06 03
17 09	other construction and demolition wastes
17 09 04	mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03 ^(Note 1)
18	Wastes from Human and Animal Health Care and/or Related Research (except kitchen and restaurant wastes not arising from immediate health care)

Table S2.2 Permitted waste types and quantities for Energy Recovery plant

Maximum quantity **232,000 tonnes per annum**

Waste code	Description
18 01	wastes from natal care, diagnosis, treatment or prevention of disease in humans
18 01 04	wastes whose collection and disposal is not subject to special requirements in order to prevent infection (for example dressings, plaster casts, linen, disposable clothing, diapers)
18 01 07	chemicals other than those mentioned in 18 01 06
18 02	wastes from research, diagnosis, treatment or prevention of disease involving animals
18 02 03	wastes whose collection and disposal is not subject to special requirements in order to prevent infection
18 02	Wastes from Research, Diagnosis, Treatment or Prevention of Disease involving Animals
18 02 06	chemicals other than those mentioned in 18 02 05
18 02 08	medicines other than those mentioned in 18 02 07
19	Wastes from Waste Management Facilities, Off-site Waste Water Treatment Plants and the Preparation of Water Intended for Human Consumption and Water for Industrial Use
19 02	wastes from physico/chemical treatments of waste (including dechromatation, decyanidation, neutralisation)
19 02 03	premixed wastes composed only of non-hazardous wastes
19 02 06	sludges from physico/chemical treatment other than those mentioned in 19 02 05
19 02 10	combustible wastes other than those mentioned in 19 02 08 and 19 02 09
19 03	stabilised/solidified wastes
19 03 05	stabilised wastes other than those mentioned in 19 03 04
19 03 07	solidified wastes other than those mentioned in 19 03 06
19 05	wastes from aerobic treatment of solid wastes
19 05 01	non-composted fraction of municipal and similar wastes
19 05 02	non-composted fraction of animal and vegetable waste
19 05 03	off-specification compost
19 06	wastes from anaerobic treatment of waste
19 06 04	digestate from anaerobic treatment of municipal waste ^(Note 3)
19 06 06	digestate from anaerobic treatment of animal and vegetable waste ^(Note 3)
19 08	Wastes from Waste Water Treatment Plants not otherwise specified
19 08 01	Screenings ^(Note 2)
19 08 05	sludges from treatment of urban waste water ^(Note 2) ^(Note 3)
19 08 09	grease and oil mixture from oil/water separation containing edible oil and fats
19 08 12	sludges from biological treatment of industrial waste water other than those mentioned in 19 08 11 ^(Note 2) ^(Note 3)
19 08 14	sludges from other treatment of industrial waste water other than those mentioned in 19 08 13 ^(Note 2) ^(Note 3)
19 09	Wastes from the Preparation of Water Intended for Human Consumption or Water for Industrial Use
19 09 01	solid waste from primary filtration and screenings
19 09 04	spent activated carbon
19 10	Wastes from Shredding of Metal-Containing Wastes
19 10 04	fluff-light fraction and dust other than those mentioned in 19 10 03
19 11	Wastes from Oil Regeneration
19 11 06	sludges from on-site effluent treatment other than those mentioned in 19 11 05
19 12	wastes from the mechanical treatment of waste (for example sorting, crushing, compacting, pelletising) not otherwise specified
19 12 01	paper and cardboard ^(Note 1)
19 12 02	ferrous metal ^(Note 1)
19 12 03	non-ferrous metal ^(Note 1)
19 12 04	plastic and rubber ^(Note 1)
19 12 05	Glass ^(Note 1)
19 12 07	wood other than that mentioned in 19 12 06 ^(Note 1)
19 12 08	Textiles ^(Note 1)
19 12 09	minerals (for example sand, stones) ^(Note 1)

Table S2.2 Permitted waste types and quantities for Energy Recovery plant

Maximum quantity **232,000 tonnes per annum**

Waste code	Description
19 12 10	combustible waste (refuse derived fuel)
19 12 12	other wastes (including mixtures of materials) from mechanical treatment of wastes other than those mentioned in 19 12 11
19 13	Wastes from Soil and Groundwater Remediation
19 13 02	solid wastes from soil remediation other than those mentioned in 19 13 01 ^(Note 3)
19 13 04	sludges from soil remediation other than those mentioned in 19 13 03 ^(Note 3)
20	Municipal Wastes (Household waste and similar commercial, industrial and institutional wastes) Including separately collected fractions
20 01	separately collected fractions (except 15 01)
20 01 01	paper and cardboard ^(Note 1)
20 01 08	biodegradable kitchen and canteen waste ^(Note 1)
20 01 10	Clothes ^(Note 1)
20 01 11	Textiles ^(Note 1)
20 01 25	edible oil and fat ^{(Note 2) (Note 3)}
20 01 28	paint, inks, adhesives and resins other than those mentioned in 20 01 27
20 01 30	detergents other than those mentioned in 20 01 29
20 01 32	medicines other than those mentioned in 20 01 31
20 01 34	batteries and accumulators other than those mentioned in 20 01 33
20 01 36	discarded electrical and electronic equipment other than those mentioned in 20 01 21, 20 01 23 and 20 01 35
20 01 38	wood other than that mentioned in 20 01 37 ^(Note 1)
20 01 39	Plastics ^(Note 1)
20 01 41	wastes from chimney sweeping
20 01 99	dog faeces from collection bins domestic type incontinence wastes nappy wastes from nurseries
20 02	garden and park wastes (including cemetery waste)
20 02 01	biodegradable waste ^{(Note 2) (Note 3)}
20 02 03	other non-biodegradable wastes
20 03	other municipal wastes
20 03 01	mixed municipal waste
20 03 02	waste from markets
20 03 03	street-cleaning residues
20 03 06	waste from sewage cleaning
20 03 07	bulky waste
20 03 99	Beach Cleaning Residues

Exclusions

Note 1. It having been separately collected for recycling, it is subsequently unsuitable for recovery by recycling.

Note 2. Only where anaerobic digestion, composting or similar treatment is not a practical option.

Note 3. Only where the waste stream is not practical for recovery through agricultural or horticultural benefit or other similar means, and has a solid phase composition (no liquid phase wastes).

Table S2.3 Permitted waste types and quantities for bottom ash treatment plant

Maximum quantity 200,000 tonnes per year

Waste Code	Description
19	Wastes from waste management facilities, off-site waste water treatment plants and preparation of water intended for human consumption/industrial use
19 01	Wastes from incineration of pyrolysis of waste
19 01 12	Bottom ash and slag other than those mentioned in 19 01 11.

Schedule 3 – Emissions and monitoring

Table S3.1 Point source emissions to air – emission limits and monitoring requirements

Emission point ref. & location	Source	Parameter	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard or method
A1 [Point A1 as shown on site plan in Schedule 7]	Incineration gases via Flue Gas Treatment Plant	Particulate matter	30 mg/Nm ³	½-hr average	Continuous	EN 14181 and EN 17255 and EN 13284
			5 mg/Nm ³	daily average		
		Hydrogen chloride	60 mg/Nm ³	½-hr average	Continuous	EN 14181 and EN 17255
			8 mg/Nm ³	daily average	Continuous	
		Hydrogen fluoride	1 mg/Nm ³	Average of three consecutive measurements of at least 30 minutes each	Bi-annually	CEN TS 17340
		Sulphur dioxide	200 mg/Nm ³	½-hr average	Continuous	EN 14181 and EN 17255
			40 mg/Nm ³	daily average	Continuous	
		Oxides of nitrogen (NO and NO ₂ expressed as NO ₂)	400 mg/Nm ³	½-hr average	Continuous	EN 14181 and EN 17255
			180 mg/Nm ³	daily average	Continuous	
		Carbon monoxide	150 mg/Nm ³	95% of all 10-minute averages in a calendar day	Continuous	EN 14181 and EN 17255
				daily average		
		Total Organic Carbon (TOC)	20 mg/Nm ³	½-hr average	Continuous	EN 14181 and EN 17255
			10 mg/Nm ³	daily average		
		Ammonia (NH ₃)	10 mg/Nm ³	daily average	Continuous	EN 14181 and EN 17255
		Nitrous Oxide (N ₂ O)	No limit set	½-hr average and daily average	Continuous	EN 14181 and EN 17255
		Cadmium & thallium and their compounds (total)	0.02 mg/Nm ³	Average of three consecutive measurements of at least 30 minutes each	Bi-annually	EN 14385

Table S3.1 Point source emissions to air – emission limits and monitoring requirements

Emission point ref. & location	Source	Parameter	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard or method
		Sb, As, Pb, Cr, Co, Cu, Mn, Ni and V and their compounds (total)	0.3 mg/Nm ³	Average of three consecutive measurements of at least 30 minutes each	Bi-annually	EN 14385
		Mercury and its compounds	0.02 mg/Nm ³	Average of three consecutive measurements of at least 30 minutes each	Bi-annually unless otherwise agreed in writing with Natural Resources Wales	EN 13211
			0.02 mg/Nm ³	Daily average	Continuous unless otherwise agreed in writing with Natural Resources Wales ¹	EN 14181 and EN 17255 and EN14884
		Dioxins / furans (I-TEQ)	0.06 ng/Nm ³	Periodic over minimum 6 hours, maximum 8 hour period	Bi-annually	Relevant parts of EN 1948
			0.08 ng/Nm ³	Value over sampling period of 2 to 4 weeks for long term sampling	Monthly unless otherwise agreed in writing with Natural Resource Wales ²	CEN TS 1948-5
		Dioxin-like PCBs (WHO-TEQ Humans / Mammals, Fish, Birds)	No limit set	Periodic over minimum 6 hours, maximum 8 hour period	Bi-annually	Relevant parts of EN 1948
		Dioxins / furans (WHO-TEQ Humans / Mammals, Fish, Birds)	No limit set	Periodic over minimum 6 hours, maximum 8 hour period	Bi-annually	Relevant parts of EN 1948
		Polybrominated dibenzo- dioxins and furans	No limit set	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually	Method based on procedural requirements of EN 1948

Table S3.1 Point source emissions to air – emission limits and monitoring requirements

Emission point ref. & location	Source	Parameter	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard or method
		Specific individual poly-cyclic aromatic hydrocarbons (PAHs), as specified in Schedule 6.	No limit set	periodic over minimum 6 hours, maximum 8 hour period	Bi-annually	BS ISO 11338 Parts 1 and 2.
		Carbon dioxide	No limit set	½-hr average and daily average	Continuous	EN 14181 and EN 17255
		Exhaust gas temperature	No limit set	½-hr average and daily average	Continuous	Traceable to national standards
		Exhaust gas pressure	No limit set	½-hr average and daily average	Continuous	Traceable to national standards
		Exhaust gas flow	No limit set	½-hr average and daily average	Continuous	EN 16911-2
		Exhaust gas oxygen content	No limit set	½-hr average and daily average	Continuous	EN 14181 and EN 17255
		Exhaust gas water vapour content	No limit set	½-hr average and daily average	Continuous	EN 14181 and EN 17255
A2 [Point A2 as shown on site plan in Schedule 7]	Emergency generator	Carbon monoxide	No limit set	In line with web guide: Monitoring stack emissions: low risk MCPs and specified generators	After 3 times the maximum average annual operating hours have elapsed and no less frequent than every 5 years	In line with web guide: Monitoring stack emissions: low risk MCPs and specified generators

Note 1: Continuous monitoring does not apply for plants incinerating wastes with a proven low and stable mercury content

Note 2: Long term sampling does not apply if the emission levels are proven to be sufficiently stable

Table S3.1(a) Point source emissions to air during abnormal operation of incineration plant– emission limits and monitoring requirements

Emission point ref. & location	Source	Parameter	Limit (including unit)	Reference period	Monitoring frequency	Monitoring standard or method
A1 [Point A1 as shown on site plan in Schedule 7]	Incineration gases via Flue Gas Treatment Plant	Particulate matter	150 mg/Nm ³	½-hr average	Continuous	EN 14181 and EN 17255 and EN13284 during abatement plant failure
						Or
						Alternative surrogate as specified in the application or as agreed in writing with Natural Resources Wales during failure of the continuous emission monitor
		Carbon monoxide	150 mg/Nm ³	95% of all 10-minute averages in a calendar day	Continuous	EN 14181 and EN 17255 during abatement plant failure
A2 [Point A2 as shown on site plan in Schedule 7]	Emergency generator	Total Organic Carbon (TOC)	20 mg/Nm ³	½-hr average	Continuous	Or
						Alternative surrogate as specified in the application or as agreed in writing with Natural Resources Wales during failure of the continuous emission monitor
		Carbon monoxide	No limit set	In line with web guide: Monitoring stack emissions: low risk MCPs and specified generators	After 3 times the maximum average annual operating hours have elapsed and no less frequent than every 5 years	In line with web guide: Monitoring stack emissions: low risk MCPs and specified generators

Table S3.2 Point Source emissions to water (other than sewer) and land – emission limits and monitoring requirements

Emission point ref. & location	Source	Parameter	Limit (incl. unit)	Reference Period	Monitoring frequency	Monitoring standard or method
W1 [Point W1 as referenced on site plan in Schedule 7]	Drainage of uncontaminated surface water via attenuation pond and oil interceptor	Visible solids, oil or grease	Discharge to be free of any visible solids, oil or grease	Instantaneous	Weekly	Visual check Permanent sampling access not required.

Table S3.3 Process monitoring requirements

Location or description of point of measurement	Parameter	Monitoring frequency	Monitoring standard or method	Other specifications
Below the boiler roof in the first boiler pass	Temperature (° C)	Continuous	Traceable to national standards	As agreed in writing with Natural Resources Wales.
Bag Filter	Pressure drop	Continuous	Not applicable	
Incineration plant	Gross electrical efficiency ^[1] or Gross energy efficiency ^[2]	within 6 months of any modification that significantly affects energy efficiency	Performance test at full load	Recovery with a high level of energy efficiency as required by permit condition 1.2.1(a) and as may be agreed in writing with NRW. In any case of no lower than: <ul style="list-style-type: none"> • 20 % for Gross electrical efficiency^[1] • 72 % for Gross energy efficiency^[2]

Note [1]: Gross electrical efficiency only applies to plants or parts of plants producing electricity using a condensing turbine

Note [2]: Gross energy efficiency only applies to plants or parts of plants producing only heat or producing electricity using a back-pressure turbine and heat with the steam leaving the turbine

Table S3.4 Residue quality

Emission point reference or source or description of point of measurement	Parameter	Limit (including unit)	Monitoring frequency	Monitoring standard or method*	Other specification
Bottom Ash (including boiler ash)	TOC	3%	Quarterly	BS EN 14899 and either BS EN 13137 or BS EN 15936	Environment Agency Guidance, 'TGN M4 – Guidelines for Ash Sampling and Analysis'.
	Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs.	No limit set	Quarterly	Environment Agency Guidance, 'TGN M4 – Guidelines for Ash Sampling and Analysis'	
	Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions	No limit set	Before use of a new disposal or recycling route		
APC Residues	Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs.	No limit set	Quarterly		
	Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions	No limit set	Before use of a new disposal or recycling route		

*Or other equivalent standard as agreed in writing with Natural Resources Wales

Schedule 4 - Reporting

Parameters, for which reports shall be made, in accordance with conditions of this permit, are listed below.

Table S4.1 Reporting of monitoring data

Parameter	Emission or monitoring point/reference	Reporting period	Period begins
Emissions to air Parameters as required by condition 3.6.1.	A1	Quarterly	1 January, 1 April, 1 July & 1 October
Emissions to air Parameters as required by condition 3.6.1	A2	After 3 times the maximum average annual operating hours have elapsed and no less frequent than every 5 years	1 January
TOC Parameter as required by condition 3.6.1	Bottom Ash (including boiler ash)	Quarterly	1 January, 1 April, 1 July & 1 October
Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs Parameters as required by condition 3.6.1			
Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions Parameters as required by condition 3.6.1		Before use of a new disposal or recycling route	-
Metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) and their compounds, dioxins/furans and dioxin-like PCBs Parameters as required by condition 3.6.1	APC residues	Quarterly	1 January, 1 April, 1 July & 1 October
Total soluble fraction and metals (Antimony, Cadmium, Thallium, Mercury, Lead, Chromium, Copper, Manganese, Nickel, Arsenic, Cobalt, Vanadium, Zinc) soluble fractions Parameters as required by condition 3.6.1		Before use of a new disposal or recycling route	-
Functioning and monitoring of the incineration plant as required by condition 4.2.2	-	Annually	1 January

Table S4.2: Annual production/treatment

Parameter	Units
Total municipal waste incinerated	tonnes
Total commercial waste incinerated	tonnes
Electrical energy produced	KWh / MWh
Thermal energy produced e.g. steam for export	KWh / MWh
Electrical energy exported	KWh / MWh
Electrical energy used on installation	KWh / MWh
Waste heat utilised by the installation	KWh / MWh
Mass of Incinerator Bottom Ash Aggregate produced	Kgs / tonne of bottom ash treated

Table S4.3 Performance parameters

Parameter	Frequency of assessment	Units
Annual report as required by condition 4.2.2	Annually	-
Electrical energy exported, imported and used at the installation	Quarterly	KWh/tonne of waste (co)incinerated
Fuel oil consumption		Kg/tonne of waste incinerated
Bottom Ash residue (including Boiler Ash)		Route, tonnes and tonnes/tonne of waste incinerated
APC residue		Route, tonnes and tonnes/tonne of waste incinerated
Urea consumption		Kg / tonne of waste incinerated
Activated Carbon consumption		Kg / tonne of waste incinerated
Lime consumption		Kg / tonne of waste incinerated
Water Consumption		m ³ / tonne of waste incinerated
Periods of abnormal operation		No. of occasions and cumulative hours for calendar year

Table S4.4 Reporting forms

Media/parameter	Reporting format	Date of form(s)
Annual report required by condition 4.2.2	No specific format specified	N/A
Air	For CEMS monitoring data - In the format indicated in forms air 1-16 as a direct output from Data Acquisition and Handling system. For other monitoring results – Form air 17. Or other forms as agreed in writing by Natural Resources Wales	03/12/23
Residue Quality	Form residue 1 and 2 or other forms as agreed in writing by Natural Resources Wales	03/12/23
Water usage	Form water usage 1 or other form as agreed in writing by Natural Resources Wales	03/12/23

Table S4.4 Reporting forms

Media/parameter	Reporting format	Date of form(s)
Energy usage	Form energy 1 or other form as agreed in writing by Natural Resources Wales	03/12/23
Other performance indicators	Form performance 1 or other form as agreed in writing by Natural Resources Wales	03/12/23
Waste Subject to Conditions 4.2.5	Waste tonnage return form from Natural Resources Wales or other form as agreed in writing by Natural Resources Wales	-

Schedule 5 - Notification

These pages outline the information that the operator must provide.

Units of measurement used in information supplied under Part A and B requirements shall be appropriate to the circumstances of the emission. Where appropriate, a comparison should be made of actual emissions and authorised emission limits.

If any information is considered commercially confidential, it should be separated from non-confidential information, supplied on a separate sheet and accompanied by an application for commercial confidentiality under the provisions of the EP Regulations.

Part A

Permit Number	AB3092CV
Name of operator	
Location of Facility	Parc Adfer Energy Recovery Facility, Deeside Industrial Park, CH5 2LL
Time and date of the detection	

(a) Notification requirements for any activity that gives rise to an incident or accident which significantly affects or may significantly affect the environment

To be notified within 24 hours of detection

Date and time of the event	
Reference or description of the location of the event	
Description of where any release into the environment took place	
Substances(s) potentially released	
Best estimate of the quantity or rate of release of substances	
Measures taken, or intended to be taken, to stop any emission	
Description of the failure or accident.	

(b) Notification requirements for the breach of a permit condition

To be notified within 24 hours of detection unless otherwise specified below

Emission point reference/ source	
Parameter(s)	
Limit	
Measured value and uncertainty	
Date and time of monitoring	
Measures taken, or intended to be taken, to stop the emission	

Time periods for notification following detection of a breach of a limit

Parameter	Notification period

(c) In the event of a breach of permit condition which poses an immediate danger to human health or threatens to cause an immediate significant adverse effect on the environment:

To be notified within 24 hours of detection

Description of where the effect on the environment was detected	
Substances(s) detected	
Concentrations of substances detected	
Date of monitoring/sampling	

Part B - to be submitted as soon as practicable

Any more accurate information on the matters for notification under Part A.	
Measures taken, or intended to be taken, to prevent a recurrence of the incident	
Measures taken, or intended to be taken, to rectify, limit or prevent any pollution of the environment which has been or may be caused by the emission	
The dates of any unauthorised emissions from the facility in the preceding 24 months.	

Name*	
Post	
Signature	
Date	

* authorised to sign on behalf of the operator

Schedule 6 - Interpretation

“abatement equipment” means that equipment dedicated to the removal of polluting substances from releases from the installation to air or water media.

“*abnormal operation*” means: any technically unavoidable stoppages, disturbances, or failures of the plant or the measurement devices. Abnormal operation starts as defined in condition 2.3.11 and ends as defined in condition 2.3.12. Abnormal operation is limited to 4 hours for a single occurrence and a total of 60 hours per year per line.

“*accident*” means an accident that may result in pollution.

“*APC residues*” means air pollution control residues

“*application*” means the application for this permit, together with any additional information supplied by the operator as part of the application and any response to a notice served under Schedule 5 to the EP Regulations.

“*authorised officer*” means any person authorised by Natural Resources Wales under section 108(1) of The Environment Act 1995 to exercise, in accordance with the terms of any such authorisation, any power specified in section 108(4) of that Act.

“*BAT conclusions*” means Commission Implementing Decision (EU) 2019/2010 of 12 November 2019 establishing the best available techniques (BAT) conclusions, under Directive 2010/75/EU of the European Parliament and of the Council, for Waste Incineration

“*bi-annually*” and “*bi-annual*” means twice per year with at least five months between tests;

“*bottom ash*” means transported by the grate

“*CEM*” means Continuous emission monitor

“*CEN*” means *Comité Européen de Normalisation*

“*Commissioning*” means testing of the new incineration plant that involves any operation of the furnace or as agreed with Natural Resources Wales.

“*Completion of commissioning*” means the date on which the listed activity is first operated

“*DAHS*” means data handling and acquisition system and includes software and hardware

“*Daily average emissions limit value*” means ‘the average of at least 43 valid half hourly averages or for CO the average of at least 43 valid half hourly averages or 129 valid 10 minute averages’

“*dioxin and furans*” means polychlorinated dibenzo-p-dioxins and polychlorinated dibenzofurans.

“*disposal*” or “*D*” means any of the operations provided for in Annex I to Directive 2008/98/EC of the European Parliament and of the Council on waste.

“*emissions to land*” includes emissions to groundwater.

“*EP Regulations*” means The Environmental Permitting (England and Wales) Regulations SI 2016 No.1154 and words and expressions used in this permit which are also used in the Regulations have the same meanings as in those Regulations.

“*emissions of substances not controlled by emission limits*” means emissions of substances to air, water or land from the activities, either from the emission points specified in schedule 3 or from other localised or diffuse sources, which are not controlled by an emission or background concentration limit.

“*gas oil*” in relation to the Medium Combustion Plant includes diesel and is defined in Article 3(19) of the MCPD.

“*Gas oil*” means low sulphur content hydrocarbon fuel oil, not arising as waste from some other process, used for furnace support and during start up procedures.

“*groundwater*” means all water, which is below the surface of the ground in the saturation zone and in direct contact with the ground or subsoil.

“*hazardous waste*” has the meaning given in the Hazardous Waste (Wales) Regulations 2005 (as amended)

“*hazardous substance*” means a substance classified as hazardous as a consequence of fulfilling the criteria laid down in parts 2 to 5 of Annex I to Regulation (EC) No 1272/2008

“*Incineration line*” means all of the incineration equipment related to a common discharge to air location.

“*Industrial Emissions Directive*” means DIRECTIVE 2010/75/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 24 November 2010 on industrial emissions

“*ISO*” means International Standards Organisation.

“*limited operating hours MCP*” means an MCP that meets the requirements of paragraph 8 of Part 2 of Schedule 25A of the EP Regulations.

“*List of Wastes*” means the list of wastes established by Commission Decision 2000/532/EC replacing Decision 94/3/EC establishing a list of wastes pursuant to Article 1(a) of Council Directive 75/442/EEC on waste and Council Decision 94/904/EC establishing a list of hazardous waste pursuant to Article 1(4) of Council Directive 91/689/EEC on hazardous waste, as amended from time to time

“*LOI*” means loss on ignition a technique used to determine the combustible material by heating the ash residue to a high temperature

“*low and stable mercury content*” can be demonstrated using the latest version of the UK WI BREF Mercury monitoring protocol (V0.28 or as updated) or an appropriate alternative method as agreed in writing with Natural Resources Wales.

“*MCERTS*” means the Environment Agency’s Monitoring Certification Scheme.

“*medium combustion plant*” or “*MCP*” means a combustion plant with a rated thermal input equal to or greater than 1 MW but less than 50 MW.

“*Medium Combustion Plant Directive*” or “*MCPD*” means Directive 2015/2193/EU of the European Parliament and of the Council on the limitation of emissions of certain pollutants into the air from medium combustion plants.

“*new MCP*” means an MCP first put into operation on or after 20/12/2018.

“*normal operation*” consists of any operation of the plant other than that as defined as “*OTNOC*” unless otherwise agreed in writing with Natural Resources Wales

“*operating hours*” in relating to the MCP means the time, expressed in hours, during which a combustion plant is operating and discharging emissions into the air, excluding start-up and shut-down periods.

“*OTNOC*” means other than normal operating conditions. OTNOC consists of start-up, shut-down and abnormal operation only, unless additional definitions are agreed in writing with Natural Resources Wales

“*PAH*” means Poly-cyclic aromatic hydrocarbon, and comprises Anthanthrene, Benzo[a]anthracene, Benzo[b]fluoranthene, Benzo[k]fluoranthene, Benzo[b]naph(2,1-d)thiophene, Benzo[c]phenanthrene, Benzo[ghi]perylene, Benzo[a]pyrene, Cholanthrene, Chrysene, Cyclopenta[c,d]pyrene, Dibenzo[ah]anthracene, Dibenzo[a,i]pyrene, Fluoranthene, Indo[1,2,3-cd]pyrene, Naphthalene

“*PCB*” means Polychlorinated Biphenyl. Dioxin-like PCBs are the non-ortho and mono-ortho PCBs listed in the table below.

“*Pests*” means Birds, Vermin and Insects.

“*quarter*” means a calendar year quarter commencing on 1 January, 1 April, 1 July or 1 October.

“*quarterly*” for reporting/sampling means after/during each 3 month period, January to March; April to June; July to September and October to December and, when sampling, with at least 2 months between each sampling date.

“*recovery*” or “*R*” means any of the operations provided for in Annex II to Directive 2008/98/EC of the European Parliament and of the Council on waste.

“*shut down*” is any period where the plant is being returned to a non-operational state and there is no waste being burned as agreed in writing with Natural Resources Wales.

“*specified generator*” has the meaning given in paragraph 2(1) of Schedule 25B of The EP Regulations.

“*start up*” is any period, where the plant has been non-operational, after igniting the auxiliary burner until waste has been fed to the plant in sufficient quantity to cover the grate and to initiate steady-state conditions as agreed in writing with Natural Resources Wales.

“sufficiently stable” in respect of dioxins/furans emissions can be demonstrated using the latest version of the UK WI BREF PCDD/F monitoring protocol (V0.28 or as updated) or an appropriate alternative method as agreed in writing with Natural Resources Wales.

“TOC” means Total Organic Carbon. In respect of releases to air, this means the gaseous and vaporous organic substances, expressed as TOC. In respect of Bottom Ash, this means the total carbon content of all organic species present in the ash (excluding carbon in elemental form).

“Waste code” means the six digit code referable to a type of waste in accordance with the list of wastes established by Commission Decision 2000/532/EC as amended from time to time (the ‘List of Wastes Decision’) and in relation to hazardous waste, includes the asterisk.

“Waste Framework Directive” or “WFD” means Waste Framework Directive 2008/98/EC of the European Parliament and of the Council on waste

“year” means calendar year ending 31 December.

Where a minimum limit is set for any emission parameter, for example pH, reference to exceeding the limit shall mean that the parameter shall not be less than that limit.

Unless otherwise stated, any references in this permit to concentrations of substances in emissions into air means:

- (a) in relation to emissions from combustion processes (excluding incineration and co-incineration), the concentration in dry air at a temperature of 273K, at a pressure of 101.3 kPa and with an oxygen content of 3 % dry for liquid and gaseous fuels, 6% dry for solid fuels; and/or
- (b) in relation to emissions from non-combustion sources, the concentration at a temperature of 273K and at a pressure of 101.3 kPa, with no correction for water vapour content.
- (c) in relation to gases from incineration plants other than those burning waste oil, the concentration in dry air at a temperature of 273K, at a pressure of 101.3 kPa and with an oxygen content of 11% dry

For dioxins/furans and dioxin-like PCBs the determination of the toxic equivalence concentration (I-TEQ, & WHO-TEQ for dioxins/furans, WHO-TEQ for dioxin-like PCBs) stated as a release limit and/ or reporting requirement, the mass concentrations of the following congeners have to be multiplied with their respective toxic equivalence factors before summing. When reporting on measurements of dioxins/furans and dioxin-like PCBs, the toxic equivalence concentrations should be reported as a range based on: all congeners less than the detection limit assumed to be zero as a minimum, and all congeners less than the detection limit assumed to be at the detection limit as a maximum. However the minimum value should be used when assessing compliance with the emission limit value in table S3.1.

TEF schemes for dioxins and furans				
Congener	I-TEF	WHO-TEF		
	1990	2005	1997/8	
		Humans / Mammals	Fish	Birds
Dioxins				
2,3,7,8-TCDD	1	1	1	1
1,2,3,7,8-PeCDD	0.5	1	1	1
1,2,3,4,7,8-HxCDD	0.1	0.1	0.5	0.05
1,2,3,6,7,8-HxCDD	0.1	0.1	0.01	0.01
1,2,3,7,8,9-HxCDD	0.1	0.1	0.01	0.1
1,2,3,4,6,7,8-HpCDD	0.01	0.01	0.001	<0.001
OCDD	0.001	0.0003	-	-
Furans				
2,3,7,8-TCDF	0.1	0.1	0.05	1
1,2,3,7,8-PeCDF	0.05	0.03	0.05	0.1
2,3,4,7,8-PeCDF	0.5	0.3	0.5	1
1,2,3,4,7,8-HxCDF	0.1	0.1	0.1	0.1
1,2,3,7,8,9-HxCDF	0.1	0.1	0.1	0.1

TEF schemes for dioxins and furans				
Congener	I-TEF	WHO-TEF		
	1990	2005	1997/8	
1,2,3,6,7,8-HxCDF	0.1	0.1	0.1	0.1
2,3,4,6,7,8-HxCDF	0.1	0.1	0.1	0.1
1,2,3,4,6,7,8_HpCDF	0.01	0.01	0.01	0.01
1,2,3,4,7,8,9-HpCDF	0.01	0.01	0.01	0.01
OCDF	0.001	0.0003	0.0001	0.0001

TEF schemes for dioxin-like PCBs			
Congener	WHO-TEF		
	2005	1997/8	
	Humans / mammals	Fish	Birds
Non-ortho PCBs			
3,4,4',5-TCB (81)	0.0001	0.0005	0.1
3,3',4,4'-TCB (77)	0.0003	0.0001	0.05
3,3',4,4',5 - PeCB (126)	0.1	0.005	0.1
3,3',4,4',5,5'-HxCB(169)	0.03	0.00005	0.001
Mono-ortho PCBs			
2,3,3',4,4'-PeCB (105)	0.00003	<0.000005	0.0001
2,3,4,4',5-PeCB (114)	0.00003	<0.000005	0.0001
2,3',4,4',5-PeCB (118)	0.00003	<0.000005	0.00001
2',3,4,4',5-PeCB (123)	0.00003	<0.000005	0.00001
2,3,3',4,4',5-HxCB (156)	0.00003	<0.000005	0.0001
2,3,3',4,4',5'-HxCB (157)	0.00003	<0.000005	0.0001
2,3',4,4',5,5'-HxCB (167)	0.00003	<0.000005	0.00001
2,3,3',4,4',5,5'-HpCB (189)	0.00003	<0.000005	0.00001

Schedule 7 - Site plan



© Crown Copyright and database right [2022]. Ordnance Survey licence number 100019741.

Schedule 8 – Annex I of MCPD

1. Rated thermal input (MW) of the medium combustion plant.	2.47 MWth input
2. Type of the medium combustion plant (diesel engine, gas turbine, dual fuel engine, other engine or other medium combustion plant).	Diesel engine
3. Type and share of fuels used according to the fuel categories laid down in Annex II.	Gas oil, 100%
4. Date of the start of the operation of the medium combustion plant or, where the exact date of the start of the operation is unknown, proof of the fact that the operation started before 20 December 2018.	19 December 2019
5. Sector of activity of the medium combustion plant or the facility in which it is applied (NACE code).	E38.2.1
6. Expected number of annual operating hours of the medium combustion plant and average load in use.	<500 hours, 100 %
7. Where the option of exemption under Article 6(3) or Article 6(8) is used, a declaration signed by the operator that the medium combustion plant will not be operated more than the number of hours referred to in those paragraphs.	Yes
8. Name and registered office of the operator and, in the case of stationary medium combustion plants, the address where the plant is located.	<p>Name and registered office address of the operator: Enfinium Parc Adfer Operations Ltd, 123 Victoria Street, London, England, SW1E 6DE</p> <p>The address where the plant is located: Deeside Industrial Park, Deeside , Flintshire CH5 2LL</p>

END OF PERMIT