


Heidelberg Materials

Heidelberg Materials: Padeswood Carbon Capture Plant – FEED Phase

Effluent & Emissions Summary



Project no. 215000-00190
Document no. Rev 0: 215000-00190-000-PR-LST-00005
21-May-24

Disclaimer

This report has been prepared on behalf of and for the exclusive use of Heidelberg Materials, and is subject to and issued in accordance with the agreement between Heidelberg Materials and Worley Europe Limited. Worley Europe Limited accepts no liability or responsibility whatsoever for it in respect of any use of or reliance upon this report by any third party. Copying this report without the permission of Hanson Cement or Worley Europe Limited is not permitted.

The information contained in these documents is protected by the General Data Protection Regulation (GDPR). Worley complies with the provisions of the Regulation and the information is disclosed on the condition that the Recipient also complies with the provisions of the (GDPR). In particular, all of the resumes and the information contained therein, must be kept securely, must be used only for the purposes of assessing the suitability of the individuals to perform the tasks proposed and/or assessing the overall capabilities of Worley to undertake the Work proposed and must be destroyed upon completion of those purposes.

Details on how personal information provided to Worley is processed can be found at <https://www.worley.com/site-services/privacy>

Rev	Description	Originator	Reviewer	Worley Approver	Revision Date
Rev A	Issued for IDC	SC S Chatterjee	AK A Kundu	AK A Kundu	15-Mar-24
Rev B	Issued for Review	SK S Kulkarni	AK A Kundu	AK A Kundu	27-Mar-24
Rev 0	Issued for Design	S Kulkarni	A Kundu	A Kundu	21-May-24

Project Name:	Heidelberg Materials: Padeswood Carbon Capture Plant – FEED Phase	Doc Rev:	Rev 0
Customer:	Heidelberg Materials	Doc No:	215000-00190-000-PR-LST-00005
Doc. Title :	Effluent & Emissions Summary	Page	3

Hold Record
Specify any Holds within the document.

Hold No.	Section	Description of Hold

Revision Tracking
Specify significant changes from previous revisions of the document.

Rev.	Section	Description of Change
A	General	Issued for IDC.
B	General	Incorporating IDC comments.
0	General	Incorporating Client comments.

Project Name	Heidelberg Materials: Padeswood Carbon Capture Plant - FEED Phase	Doc. No.	215000-00190-000-PR-LST-00005
Customer	Heidelberg Materials	Revision	Rev 0
Document Title	Effluent & Emissions Summary	Page	4

This document describes the Effluent and Emissions from the OSBL areas. For the ISBL area refer to Technology Provider document Effluent and Emissions List (startup, shut down, emergency) 215000-00190-720-PR-LST-10003 (Appendix-1)

GENERAL NOTE

1. Emergency relief vents are excluded from this summary. See MHI vent list (215000-00190-720-PR-LST-10004) for CO2 vent scenarios provided by the Technology Provider
2. The Process Condensate which is mentioned in the Technology Providers Effluent List is not considered an effluent as it is treated within the WWTP. Water exiting the WWTP is sent to the Quencher as RO reject water.
3. During media regeneration.
4. Flowrate provided for the worst case when downstream T&S pipeline is blocked or there is process upset.
5. For list of HP CO2 venting scenarios see MHI vent list (215000-00190-720-PR-LST-10004)
6. For list of LP CO2 venting scenarios see MHI vent list (215000-00190-720-PR-LST-10004)
7. Only when outbreathing.
8. See Stream no. 710-01 for composition for different modes (215000-00190-710-PR-HMB-00001)
9. Deleted.
10. Continuous Treated Gas to stack flow will be stopped if bypass stream is routed to stack.

EFFLUENTS & EMISSIONS SUMMARY


			Project Name	Heidelberg Materials: Padeswood Carbon Capture Plant – FEED Phase		215000-00190
			Customer	Heidelberg Materials		Rev 0
			Document Title	Effluent & Emissions Summary		Page 5
No.	1	2	3	4	5	6
SOURCE	TYPE	PHASE	FLOWRATE	TEMPERATURE °C	COMPOSITION	NOTES
Cooling Tower Exhaust	Continuous	V	57 tph	37	Air saturated with water	
Filter Vent (WWTP)	Intermittent	V	TBC by Vendor	TBC	Air	Note 3
Pond outfall	Intermittent	L	NNF	Amb	Water	
Flue Gas from Kiln to new stack header via bypass	Occasional	V	430034 kg/hr	165	O ₂ /N ₂ /Ar/CO ₂ /H ₂ O	Note 8, 10
Deaerator Vent	Continuous	V	672 kg/hr	132	Steam	
OSBL CO ₂ Vent to new stack	Occasional	V	112321 kg/hr	38	CO ₂	Note 4
WWTP Chemical Storage Tanks	Intermittent	V	NNF	Ambient		Note 7
CCP Effluent Storage Tank	Intermittent	V	NNF	Ambient		Note 7
WWTP Filter Media	Intermittent	S				Periodic (during filter changeover)
Pump suction filter Cartridge	Intermittent	S				
HTF drain	Occasional	L	28.4 m ³ /h	30	Therminol-66	Truck Unloading
Interceptor	Intermittent	L	NNF	Ambient	Hydrocarbons	Truck Unloading
CCP Effluent Tank	Intermittent	L	NNF	33	Water	Truck Unloading
FGD Tank	Intermittent	L	NNF	55	Water	Truck Unloading
RO Reject Tank	Intermittent	L	NNF	31	Water	Truck Unloading
WWT Tanker Loading	Intermittent	L	NNF	TBC by Vendor	TBC by Vendor	Truck Unloading

HEIDELBERG MATERIALS

Padeswood Carbon Capture Plant – FEED Phase

Effluent & Emissions List (ISBL)

Document no. Rev A : 215000-00190-720-PR-LST-10003



27 Great West Road
Brentford
TW8 9BW
United Kingdom
T: +44 208 326 5000
Worley Europe Limited
Incorporated in England number: 4334425
VAT Reg No 945 6484 83

© Copyright 2024 Worley ACN 096 090 158. No part of this document or the information it contains may be reproduced or transmitted in any form or by any means electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without permission in writing from Worley.

worley.com

Disclaimer

This report has been prepared on behalf of and for the exclusive use of Heidelberg Materials, and is subject to and issued in accordance with the agreement between Heidelberg Materials and Worley Europe Limited. Worley Europe Limited accepts no liability or responsibility whatsoever for it in respect of any use of or reliance upon this report by any third party. Copying this report without the permission of Heidelberg Materials or Worley Europe Limited is not permitted.

The information contained in these documents is protected by the Global Data Protection Regulation (GDPR). Worley complies with the provisions of the Regulation and the information is disclosed on the condition that the Recipient also complies with the provisions of the (GDPR). In particular, all of the resumes and the information contained therein, must be kept securely, must be used only for the purposes of assessing the suitability of the individuals to perform the tasks proposed and/or assessing the overall capabilities of Worley to undertake the Work proposed and must be destroyed upon completion of those purposes.

Details on how personal information provided to Worley is processed can be found at <https://www.worley.com/site-services/privacy>.

Rev	Description	Originator	Reviewer	MHI Approver	Revision Date
Rev A	Issue for Information	Yang	Kamada	Obata	15 May 2024

FOR REVIEW



EFFLUENT & EMISSIONS LIST (ISBL)

PROPRIETARY & CONFIDENTIAL

THIS DOCUMENT HAS BEEN PROVIDED TO THE RECIPIENTS UNDER A WRITTEN AGREEMENT PROVIDING FOR THE TERMS OF ITS RESTRICTED USE AND DISCLOSURE. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION AND EMBODIES CERTAIN INTELLECTUAL PROPERTY OF MITSUBISHI HEAVY INDUSTRIES, LTD. (MHI) THAT MAY NOT BE OTHERWISE USED, COPIED, REPRODUCED OR READ BY ANY PERSON, WITHOUT PREVIOUS WRITTEN AUTHORIZATION OF MHI.

ORDER NO. 583360		OWNER	
PROJECT	HMUK	PROJECT	
Approved	<i>Data</i>		
	<i>S. Sudo</i>	Heidelberg Materials Padeswood Carbon Capture Plant Project	
DISCIPLINE	KM-CDR Group		
APPROVED	<i>T. Kamada</i>		
CHECKED	<i>O. Miyamoto</i>		
PREPARED	<i>X. Yang</i>	DWG. NO.	REV.
	<i>K. Nakayama</i>	8382M-B 543 - S00 - 0010	
JAPAN EXPORT CONTROL	<input type="checkbox"/> On the control list <input checked="" type="checkbox"/> Not on the control list		
DRAWN DATE	24/4/2024		

DISTRIBUTION

PM	E
EM	E
PE	-
QA/QC	-
PROCURE.	-
SUBCONT.	-
LOGISTICS	-
COST	-
SCHEDULE	-
BUSINESS	-
PROCESS	-
MACHINE	-
EQUIP.	-
UNIT	-
PIPING	-
I&C	-
ELECT.	-
CIVIL	-
CONST.	-

HM	E
Worley	-
EMEA	-
VENDOR	-
TOTAL	-

EFFLUENT & EMISSIONS LIST (MODE 1)

CONFIDENTIAL

No.	1	2	3	4	5	6	7
ITEM	Treated Gas from CCP Flue Gas Stack (720-SK-001)	Filter Media from Guard Filter and Solvent Sump Filter (720-FU-002, 720-FU-003)	Activated Carbon from Carbon Filter (720-FU-004)	Dehydration Adsorbent in Dehydration Unit (730-ZZ-002)	O ₂ Removal Catalyst in O ₂ Removal Reactor (730-RA-001)	O ₂ Gas from H ₂ Generation Unit (730-ZZ-001)	H ₂ Gas from H ₂ Generation Unit (730-ZZ-001)
Quantity (Expected)	304,254 Nm ³ /h	720-FU-002 : 0.1 m ³ /Filter *1) *2) 720-FU-003 : 0.1 m ³ /Filter *1) *2)	10.3 m ³ *1) (per 1 year) *2)	20 m ³ *1) (per 3 years) *2)	2.9 m ³ *1) (per 4 years) *2)	3 Nm ³ /h *1)	9 L/min from PSA Dryer (Intermittent)
Temperature	100 °C			-	-	-	-
Composition	Composition H ₂ O 8.96 vol% N ₂ + Ar 81.7 vol% O ₂ 8.35 vol% CO ₂ 0.99 vol% Impurity *1) SOx *2) < 3.5 mg/Nm ³ -dry (10%O ₂) CO *2) < 13 mg/Nm ³ -dry (10%O ₂) NH ₃ < 3 mg/Nm ³ -dry (10%O ₂) HCl *2) < 1.3 mg/Nm ³ -dry (10%O ₂) HF *2) < 0.2 mg/Nm ³ -dry (10%O ₂) NOx as NO ₂ *2) < 65 mg/Nm ³ -dry (10%O ₂) CH ₂ O (formaldehyde) < 5 mg/Nm ³ -dry (10%O ₂) *3) C ₂ H ₄ O (acetaldehyde) < 5 mg/Nm ³ -dry (10%O ₂) *3) Amine < 1 mg/Nm ³ -dry (10%O ₂) TOC (excluding aldehydes) < 10 mg-C/Nm ³ -dry (10%O ₂) *3) Particulate < 1 mg/Nm ³ -dry (10%O ₂)	Polypropylene or Nylon or eq. ~100 wt% PM Trace Rust Trace Activated carbon Trace	*3 Activated Carbon Approx. 55 wt% Water Approx. 45 wt% Unburnt Carbon Trace Amine Trace Degraded product Trace	Alumino-silicate gel, Molecular Sieve, etc. *3) Solid Beads Type, etc. *3)	*3) Al ₂ O ₃ : Balance Pd : 0.3 - 0.4 wt% Solid Beads Type, etc. *3)	O ₂ + Moisture	H ₂ + Moisture
Note	*1) These are dependent on the impurity level of the inlet flue gas. *2) SOx, CO, HCl, HF and NOx is not produced in the CO ₂ capture plant. *3) To be confirmed by CHP vendor after CHP paid study.	*1) To be verified based on vendor's information. Disposal of the filter media shall be in accordance with the site environmental regulation. *2) The typical frequency of replacement for new filters is less than once per year during normal operation, excluding the commissioning or re-start periods.	*1) Disposal of the activated carbon shall be in accordance with the site environmental regulation. *2) Activated carbon is recommended to be replaced once per year. *3) To be verified based on vendor's information.	*1) To be verified based on vendor's information. *2) Expected lifetime is 3 years as per vendor's information. It will vary depending on actual plant condition. *3) Adsorbent material depends on vendor selection.	*1) To be verified based on vendor's information. *2) Expected lifetime is 4 years as per vendor's information. It will vary depending on actual plant condition. *3) Catalyst material depends on vendor selection.	*1) To be verified based on vendor's information.	*1) To be verified during detailed engineering.