



Industrial Heating Oil

Description

Industrial Heating Oil is a blend of petroleum fractions and performance additives which provides a more economical alternative to BS2869 Class D Gas Oil for burning applications.

Features & Benefits

Compatible with BS2869 Class D – British Standard for heating oil.

Same calorific value as Gas Oil – same heat output for less money.

Same physical properties as Gas Oil – no burner modifications required.

Totally miscible with Gas Oil – no need to empty fuel tanks before changing to IHO.

Low CFPP/pour point – allows year round summer/winter performance.

Reduced sulphur content – lowers acidic flue gas emissions by up to 50%.

Contains multifunctional additive – provides fuel system cleanliness & corrosion protection, reduced emissions and combustion chamber deposit control.

Light colour, low odour, sediment free – much cleaner than some commercially available products.

Applications & Limitations

Industrial Heating Oil is specifically intended for use in commercial boiler applications for heat generation. It typically finds application in large public buildings, hospitals, schools, factories, hotels, distilleries, quarries, grain driers.

Industrial Heating Oil is a fully rebated product (nil excise duty) and is therefore strictly prohibited for use in both on and off road vehicles or any other mobile or static engines.



Industrial Heating Oil

Specification

Parameter	Unit	Minimum	Maximum	Typical
Appearance	-	Clear & bright, Pale yellow, Free from visible sediment.		Pass
Density at 15°C	kg/m ³	0.820	-	0.830
Kinematic viscosity at 40°C	mm ² /s	1.50	5.0	2.4
Carbon residue (Ramsbottom on 10% residue)	% (m/m)	-	0.30	<0.30
Flash point (PMCC)	°C	45	-	58
Water content	mg/kg	-	200	100
Particulate content	mg/kg	-	10	<10
Ash content	% (m/m)	-	0.01	<0.01
Sulphur content	% (m/m)	-	0.10	0.05
Copper corrosion (3 hrs at 50°C)	Class	-	1	1
Cold filter plugging point Summer	°C	-	-4	-25
Winter	°C	-	-12	-25
Strong acid number	mgKOH/g	-	nil	nil
Oxidation stability	g/m ³	-	25	<25
Fatty acid methyl ester (FAME)	% (v/v)	-	-	None Added
Gross calorific value	MJ/kg	-	-	nil 46.00
	MJ/litre	-	-	38.00
Lubricity at 60°C (HFRR)	µm	-	460	300

Revision 4 : 01.04.19