



gwerth mewn gwahaniaeth  
delivering on distinction

## Morlais Demonstration Zone

### Further information on predicted changes in currents

Document Title: Further information on predicted changes in currents

Morlais Document No. MOR-HRW-DOC-0002

File No.: MMC 350

Status:

FINAL

Version No:

F1

Date:

16/10/2020

© 2020 Menter Môn This document is issued and controlled by:

Morlais, Menter Môn. Registered Address: Llangefni Town Hall, Anglesey, Wales, LL77 7LR, UK

Unauthorised copies of this document are NOT to be made

Company registration No: 03160233 Requests for additional copies shall be made to Morlais Project

## **1. INTRODUCTION**

The following HR Wallingford Report “Further information on predicted changes in waves and currents” should be read in conjunction with HR Wallingford Coastal Process Report DER6261\_RT001-R02-00. This supplementary report provides further information from the original study regarding the effect of the proposed scheme on speeds and directions of tidal currents throughout the tidal cycle to assist in discussions with navigational stakeholders and canoeists and kayakers in particular. This note presents predicted changes in current speeds and directions at hourly intervals throughout a Mean Spring Tide cycle.

It should be noted that the recently completed Navigation Risk Assessment (NRA) Addendum has already considered currents and tidal flows as presented in the original HR report in addition to published information for the region including tidal diamonds and the tidal stream atlas. Marico, who completed the independent NRA, have since reviewed this supplementary report and advised that the additional information does not change the risk scoring as the impacts of the MDZ to the tidal stream are considered to be of low significance in terms of additional impact to navigation risk over the existing sea conditions.

# Morlais Demonstration Zone

Further information on predicted  
changes in currents



## Document information

Document permissions	Confidential - client
Project number	DER6261
Project name	Morlais Demonstration Zone
Report title	Further information on predicted changes in currents
Report number	RT002
Release number	R05-00
Report date	October 2020
Client	Menter Mon Morlais Limited
Client representative	James Orme
Project manager	Juliette Parisi
Project director	Graham Siggers

## Document authorisation

Prepared



Approved



Authorised



© HR Wallingford Ltd

This report has been prepared for HR Wallingford's client and not for any other person. Only our client should rely upon the contents of this report and any methods or results which are contained within it and then only for the purposes for which the report was originally prepared. We accept no liability for any loss or damage suffered by any person who has relied on the contents of this report, other than our client.

This report may contain material or information obtained from other people. We accept no liability for any loss or damage suffered by any person, including our client, as a result of any error or inaccuracy in third party material or information which is included within this report.

To the extent that this report contains information or material which is the output of general research it should not be relied upon by any person, including our client, for a specific purpose. If you are not HR Wallingford's client and you wish to use the information or material in this report for a specific purpose, you should contact us for advice.

## Document history

Date	Release	Prepared	Approved	Authorised	Notes
14 Oct 2020	05-00	TMI	JCP	NPB	
13 Oct 2020	04-00	TMI	JCP	NPB	
16 Sep 2020	03-00	TMI	NPB	GBS	
07 Sep 2020	02-00	TMI	JS	NPB	
03 Sep 2020	01-00	TMI	NPT	JS	

## Summary

Menter Mon Morlais Limited (MMML) is developing the Morlais Demonstration Zone (MDZ), situated to the west of Holy Island on the Isle of Anglesey. The MDZ will incorporate multiple tidal current device array projects from different project owners and with different technologies. HR Wallingford has undertaken a detailed study of the effects of the MDZ on currents, waves and sediment transport. This is described in HR Wallingford Report DER6261\_RT001-R02-00. MMML has requested that further information be provided from the study regarding the effect of the proposed scheme on the direction and strength of the tidal currents, to assist it with discussions with stakeholder parties including kayakers. This note presents predicted changes in current speeds and directions at hourly intervals throughout a Mean Spring Tide cycle. In general there is a reduction in current speeds due to the tidal current scheme although the tidal stream is also diverted around the development causing a shift in the location of the tidal stream between the development area and the coast at some states of the tide. The pattern of the tidal eddy around North Stack Head is also changed.

# Contents

## Summary

1. Introduction	1
1.1. Background	1
1.2. Report Structure	1
2. Characteristics of devices considered in the study	1
3. Flow conditions	2
4. References	42

## Figures

Figure 3.1: Existing flow velocity. High Water minus 6 hours	3
Figure 3.2: Scheme flow velocity. High Water minus 6 hours	4
Figure 3.3: Existing (blue) and Scheme (red) flow velocity. High Water minus 6 hours	5
Figure 3.4: Existing flow velocity. High Water minus 5 hours	6
Figure 3.5: Scheme flow velocity. High Water minus 5 hours	7
Figure 3.6: Existing (blue) and Scheme (red) flow velocity. High Water minus 5 hours	8
Figure 3.7: Existing flow velocity. High Water minus 4 hours	9
Figure 3.8: Scheme flow velocity. High Water minus 4 hours	10
Figure 3.9: Existing (blue) and Scheme (red) flow velocity. High Water minus 4 hours	11
Figure 3.10: Existing flow velocity. High Water minus 3 hours	12
Figure 3.11: Scheme flow velocity. High Water minus 3 hours	13
Figure 3.12: Existing (blue) and Scheme (red) flow velocity. High Water minus 3 hours	14
Figure 3.13: Existing flow velocity. High Water minus 2 hours	15
Figure 3.14: Scheme flow velocity. High Water minus 2 hours	16
Figure 3.15: Existing (blue) and Scheme (red) flow velocity. High Water minus 2 hours	17
Figure 3.16: Existing flow velocity. High Water minus 1 hour	18
Figure 3.17: Scheme flow velocity. High Water minus 1 hour	19
Figure 3.18: Existing (blue) and Scheme (red) flow velocity. High Water minus 1 hour	20
Figure 3.19: Existing flow velocity. High Water	21
Figure 3.20: Scheme flow velocity. High Water	22
Figure 3.21: Existing (blue) and Scheme (red) flow velocity. High Water	23
Figure 3.22: Existing flow velocity. High Water plus 1 hour	24
Figure 3.23: Scheme flow velocity. High Water plus 1 hour	25
Figure 3.24: Existing (blue) and Scheme (red) flow velocity. High Water plus 1 hour	26
Figure 3.25: Existing flow velocity. High Water plus 2 hours	27
Figure 3.26: Scheme flow velocity. High Water plus 2 hours	28
Figure 3.27: Existing (blue) and Scheme (red) flow velocity. High Water plus 2 hours	29
Figure 3.28: Existing flow velocity. High Water plus 3 hours	30
Figure 3.29: Scheme flow velocity. High Water plus 3 hours	31
Figure 3.30: Existing (blue) and Scheme (red) flow velocity. High Water plus 3 hours	32
Figure 3.31: Existing flow velocity. High Water plus 4 hours	33

Figure 3.32: Scheme flow velocity. High Water plus 4 hours .....	34
Figure 3.33: Existing (blue) and Scheme (red) flow velocity. High Water plus 4 hours.....	35
Figure 3.34: Existing flow velocity. High Water plus 5 hours.....	36
Figure 3.35: Scheme flow velocity. High Water plus 5 hours .....	37
Figure 3.36: Existing (blue) and Scheme (red) flow velocity. High Water plus 5 hours.....	38
Figure 3.37: Existing flow velocity. High Water plus 6 hours.....	39
Figure 3.38: Scheme flow velocity. High Water plus 6 hours .....	40
Figure 3.39: Existing (blue) and Scheme (red) flow velocity. High Water plus 6 hours.....	41

## Tables

Table 2.1: Sea bed Turbine Characteristics .....	2
--	---



# 1. Introduction

## 1.1. Background

Menter Mon Morlais Limited (MMML) is developing the Morlais Demonstration Zone (MDZ), situated to the west of Holy Island on the Isle of Anglesey. The MDZ will incorporate multiple tidal current device array projects from different project owners and with different technologies.

HR Wallingford has undertaken a detailed study of the effects of the MDZ on currents, waves and sediment transport. This is described in HR Wallingford Report DER6261\_RT001-R02-00 (Reference 1).

MMML has requested that further information be provided from the study regarding the effect of the proposed scheme on currents, to assist it with discussions with stakeholder parties. This note presents predicted changes in currents throughout a Mean Spring Tide cycle.

## 1.2. Report Structure

The remainder of this report includes two further sections. Section 2 briefly describes the devices considered in the study. Section 3 details changes in currents throughout a Mean Spring tide.

# 2. Characteristics of devices considered in the study

The HR Wallingford study (Reference 1) considers the worst case scenarios for the impact on the : 620 seabed-mounted devices, 112 electrical seabed hubs, 8 surface piercing electrical hubs and rock bag protection along 9 cable routes.

The seabed turbine characteristics assumed in the study are given in Table 2.1 below.

Table 2.1: Sea bed Turbine Characteristics

Characteristic	Assumed Value
Rotor diameter (D)	16.13 m
Rated flow speed	2.015 m/s
Cut-in flow speed	0.5 m/s
Rated mechanical (electrical) power	429 kW (387 kW)
Power Curve	Variable with flow speed
Thrust Curve	Variable with flow speed
Position in water column	Mid depth

### 3. Flow conditions

The following figures illustrate the flow conditions for a Mean Spring Tide from High Water minus 6 hours to High Water plus 6 hours at 1-hour intervals. For each time, there are 3 figures, one for the existing case, one for the scheme and one showing vectors for both, with blue arrows for the existing case and red arrows for the scheme. Point 3 is marked on these figures. This is one of the key points of interest referred to in Reference 1.




Figure 3.1: Existing flow velocity. High Water minus 6 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.2: Scheme flow velocity. High Water minus 6 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.3: Existing (blue) and Scheme (red) flow velocity. High Water minus 6 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.4: Existing flow velocity. High Water minus 5 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.5: Scheme flow velocity. High Water minus 5 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.6: Existing (blue) and Scheme (red) flow velocity. High Water minus 5 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)






Figure 3.7: Existing flow velocity. High Water minus 4 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.8: Scheme flow velocity. High Water minus 4 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.9: Existing (blue) and Scheme (red) flow velocity. High Water minus 4 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.10: Existing flow velocity. High Water minus 3 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)






Figure 3.11: Scheme flow velocity. High Water minus 3 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.12: Existing (blue) and Scheme (red) flow velocity. High Water minus 3 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.13: Existing flow velocity. High Water minus 2 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.14: Scheme flow velocity. High Water minus 2 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)






Figure 3.15: Existing (blue) and Scheme (red) flow velocity. High Water minus 2 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.16: Existing flow velocity. High Water minus 1 hour

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.17: Scheme flow velocity. High Water minus 1 hour

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.18: Existing (blue) and Scheme(red) flow velocity. High Water minus 1 hour

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)






Figure 3.19: Existing flow velocity. High Water

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.20: Scheme flow velocity. High Water

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.21: Existing (blue) and Scheme (red) flow velocity. High Water

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.22: Existing flow velocity. High Water plus 1 hour

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)






Figure 3.23: Scheme flow velocity. High Water plus 1 hour

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.24: Existing (blue) and Scheme (red) flow velocity. High Water plus 1 hour

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.25: Existing flow velocity. High Water plus 2 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.26: Scheme flow velocity. High Water plus 2 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.27: Existing (blue) and Scheme (red) flow velocity. High Water plus 2 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)






Figure 3.28: Existing flow velocity. High Water plus 3 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.29: Scheme flow velocity. High Water plus 3 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.30: Existing (blue) and Scheme (red) flow velocity. High Water plus 3 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)






Figure 3.31: Existing flow velocity. High Water plus 4 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.32: Scheme flow velocity. High Water plus 4 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.33: Existing (blue) and Scheme (red) flow velocity. High Water plus 4 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.34: Existing flow velocity. High Water plus 5 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.35: Scheme flow velocity. High Water plus 5 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)






Figure 3.36: Existing (blue) and Scheme (red) flow velocity. High Water plus 5 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)






Figure 3.37: Existing flow velocity. High Water plus 6 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.38: Scheme flow velocity. High Water plus 6 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)




Figure 3.39: Existing (blue) and Scheme (red) flow velocity. High Water plus 6 hours

Source: HR Wallingford

Note: Extent of Morlais Demonstration Zone (dashed line). Area within which surface devices may be present (continuous line)

## 4. References

Morlais Demonstration Zone, Coastal Processes, HR Wallingford Report DER6261-RT001-R02-00, March 2020.



HR Wallingford is an independent engineering and environmental hydraulics organisation. We deliver practical solutions to the complex water-related challenges faced by our international clients. A dynamic research programme underpins all that we do and keeps us at the leading edge. Our unique mix of know-how, assets and facilities includes state of the art physical modelling laboratories, a full range of numerical modelling tools and, above all, enthusiastic people with world-renowned skills and expertise.



FS 516431  
EMS 558310  
OHS 595357

HR Wallingford, Howbery Park, Wallingford, Oxfordshire OX10 8BA, United Kingdom  
tel +44 (0)1491 835381 fax +44 (0)1491 832233 email [info@hrwallingford.com](mailto:info@hrwallingford.com)  
[www.hrwallingford.com](http://www.hrwallingford.com)