

OUTLINE DRAINAGE STRATEGY REPORT

Simec Uskmouth Power Station Conversion SUP



019784 - Simec Uskmouth
Power Station Conversion SUP
Outline Drainage Strategy
Report
P03
1st April 2020

REPORT

Document status

Version	Purpose of document	Authored by	Reviewed by	Approved by	Review date
P01	Planning	LJS	DW	DW	17/03/20
P02	Planning	LJS	DW	DW	26/03/20
P03	Planning	LJS	DW	DW	01/04/20

Approval for issue

G.Barnard



1 April 2020

© Copyright RPS Group Plc. All rights reserved.

The report has been prepared for the exclusive use of our client and unless otherwise agreed in writing by RPS Group Plc, any of its subsidiaries, or a related entity (collectively 'RPS'), no other party may use, make use of, or rely on the contents of this report. The report has been compiled using the resources agreed with the client and in accordance with the scope of work agreed with the client. No liability is accepted by RPS for any use of this report, other than the purpose for which it was prepared. The report does not account for any changes relating to the subject matter of the report, or any legislative or regulatory changes that have occurred since the report was produced and that may affect the report. RPS does not accept any responsibility or liability for loss whatsoever to any third party caused by, related to or arising out of any use or reliance on the report.

RPS accepts no responsibility for any documents or information supplied to RPS by others and no legal liability arising from the use by others of opinions or data contained in this report. It is expressly stated that no independent verification of any documents or information supplied by others has been made. RPS has used reasonable skill, care and diligence in compiling this report and no warranty is provided as to the report's accuracy. No part of this report may be copied or reproduced, by any means, without the prior written consent of RPS.

Prepared by:

RPS Group

Louis Sime

Engineer

Sherwood House
Sherwood Avenue
Newark
Nottinghamshire
NG24 1QQ

T +44 1636 605 700

E louis.sime@rpsgroup.com

Prepared for:

SIMEC ATLANTIS ENERGY

Uskmouth Power Station
West Nash Road
Nash
Newport
NP18 2BZ

T +44 1633 292700

E

Contents

1	INTRODUCTION	1
	Background	1
	Existing Site.....	1
	Proposed Site	2
	Drainage Strategy overview	2
2	SURFACE WATER RUNOFF DESTINATION	3
3	SURFACE WATER RUNOFF HYDRAULIC CONTROL	4
4	SURFACE WATER QUALITY MANAGEMENT	5
5	AMENITY & BIODIVERSTIY	6
6	DESIGN OF DRAINAGE FOR CONSTRUCTION, OPERATION AND MAINTENANCE	7
	Appendix A – RPS Drawings	9
	Appendix B – RPS Calculations	10

Figures

Figure 1 (Pictured left) view from south of site looking north over interceptor ditch.....	1
Figure 2 (Pictured right) looking east into existing attenuation pond.	1
Figure 3 Looking east over the area previously used for coal storage.....	2

1 INTRODUCTION

Background

- 1.1 RPS has been commissioned by SIMEC Atlantis Energy to produce an Outline Drainage Strategy Report for the proposed fuel conversion works to an existing coal fired power generation plant. The 363-megawatt SIMEC Uskmouth Power Station was built in 1959 and is located in South Wales, UK.
- 1.2 On the 7th January 2019, Schedule 3 of the Floods and Water Management Act 2010 (FWMA) was enacted in Wales. This Act requires all new developments of more than 1 dwelling or where the construction area is greater than 100m² to incorporate Sustainable Drainage Systems (SuDS) into their drainage proposals.
- 1.3 These SUDS proposals must be designed and built in accordance with the Welsh Government's Statutory SuDS Standards for designing, constructing, operating and maintaining surface water drainage systems. The SuDS schemes must be approved by the local SuDS Approving Body (SAB) before construction work begins.
- 1.4 This report has been completed by RPS to satisfy the SAB that the SuDS proposals for the proposed fuel conversion works have been designed in accordance with the six Statutory SuDS Standards and SuDS design guidance including The SuDS Manual, CIRIA Report C753.

Existing Site

- 1.5 Built in 1959, the existing power generation plant is located approximately 4km south of the City of Newport, South Wales, UK on the east bank of the River Usk as it reaches the Severn estuary. The site is currently drained via a combination of traditional below ground drainage networks and open ditches before discharging to the Severn Estuary approximately 0.5km to the west of the site.
- 1.6 Works undertaken C.2006-2009 included provisions for storage of fuel ash including a new surface water drainage system, an attenuation pond and other infrastructure improvements. RPS drawing 019784-RPS-SI-ZZ-DR-D-0300 included in Appendix A depicts the site in its existing state.



Figure 1 (Pictured left) view from south of site looking north over interceptor ditch.

Figure 2 (Pictured right) looking east into existing attenuation pond.

- 1.7 Forming part of the 2006-2009 works, an interceptor ditch was constructed (Figure 1 above) around the coal storage area to intercept surface water runoff. This ditch assists in removing suspended sediments before runoff passed through a lamella plate clarifier. Treated runoff is then discharged from the clarifier via hydrobrake at a reduced rate of 30l/s into the attenuation pond (Figure 2 above).

Proposed Site

- 1.8 The site is bisected by an existing railway running west to east. Significant aspects of the proposed fuel conversion works are located in the southern section of the site around the area previously used for coal storage. The RPS Proposed SUP Site Plan 019784-RPS-SI-ZZ-DR-A-5003 has been included in Appendix A which indicates the new and remediation works proposed. In this area, the parcel of land previously used for storage of coal will house new storage silos for storage of pelletised fuel with associated rail unloading facilities. High level conveyors will allow connection of these elements and facilitate the transfer of materials.
- 1.9 The Proposed SUP Site Plan also includes some relatively minor works in the north of the site which are also encompassed as part of this application.

Drainage Strategy overview

- 1.10 The overall drainage strategy has carefully considered the existing drainage assets in order to provide a sustainable solution which utilises existing infrastructure where feasible to reduce the use of new building materials and construction activity.
- 1.11 The area previously used for coal storage pictured in Figure 3 below will be remediated prior to development, leaving this an ideal opportunity to develop in line with new SuDS standards.



Figure 3 Looking east over the area previously used for coal storage

- 1.12 It is proposed that grassed conveyance swales will be constructed adjacent the new hardstanding areas to intercept runoff and direct flows towards the existing interceptor ditch.
- 1.13 As per existing arrangements, the interceptor ditch will then direct flows east to the lamella plate clarifier. Runoff will then be discharged into the attenuation pond via the existing hydrobrake limited to 30l/s.
- 1.14 Preliminary design of the proposed surface water drainage system serving the new hardstanding areas and silos in the southern section of the site has been undertaken using current MicroDrainage analysis software. The following sections of this report cover how the preliminary design aims to satisfy The Welsh Government six the Statutory SuDS Standards. An indicative drainage layout has been included in Appendix A.
- 1.15 Existing concrete roads and conveyor buildings will be left to drain as per existing arrangements to the on-site attenuation pond with localised enhancement where necessary. Any necessary amendments to the existing drainage networks will be reviewed at detailed design stage once an intrusive CCTV drainage investigation has been undertaken.

2 SURFACE WATER RUNOFF DESTINATION

S1 Surface water runoff destination

- Priority Level 1: Surface water runoff is collected for use;
- Priority Level 2: Surface water runoff is infiltrated to ground;
- Priority Level 3: Surface water runoff is discharged to a surface water body;
- Priority Level 4: Surface water runoff is discharged to a surface water sewer, highway drain, or another drainage system;
- Priority Level 5: Surface water runoff is discharged to a combined sewer.

- 2.1 The surface water runoff destination has been selected in accordance with the priority levels set out in the Welsh Government Statutory SuDS Standards included above.
- 2.2 There is no significant opportunity for water recycling in the proposed facility other than for use in staff welfare facilities. Opportunities for collecting roof water for use as grey water in welfare facilities will be identified and utilised during detailed design. Priority Level 1 will therefore be reviewed as detailed design.
- 2.3 Due to site being located close to the Severn Estuary at a level nearing sea level, infiltration is not considered a viable means of discharge however the site SuDS system will incorporate source control SuDS features where possible to harness residual infiltration in the underlying strata in an attempt to reduce volumetric runoff. Priority Level 2 is therefore not viable
- 2.4 As per existing arrangements, it is proposed to utilise the network of ditches and outfall to the Severn Estuary as the primary means of surface water disposal. Priority Level 3, discharging to a surface water body will therefore from the primary method of surface water disposal.

3 SURFACE WATER RUNOFF HYDRAULIC CONTROL

S2 Surface water runoff hydraulic control

- 1) Surface water should be managed to prevent, so far as possible, any discharge from the site for the majority of rainfall events of less than 5mm.
- 2) The surface water runoff rate for the 1 in 1 year return period event (or agreed equivalent) should be controlled to help mitigate the negative impacts of the development runoff on the morphology and associated ecology of the receiving surface water bodies.
- 3) The surface water runoff (rate and volume) for the 1% (1 in 100 year) return period event (or agreed equivalent) should be controlled to help mitigate negative impacts of the development on flood risk in the receiving water body.
- 4) The surface water runoff for events up to the 1% (1 in 100 year) return period (or agreed equivalent) should be managed to protect people and property on and adjacent to the site from flooding from the drainage system.
- 5) The risks (both on site and off site) associated with the surface water runoff for events greater than the 1% (1 in 100 year) return period should be considered. Where the consequences are excessive in terms of social disruption, damage or risk to life, mitigating proposals should be developed to reduce these impacts.
- 6) Drainage design proposals should be examined for the likelihood and consequences of any potential failure scenarios (e.g. structural failure or Sustainable Drainage Systems Standards for Wales Page 20 of 63 blockage), and the associated flood risks managed where possible.

- 3.1 Due to the limited opportunity for infiltration presented by the underlying strata, the ability to prevent runoff from the 'first flush' 5mm rainfall event is limited. However, opportunities to encourage natural process such as infiltration and evaporation will be harnessed by the inclusion of new filter strips and grassed swales and the retention of the existing interceptor ditch.
- 3.2 The surface water runoff will be controlled in all events including the 1 in 1 year return period via the existing lamella plate clarifier and hydrobrake prior to discharge into the attenuation pond. This will help mitigate any negative impacts to the morphology and ecology to the receiving surface water body as a result of the development. By maintaining the existing hydrobrake 30l/s runoff rate, this will also mitigate any adverse impacts of flood risk to the receiving surface water body as a result of the development.
- 3.3 Initial hydraulic calculations identified that the existing interceptor ditch did not have sufficient capacity to attenuate the flows from the existing and proposed impermeable areas. As a result, the eastern section of the interceptor ditch will be enlarged to provide additional surface water storage. An Indicative Drainage Layout has been included as Appendix A, RPS Drawing 019784-RPS-SI-ZZ-DR-D-0301.
- 3.4 Modelled outputs have been included as Appendix B. These results indicate that, following the localised enlargement of the interceptor ditch, the system has sufficient capacity to attenuate flows from the critical 1 in 100 year event including a 40% allowance for climate change with no onsite flooding.
- 3.5 In the event of a failure of the local drainage system or for storms in excess of those considered, site levels will be designed so that exceedance routes direct runoff towards low lying areas of the site where runoff will be stored safely until the failure rectified or until the rainfall event passes.

4 SURFACE WATER QUALITY MANAGEMENT

S3 Surface water quality management

Treatment for surface water runoff should be provided to prevent negative impacts on the receiving water quality and/or protect downstream drainage systems, including sewers.

- 4.1 Surface water quality for site runoff for the site will be managed through a combination of new sustainable drainage features and enhancing the existing drainage assets.
- 4.2 A water quality risk assessment has been carried out using the SuDS hazard mitigation indices in accordance with Chapter 26, of the CIRIA C753 SuDS Manual (CIRIA, 2015). Under this method of assessment, the main silo area of the development has been conservatively considered as having high pollution hazard level.

Table 1: High Hazard –Pollution Mitigation

	Hazard Level	TSS	Metals	Hydro-carbons
Pollution Hazard Indices	High	0.8	0.8	0.9
Proposed SuDS mitigation I ₁ Swales	-	0.5	0.6	0.6
Proposed SuDS mitigation I ₂ interceptor ditch (wetland)	-	0.8	0.8	0.8
Proposed SuDS mitigation I ₃ Attenuation pond	-	0.7	0.7	0.5
Total SuDS Mitigation Indices (I₁+0.5xI₂+0.5xI₃...)		1.25	1.35	1.35

- 4.3 From Table 1 above it is evident that the proposed SuDS mitigation indices far exceed the pollution hazard indices. It is important to note that this assessment does not include the additional water quality benefits provided by the existing lamella plate clarifier.
- 4.4 An external on site plant re-fuelling area and diesel fuel exists on the north boundary of the SIMEC site. This area will be isolated from the general hardstanding by way of a surface water channel drain surrounding the fuelling area, and then connected via a Class 1 full retention forecourt separator, prior to discharge into the surface water drainage system. Additional opportunities for isolating sections of the drainage network have also been provided as penstock valves.
- 4.5 The site wide water quality management will be re-evaluated at detailed design stage in conjunction with the ground remediation strategy.

5 AMENITY & BIODIVERSITY

- 5.1 The proposed on site SuDS features will be designed in accordance with The SuDS Manual, CIRIA Report C753 to maximise the multiple benefits of SuDS including Amenity and Biodiversity.

S4 Amenity

The design of the surface water management system should maximise amenity benefits.

- 5.2 Due to the proposed nature of the site, designing for amenity is not considered of particular priority. However, the SuDS proposals will assist in providing amenity benefit to employees and site visitors.

S5 Biodiversity

The design of the surface water management system should maximise biodiversity benefits.

- 5.3 Considering the site's current poor ecological value, the redevelopment is recognised as an ideal opportunity to use SuDS proposals to maximise the biodiversity benefits. Through redevelopment it is envisaged that the proposed swale and interceptor ditch can be enhanced to mimic the wetland habitat observed at the nearby RSPB Reserve to provide a continuation of habitat.

6 DESIGN OF DRAINAGE FOR CONSTRUCTION, OPERATION AND MAINTENANCE

S6 Design of drainage for Construction, Operation and Maintenance

- 1) All elements of the surface water drainage system should be designed so that they can be constructed easily, safely, cost-effectively, in a timely manner, and with the aim of minimising the use of scarce resources and embedded carbon (energy).
- 2) All elements of the surface water drainage system should be designed to ensure maintenance and operation can be undertaken (by the relevant responsible body) easily, safely, cost-effectively, in a timely manner, and with the aim of minimising the use of scarce resources and embedded carbon (energy).
- 3) The surface water drainage system should be designed to ensure structural integrity of all elements under anticipated loading conditions over the design life of the development site, taking into account the requirement for reasonable levels of maintenance

- 6.1 Under RPS' CDM Designer responsibilities, the surface water drainage system will be designed considering the health and safety both during construction and for the long term operations and maintenance of the system.
- 6.2 Prior to detailed design, an intrusive CCTV investigation will be undertaken to determine the location and condition of the existing site drainage assets. Detailed design will then look to retain the existing drainage assets where possible to reduce construction activity and provide an economical solution.
- 6.3 The detailed design of the drainage system will be undertaken concurrently with detailed level design and earthworks analysis to minimise groundworks and reduce imported fill material.
- 6.4 All below ground drainage infrastructure will be designed in accordance with DMRB Volume 4 Section 2 Part 5 (HA 40/01) "Determination of pipe and bedding combinations for drainage works" to ensure structural integrity under the anticipated vehicular loading. Proprietary interceptors to be installed in accordance with supplier specification.

6.5 The maintenance for all on plot drainage infrastructure will be the responsibility of the client or appointed management company. Details of the maintenance activities for the constructed drainage infrastructure will be passed to the end user as part of an Operation and Maintenance Manual post completion. Typical maintenance activities may include;


Table 2: Typical Maintenance Activities

Element	Access Method	Method of Maintenance	Frequency Required
Roof Gutters	Scaffolding / Cherry pickers to be used where required.	General cleaning of gutters. Jet cleaning where required.	Periodic inspection of gutters to ensure rainwater outlets do not become blocked. Periodic renewal of gutter coatings to prevent corrosion.
Oil / Petrol Separators	In accordance with H&S regulations and confined spaces requirements.	Refer to manufacturer's guidance.	Bi-annual inspection and emptying.
Channel Drains / Kerb Drainage	In accordance with H&S regulations.	Monitor to ensure no blockages develop. Jet cleaning where required.	Bi-annual jet cleaning of channel drains.
Silt-traps and Gullies	In accordance with H&S regulations.	Monitor to ensure no blockages develop.	Bi-annual inspection and emptying of all silt traps and gullies.
Penstock Valves/ Non-Return Flap Valves	In accordance with health and safety regulations and confined spaces requirements.	Monitored to ensure no blockages develop in accordance with the manufacturer's recommendations.	Bi-annual inspection or in accordance with the manufacturer's recommendations, whichever occurs sooner.
Surface Water Ponds and Swales	In accordance with H&S regulations	General cleaning and monitoring to ensure no blockage. Remove litter and debris. Cut grass and manage vegetation. Inspect inlets and outlets	Bi-annual inspection, cleaning and removal of silt and/or debris
Pumps	In accordance with health and safety regulations and confined spaces requirements.	Monitored via visual and audible alarms in development gatehouse to ensure no blockages develop in accordance with the manufacturer's recommendations.	Bi-annual inspection or in accordance with the manufacturer's recommendations, whichever occurs sooner.
Headwall	In accordance with health and safety regulations.	Monitored to ensure no blockages develop.	Bi-annual inspection and clearance of any debris

APPENDIX A – RPS DRAWINGS

Notes

1. This drawing has been prepared in accordance with the scope of RPS's appointment with its client and is subject to the terms and conditions of that appointment. RPS accepts no liability for any use of this document other than by its client and only for the purposes for which it was prepared and provided.
2. If viewed electronically it is the recipient's responsibility to print to correct scale. Only written dimensions should be used.
3. This drawing should be read in conjunction with all other relevant drawings and specifications.



P02	Amended in accordance with client comment.	MB	LJS	26.03.20
P01	First issue	CW	LJS	16.03.20
Rev	Description	By	Ckd	Date



Sherwood House, Sherwood Avenue,
Newark, Nottinghamshire, NG24 1QG
T:01639 665 700 E: rpsnewark@rpsgroup.com



Client: Simec Atlantis Energy
Project: Simec Uskmouth Power Station Conversion SUP

Title: Existing Drainage

RPS Project Number	Scale @ A1	Date Created
NK019784	1:750	16.03.2020
Task Team Manager	Information Author	Task Information Manager
GB	CW	LJS

Status: S2 (Suitable for Information)
Document Number: 019784-RPS-SI-ZZ-DR-D-0300
Revision: P02
Project Code - Originator - Zone - Level - Type - File - Drawing Number
rpsgroup.com

Notes

1. This drawing has been prepared in accordance with the scope of RPS's appointment with its client and is subject to the terms and conditions of that appointment. RPS accepts no liability for any use of this document other than by its client and only for the purposes for which it was prepared and provided.
2. If received electronically it is the recipient's responsibility to print to correct scale. Only written dimensions should be used.
3. This drawing should be read in conjunction with all other relevant drawings and specifications.

Legend

- Landscaped Area
- Existing Shrubby Area
- Existing Native Trees and Shrubs
- Concrete
- Aggregate Crushed Stone
- Ditch / Reen
- Denotes Existing structure to be re-clad
- Denotes new works to powerstation



P07	Drawing revised and updated to show lorry unloading building removed including the towers and conveyor system leads, weighbridges removed to suit, access road revised to existing layout at junction	PBR	TFH	03/02/20
P06	Drawing revised and updated to reflect new topographical survey	PBR	TFH	12/09/19
P05	Site boundary revised	PBR	TFH	01/08/19
P04	Drawing revised to current details	PBR	TFH	03/07/19
P03	Drawing sent to team prior to design change	PBR	TFH	14/06/19
P02	Drawing revised and updated to show day silo adjacent to main power station, new lime silo adjacent existing and primary storage facility to show 4 large silos	PBR	NB	07/06/19
P01	Initial Issue	PBR	TFH	21.05.19
Rev	Description	By	Ckd	Date



Suite D10, Josephs Well, Hanover Walk
Leeds, West Yorkshire LS3 1AB, United Kingdom
T:0113 220 6190 E: rpsnewark@rpsgroup.com




Project **SUP Fuel Conversion project**

Title **Proposed SUP Site Plan**


Status **Preliminary** Scale @ A1 **As indicated** Date Created **20/05/19**
Task Team Manager **TFH** Information Author **PBR** Task Information Manager **NB**

Document Number
019784-RPS-SI-ZZ-DR-A-5003

RPS Project Number **NK019784** Suitability **S0** Revision **P07**
rpsgroup.com




1 Site Plan.
1 : 1250




- Notes:
1. This drawing has been prepared in accordance with the scope of RPS's agreement with the client and subject to the terms and conditions of that agreement. With respect to liability for any use of this document other than for the purposes intended by RPS, the project owner shall be deemed to warrant and provide.
 2. Structural engineering is the responsible party to provide to correctable. Only written dimensions should be used.
 3. This drawing should be read in conjunction with all other relevant drawings and specifications.

Key:

- 1:800 FW Main (D & Gradient)
- 1:1000 SW Main (D & Gradient)
- Linear Drainage
- SW Manhole
- Area of existing drainage enhancement
- Contaminant area
- Heavefill
- Attenuation Pond/Ditch
- Grassed Conveyance Swale



Section B-B
Typical section through remediated existing interceptor ditch
Scale 1:25



Section A-A
Typical section through proposed conveyance swale
Scale 1:25

Rev	Description	By	Chk	Date
01	Approved in accordance with department.	MJ	LJL	20.03.20
02	Final issue	CW	LJL	16.03.20

rps RPS GROUP
 SHROUD HOUSE, SHROUD CANNON,
 SHROUD, NORTHAMPTONSHIRE, NN4 5GG
 T 01606 805 700 E rps@rpsgroup.com

Client: **SMIC ATLANTIS ENERGY**
 Project: **Simec Ukmouth Power Station Conversion SUP**
 Title: **Indicative Drainage Layout**

RPS Project Number: 160257974	Scale: A3	Date Created: 16.03.2020
Task Team Manager: CJB	Author: CJB	Task Reviewer: LJL
Scale: S2 (Suitable for Information)	Client Reference: 019784-RPS-S1ZZ-DR-D-0301	Revision: P02

Project Code: 019784-RPS-S1ZZ-DR-D-0301
 Project Name: Ukmouth Power Station Conversion SUP
 Project Location: Ukmouth Power Station, Northamptonshire

APPENDIX B – RPS CALCULATIONS

RPS Group Plc		Page 1
Technology Services Sherwood House, Sherwood Ave. Newark, Nottinghamshire,		
Date 17/03/2020 11:37 File SIMEC FUEL CONVERSION.MDX	Designed by louis.sime Checked by	

Innovyze Network 2019.1

STORM SEWER DESIGN by the Modified Rational Method

Design Criteria for Storm

Pipe Sizes STANDARD Manhole Sizes STANDARD

FEH Rainfall Model

Return Period (years)	2
FEH Rainfall Version	2013
Site Location GB 332964 183552 ST 32964 83552	
Data Type	Point
Maximum Rainfall (mm/hr)	50
Maximum Time of Concentration (mins)	30
Foul Sewage (l/s/ha)	0.000
Volumetric Runoff Coeff.	1.000
PIMP (%)	100
Add Flow / Climate Change (%)	0
Minimum Backdrop Height (m)	0.200
Maximum Backdrop Height (m)	1.500
Min Design Depth for Optimisation (m)	0.150
Min Vel for Auto Design only (m/s)	1.00
Min Slope for Optimisation (1:X)	500

Designed with Level Soffits

Time Area Diagram for Storm

Time (mins)	Area (ha)												
0-4	2.707	4-8	0.382	8-12	0.284	12-16	0.737	16-20	0.116	20-24	0.116	24-28	0.101

Total Area Contributing (ha) = 4.443

Total Pipe Volume (m³) = 456.428

Network Design Table for Storm

- Indicates pipe length does not match coordinates

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
----	------------	----------	-------------	-------------	-------------	-----------------	--------	---	----------	----------	--------------	-------------

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	Σ I.Area (ha)	Σ Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
----	--------------	-------------	-----------	---------------	-------------------	------------	----------------	-----------	-----------	------------

Technology Services
 Sherwood House, Sherwood Ave.
 Newark, Nottinghamshire,



Date 17/03/2020 11:37
 File SIMEC FUEL CONVERSION.MDX

Designed by louis.sime
 Checked by

Innovyze Network 2019.1

Network Design Table for Storm

PN	Length (m)	Fall (m)	Slope (1:X)	I.Area (ha)	T.E. (mins)	Base Flow (l/s)	k (mm)	n	HYD SECT	DIA (mm)	Section Type	Auto Design
1.000	65.429	0.082	797.9	0.291	10.00	0.0		0.045	3 \=/	900	1:3 Swale	
1.001	67.609	0.085	795.4	0.555	0.00	0.0		0.045	3 \=/	2400	1:3 Swale	
1.002	59.144	0.074	799.2	0.198	0.00	0.0		0.045	3 \=/	2600	1:3 Swale	
1.003	10.000#	0.013	769.2	0.184	0.00	0.0		0.045	3 \=/	3000	1:3 Swale	
2.000	63.517	0.079	804.0	0.329	5.00	0.0		0.045	3 \=/	1300	1:3 Swale	
2.001	59.175	0.074	799.7	0.184	0.00	0.0		0.045	3 \=/	1700	1:3 Swale	
2.002	10.000#	0.013	769.2	0.203	0.00	0.0		0.045	3 \=/	2300	1:3 Swale	
3.000	5.000#	0.017	300.0	0.275	5.00	0.0	0.600			300	Pipe/Conduit	
1.004	10.000#	0.260	38.5	2.224	0.00	0.0	0.600			375	Pipe/Conduit	

Network Results Table

PN	Rain (mm/hr)	T.C. (mins)	US/IL (m)	E I.Area (ha)	E Base Flow (l/s)	Foul (l/s)	Add Flow (l/s)	Vel (m/s)	Cap (l/s)	Flow (l/s)
1.000	32.62	16.05	7.100	0.291	0.0	0.0	0.0	0.18	36.5	34.3
1.001	27.26	21.70	7.018	0.846	0.0	0.0	0.0	0.20	85.4	83.3
1.002	24.01	26.61	6.933	1.044	0.0	0.0	0.0	0.20	91.8	90.5
1.003	23.56	27.42	6.859	1.228	0.0	0.0	0.0	0.21	107.0	104.5
2.000	40.98	10.66	7.100	0.329	0.0	0.0	0.0	0.19	49.1	48.7
2.001	32.97	15.76	7.021	0.513	0.0	0.0	0.0	0.19	62.3	61.1
2.002	32.01	16.59	6.947	0.716	0.0	0.0	0.0	0.20	83.5	82.8
3.000	50.00	5.09	6.900	0.275	0.0	0.0	0.0	0.90	63.8	49.7
1.004	50.00	5.06	6.800	0.000	30.0	0.0	0.0	2.93	323.6	30.0

Technology Services
Sherwood House, Sherwood Ave.
Newark, Nottinghamshire,



Date 17/03/2020 11:37
File SIMEC FUEL CONVERSION.MDX

Designed by louis.sime
Checked by

Innovyze Network 2019.1

Storage Structures for Storm

Tank or Pond Manhole: Stock Ditch, DS/PN: 1.004

Invert Level (m) 6.800

Depth (m)	Area (m ²)	Depth (m)	Area (m ²)
0.000	4278.0	0.600	5541.0

Technology Services Sherwood House, Sherwood Ave. Newark, Nottinghamshire,		
Date 17/03/2020 11:37 File SIMEC FUEL CONVERSION.MDX	Designed by louis.sime Checked by	

Innovyze	Network 2019.1
----------	----------------

100 year Return Period Summary of Critical Results by Maximum Level (Rank 1) for Storm

Simulation Criteria

Areal Reduction Factor	1.000	Additional Flow - % of Total Flow	0.000
Hot Start (mins)	0	MADD Factor * 10m ³ /ha Storage	2.000
Hot Start Level (mm)	0	Inlet Coefficient	0.800
Manhole Headloss Coeff (Global)	0.500	Flow per Person per Day (l/per/day)	0.000
Foul Sewage per hectare (l/s)	0.000		

Number of Input Hydrographs	0	Number of Storage Structures	1
Number of Online Controls	1	Number of Time/Area Diagrams	0
Number of Offline Controls	0	Number of Real Time Controls	0

Synthetic Rainfall Details

Rainfall Model	FEH
FEH Rainfall Version	2013
Site Location	GB 332964 183552 ST 32964 83552
Data Type	Point
Cv (Summer)	0.606
Cv (Winter)	0.801
Margin for Flood Risk Warning (mm)	50.0
Analysis Timestep	2.5 Second Increment (Extended)
DTS Status	ON
DVD Status	OFF
Inertia Status	OFF
Profile(s)	Summer and Winter
Duration(s) (mins)	60, 120, 180, 240, 360, 480, 600, 720, 960, 1440
Return Period(s) (years)	2, 30, 100
Climate Change (%)	0, 0, 40

PN	US/MH Name	Storm	Return Period	Climate Change	First (X) Surcharge	First (Y) Flood	First (Z) Overflow	Overflow Act.
1.000	S1.1	720 Winter	100	+40%				
1.001	S1.2	720 Winter	100	+40%				
1.002	S1.3	720 Winter	100	+40%				
1.003	S1.4	720 Winter	100	+40%				
2.000	S2.1	720 Winter	100	+40%				
2.001	S2.2	720 Winter	100	+40%				
2.002	S2.3	720 Winter	100	+40%				
3.000	SW1	720 Winter	100	+40%	100/60 Summer			
1.004	Stock Ditch	720 Winter	100	+40%	100/60 Winter			

Technology Services Sherwood House, Sherwood Ave. Newark, Nottinghamshire,	Designed by louis.sime Checked by	
Date 17/03/2020 11:37 File SIMEC FUEL CONVERSION.MDX		


Innovyze	Network 2019.1
----------	----------------

100 year Return Period Summary of Critical Results by Maximum Level (Rank 1) for Storm

PN	US/MH Name	Water Level (m)	Surcharged Depth (m)	Flooded Volume (m ³)	Flow / Cap. (l/s)	Overflow (l/s)	Pipe Flow (l/s)	Status	Level Exceeded
1.000	S1.1	7.361	-0.089	0.000	0.08		15.1		OK
1.001	S1.2	7.360	-0.090	0.000	0.07		41.7		OK
1.002	S1.3	7.360	-0.090	0.000	0.05		45.2		OK
1.003	S1.4	7.360	-0.090	0.000	0.04		47.2		OK
2.000	S2.1	7.360	-0.090	0.000	0.07		17.1		OK
2.001	S2.2	7.361	-0.089	0.000	0.05		23.9		OK
2.002	S2.3	7.361	-0.089	0.000	0.04		29.7		OK
3.000	SW1	7.361	0.161	0.000	0.31		14.3	SURCHARGED	
1.004	Stock Ditch	7.360	0.185	0.000	0.15		29.9	FLOOD RISK*	

Notes

1. This drawing has been prepared in accordance with the scope of RPS's appointment with its client and is subject to the terms and conditions of that appointment. RPS accepts no liability for any use of this document other than by its client and only for the purposes for which it was prepared and provided.
2. If viewed electronically it is the recipient's responsibility to print to correct scale. Only written dimensions should be used.
3. This drawing should be read in conjunction with all other relevant drawings and specifications.



P02	Amended in accordance with client comment.	MB	LJS	26.03.20
P01	First issue	CW	LJS	16.03.20
Rev	Description	By	Ckd	Date



Sherwood House, Sherwood Avenue,
Newark, Nottinghamshire, NG24 1QG
T:01639 665 700 E: rpsnewark@rpsgroup.com

Client



Project: Simec Uskmouth Power Station
Conversion SUP

Title: Existing Drainage


RPS Project Number	Scale @ A1	Date Created
NK019784	1:750	16.03.2020
Task Team Manager	Information Author	Task Information Manager
GB	CW	LJS

Status
S2 (Suitable for Information)
Document Number
019784-RPS-SI-ZZ-DR-D-0300
Revision
P02
Project Code - Originator - Zone - Level - Type - Role - Drawing Number
rpsgroup.com


- Notes:
1. This drawing has been prepared in accordance with the scope of RPS's agreement with the client and subject to the terms and conditions of that agreement. With respect to liability for any use of this document other than for the purposes intended by RPS, the project owner shall be deemed to warrant and provide.
 2. Structural engineering is the responsible party to provide to correctable. Only written dimensions should be used.
 3. This drawing should be read in conjunction with all other relevant drawings and specifications.

Key:

- FW Main (6D & Gradient)
- SW Main (6D & Gradient)
- Linear Drainage
- SW Manhole
- Area of existing drainage enhancement
- Contaminant area
- Headwall
- Attenuation Pond/Ditch
- Grassed Conveyance Swale



Section B-B
Typical section through remediated existing intercepter ditch
Scale 1:25



Section A-A
Typical section through proposed conveyance swale
Scale 1:25

Rev	Description	By	Chk	Date
01	Approved in accordance with department.	MH	LJH	20.03.20
02	Final issue	CW	LJH	16.03.2020

RPS RANKING COMPLEX EAST

Shenwood House, Shenwood campus,
Shenwood, Northamptonshire, NN4 5GG
T 01606 805 700 E rps@rpsgroup.com

Client: **SMIC ATLANTIS** RESORT

Project: **Simec Ukmouth Power Station Conversion SUP**

Title: **Indicative Drainage Layout**

RPS Project Number: N0029764	Scale: A3	Date Created: 16.03.2020
Task Team Manager: CJB	Author: CJB	Task Reviewer: LJH
Scale: S2 (Suitable for Information)	Client/Reference: 019784-RPS-S1ZZ-DR-D-0301	Revision: P02

Project Date: 03/04/2020
Project Name: Ukmouth Power Station Conversion
Project Location: Shenwood, Northamptonshire
Project Status: Final Design