



# Appendix 6:

# Energy Efficiency

---

Environmental Permit Bespoke Application

H.B.J Farms

**BERRYS**

T: 01432 809830 | E: [hereford@berrys.uk.com](mailto:hereford@berrys.uk.com) | [berrys.uk.com](http://berrys.uk.com)

Contents

---

1. Energy Usage .....3

2. Heating .....3

3. Electricity .....4

4. Fuel Oil .....4

5. Other (Biomass Boiler System).....4

6. Breakdown .....4

## 1. Energy Usage

---

Energy Source	Use
Mains electricity	Lighting, ventilation, computer control systems, feed augers, water pumps
Biomass System	Heating sheds.
Diesel	Standby generator and backup electric system
Gas	Standby gas boilers and backup heating system

## 2. Heating

---

The correct environment for the birds is maintained in the sheds through a combination of heating using the biomass boiler system and ventilation fans located in the roofs, side inlets and gable ends.

Each shed will be / is monitored by a computer system, which automatically controls and records the humidity and the temperature. Control sensors are checked regularly and kept clean so they are able to detect the temperature at the stock level. Ventilation rates are computer controlled to minimise, as far as the indoor requirements allow heat losses from the sheds. Most of the year the roof fans will provide adequate ventilation within the existing sheds, with the gable fans required during the latter stages of the cropping cycle and in very hot weather. Fans are fitted with back draft shutters to reduce heat loss.

The new sheds will be fully insulated with a U-Value of approximately 0.4 W/m<sup>2</sup>/°C to reduce condensation and heat lost. This insulation is contained within the existing poultry building.

The sheds will be constructed to ensure litter is dry and friable, and reduce the need to heat the sheds to keep the litter dry.

The sheds will be maintained in good condition, cracks and open seams will be repaired. The concrete flooring will be maintained and cracks will be repaired. Each shed will have a damp proof course. Nipple drinking system reduces spillage of water.

There is a backup gas boiler and heating system in case of a breakdown.

### 3. Electricity

---

The ventilation fans have been selected so that they are appropriate in power and size for the sheds. The computer control systems control the ventilation for maximum efficiency i.e. one fan operating at full capacity rather than two operating at half their capacity. The fans are regularly maintained, and cleared of debris.

Low energy light bulbs will be used in the control areas and stores. Fluorescent lights will be used in the sheds. A variable lighting period will be used during the crop cycle.

A diesel run back-up generator will be used in case of a power cut. This will have an automatic change over and will also swap back once the power shortage is over.

### 4. Fuel Oil

---

The standby generator will be regularly maintained in accordance with the manufacturers' instructions to ensure it operates efficiently.

### 5. Other (Biomass Boiler System)

---

The heating in the broiler houses will be provided via a biomass boiler heat system in each shed. This system is maintained by the installation company.

### 6. Breakdown

---

A breakdown of delivered and primary energy consumption will be recorded and provided to Natural Resources Wales annually in the following format:

Energy Source Delivered MWh	Energy Consumption Primary MWh	% of Total
Electricity		
Oil		
Gas		
Other (Ground Source)		
Exported Energy	MWh	Source
	N/A	N/A