

Permit Reference Number: EPR/BV58581W

Operator: Abril Industrial Waxes Ltd

Installation: 17A Sturmi Way, Village Farm Industrial Estate,
Pyle, Bridgend. CF33 6BZ

Form Number: A1 Dated 19/06/2014

Reporting of Emissions to Air for the 3 month period from 1st April 2021 to 30th June 2021

Date	Parameters			Total number of days
	Number of days deposits seen	Number of days no deposits seen		
Release point A2				
Month 1	Nil	20		20
Month 2	Nil	14		14
Month 3	Nil	20		20
Quarter Total	Nil	54		54
Release point A3				
Month 1	Nil	17		17
Month 2	Nil	14		14
Month 3	Nil	20		20
Quarter Total	Nil	51		51
Release point A4				
Month 1				0
Month 2				0
Month 3				0
Quarter Total				0
Release point A12				
Month 1	Nil	9		9
Month 2	Nil	5		5
Month 3	Nil	20		20
Quarter Total	Nil	34		34

Signed 
(authorised to sign as representative of the Operator)

Date 01-07-21

Permit Reference Number: EPR/BV/58581W

Operator: Abril Industrial Waxes Ltd

Installation: 17A Sturmi Way, Village Farm Industrial Estate,
Pyle, Bridgend. CF33 6BZ

Form Number: S1 Dated 19/06/2014

Reporting of Emissions to Sewer for the period from 1st April 2021 to 30th June 2021

Emission Point	Substance / Parameter	Emission Limit Value	Result ^[1]			Test Method ^[2]	Sample Date and Times ^[3]	Accreditation / Certification ^[4]	Uncertainty ^[5]
			Month1	Month2	Month3				
S1	Suspended solids (maximum)	400mg/l	94	193	32	Abril Test Method 005	01/04; 13/05; 14/06.	Calibrated Balance	± 1 mg/l
	Suspended solids (mean)	No limit	94	193	32	Abril Test Method 005	01/04; 13/05; 14/06.	Calibrated Balance	± 1 mg/l
	pH	6 ^[7]	8	7	8	pH meter	01/04; 13/05; 14/06.	pH standards	± 0.1
	pH	10 ^[7]	8	7	8	pH meter	01/04; 13/05; 14/06.	pH standards	± 0.1
	Chemical oxygen demand (maximum)	20000 mg/l	9480	12080	11380	Abril Test Method 005	01/04; 13/05; 14/06.	Calibrated Balance	± 500 mg/l
	Chemical oxygen demand (mean)	No limit	7353	9406	7913	Abril Test Method 005	01/04; 13/05; 14/06.	Calibrated Balance	± 500 mg/l
	Temperature	43 °C ^[6]	17	16	20	Thermometer	01/04; 13/05; 14/06.	Calibrated Thermometer	± 1 °C
	Oil & grease	150 mg/l ^[6]	11	53	8	Abril Test Method 023	01/04; 13/05; 14/06.	Calibrated Balance	± 10 mg/l
	Flow	1000 l/day ^[6]	950	900	950	Calculation	01/04; 13/05; 14/06.	Calibration	

^[1] The result given is the maximum value (or the minimum value in the case of a limit that is expressed as a minimum) obtained during the reporting period, expressed in the same terms as the emission limit value. Where the emission limit value is expressed as a range, the result is given as the 'minimum - maximum' measured values.

^[2] Where an internationally recognised standard test method is used the reference number is given. Where another method that has been formally agreed with Natural Resources Wales is used, then the appropriate identifier is given. In other cases the principal technique is stated, e.g. colorimetry.

^[3] For non-continuous measurements the date and time of the sample that produced the result is given. For continuous measurements, or flow/time proportional samples, the percentage of the process operating time covered by the monitoring is given.

^[4] The accreditation status of the equipment and/or the monitoring organisation, as appropriate, for the methods used for both sampling and analysis.

^[5] The uncertainty associated with the quoted result at the 95% confidence interval, unless otherwise stated.

^[6] The emission limit values are expressed as monthly maxima.

^[7] The emission limit values for pH are expressed as minimum and maximum individual values.

Signed
(authorised to sign as representative of the Operator)

Date 01-07-21