



Unit 7-8 Hawarden Business Park

Manor Road (off Manor Lane)

Hawarden

Deeside

CH5 3US

Tel: (01244) 528700

Fax: (01244) 528701

email: hawardencustomerservices@alsglobal.com

Website: www.alsenvironmental.co.uk

Atkins Global Ltd
Project Jonah site office
Llan Coed House
Suite 24
Coed Darcy
Llandarcy
SA10 6HJ

Attention: John Fitzgerald

CERTIFICATE OF ANALYSIS

Date of report Generation: 31 December 2020
Customer: Atkins Global Ltd
Sample Delivery Group (SDG): 201219-61
Your Reference:
Location: Llanwern
Report No: 581970

We received 2 samples on Saturday December 19, 2020 and 2 of these samples were scheduled for analysis which was completed on Thursday December 31, 2020. Accredited laboratory tests are defined within the report, but opinions, interpretations and on-site data expressed herein are outside the scope of ISO 17025 accreditation.

Should this report require incorporation into client reports, it must be used in its entirety and not simply with the data sections alone.

Chemical testing (unless subcontracted) performed at ALS Life Sciences Ltd Hawarden (Method codes TM) or ALS Life Sciences Ltd Aberdeen (Method codes S).

All sample data is provided by the customer. The reported results relate to the sample supplied, and on the basis that this data is correct.

Incorrect sampling dates and/or sample information will affect the validity of results.

The customer is not permitted to reproduce this report except in full without the approval of the laboratory.

Approved By:

Sonia McWhan

Operations Manager





CERTIFICATE OF ANALYSIS

Validated

SDG: 201219-61
Location: Llanwern

Client Reference:
Order Number: LLA808

Report Number: 581970
Superseded Report:

Received Sample Overview

Lab Sample No(s)	Customer Sample Ref.	AGS Ref.	Depth (m)	Sampled Date
23471885	ML-N		0.00 - 0.00	18/12/2020
23471904	ML-S		0.00 - 0.00	18/12/2020

Only received samples which have had analysis scheduled will be shown on the following pages.



CERTIFICATE OF ANALYSIS

Validated

SDG: 201219-61
Location: Llanwern

Client Reference:
Order Number: LLA808

Report Number: 581970
Superseded Report:

Results Legend



Test


No Determination
Possible

Sample Types -

S - Soil/Solid
 UNS - Unspecified Solid
 GW - Ground Water
 SW - Surface Water
 LE - Land Leachate
 PL - Prepared Leachate
 PR - Process Water
 SA - Saline Water
 TE - Trade Effluent
 TS - Treated Sewage
 US - Untreated Sewage
 RE - Recreational Water
 DW - Drinking Water Non-regulatory
 UNL - Unspecified Liquid
 SL - Sludge
 G - Gas
 OTH - Other

Lab Sample No(s)

Customer
Sample Reference

AGS Reference

Depth (m)

Container

Sample Type

Turbidity in waters

All

NDPs: 0
Tests: 2

X

X

VOC MS (W)

All

NDPs: 0
Tests: 2

X

X



CERTIFICATE OF ANALYSIS

Validated

SDG: 201219-61
Location: Llanwern

Client Reference:
Order Number: LLA808

Report Number: 581970
Superseded Report:

Results Legend			Customer Sample Ref.		ML-N	ML-S				
#	ISO17025 accredited.		Depth (m) Sample Type Date Sampled Sample Time Date Received SDG Ref Lab Sample No.(s) AGS Reference		0.00 - 0.00	0.00 - 0.00				
M	mCERTS accredited.				Surface Water (SW)	Surface Water (SW)				
aq	Aqueous / settled sample.				18/12/2020	18/12/2020				
diss.filt	Dissolved / filtered sample.				00:00	00:00				
tot.unfilt	Total / unfiltered sample.				19/12/2020	19/12/2020				
*	Subcontracted - refer to subcontractor report for accreditation status.				201219-61	201219-61				
**	% recovery of the surrogate standard to check the efficiency of the method. The results of individual compounds within samples aren't corrected for the recovery				23471885	23471904				
(F)	Trigger breach confirmed									
1-4*5@	Sample deviation (see appendix)									
Component	LOD/Units	Method								
Suspended solids, Total	<2 mg/l	TM022	24.5		12					
			#		#					
BOD, unfiltered	<1 mg/l	TM045	<1		<1					
			#		#					
Oxygen, dissolved	<0.3 mg/l	TM046	10.1		10					
Carbon, Organic (diss.filt)	<3 mg/l	TM090	8.06		9.03					
Organic Carbon, Total	<3 mg/l	TM090	6.89		6.62					
			#		#					
Ammoniacal Nitrogen as NH4	<0.3 mg/l	TM099	1.3		1.3					
			#		#					
Sulphide	<0.01 mg/l	TM101	<0.01		<0.01					
Fluoride	<0.5 mg/l	TM104	0.652		0.63					
COD, unfiltered	<7 mg/l	TM107	22.6		<7					
			#		#					
Redox potential	mV	TM110	154		153					
Conductivity @ 20 deg.C (diss.filt)	<0.02 mS/cm	TM120	0.583		0.57					
Dissolved solids, Total (meter)	<5 mg/l	TM123	492		470					
			#		#					
Antimony (diss.filt)	<1 µg/l	TM152	<1		<1					
			#		#					
Antimony (tot.unfilt)	<4 µg/l	TM152	<4		<4					
			#		#					
Arsenic (diss.filt)	<0.5 µg/l	TM152	2.25		1.91					
			#		#					
Arsenic (tot.unfilt)	<2 µg/l	TM152	5.55		3.23					
			#		#					
Barium (diss.filt)	<0.2 µg/l	TM152	45.9		46.5					
			#		#					
Barium (tot.unfilt)	<0.5 µg/l	TM152	60.1		62.5					
			#		#					
Beryllium (diss.filt)	<0.1 µg/l	TM152	<0.1		<0.1					
			#		#					
Beryllium (tot.unfilt)	<1 µg/l	TM152	<1		<1					
			#		#					
Boron (diss.filt)	<10 µg/l	TM152	103		103					
			#		#					
Boron (tot.unfilt)	<20 µg/l	TM152	114		109					
			#		#					
Cadmium (diss.filt)	<0.08 µg/l	TM152	<0.08		<0.08					
			#		#					
Cadmium (tot.unfilt)	<0.5 µg/l	TM152	<0.5		<0.5					
			#		#					
Chromium (tot.unfilt)	<3 µg/l	TM152	<3		<3					
			#		#					
Chromium (diss.filt)	<1 µg/l	TM152	<1		<1					
			#		#					
Copper (tot.unfilt)	<1 µg/l	TM152	3.9		3.36					
			#		#					
Copper (diss.filt)	<0.3 µg/l	TM152	2.83		1.69					
			#		#					
Manganese (tot.unfilt)	<1 µg/l	TM152	63.7		57.3					
			#		#					
Lead (diss.filt)	<0.2 µg/l	TM152	0.377		<0.2					
			#		#					
Nickel (tot.unfilt)	<1 µg/l	TM152	3.2		3.55					
			#		#					
Manganese (diss.filt)	<3 µg/l	TM152	13.2		7.86					
			#		#					
Phosphorus (tot.unfilt)	<20 µg/l	TM152	57.2		49					
			#		#					



CERTIFICATE OF ANALYSIS

Validated

SDG: 201219-61
Location: Llanwern

Client Reference:
Order Number: LLA808

Report Number: 581970
Superseded Report:

Results Legend		Customer Sample Ref.	ML-N	ML-S				
#	ISO17025 accredited.	Depth (m) Sample Type Date Sampled Sample Time Date Received SDG Ref Lab Sample No.(s) AGS Reference						
M	mCERTS accredited.							
aq	Aqueous / settled sample.							
diss.filt	Dissolved / filtered sample.							
tot.unfilt	Total / unfiltered sample.							
*	Subcontracted - refer to subcontractor report for accreditation status.							
**	% recovery of the surrogate standard to check the efficiency of the method. The results of individual compounds within samples aren't corrected for the recovery							
(F)	Trigger breach confirmed							
1-4+§@	Sample deviation (see appendix)							
Component	LOD/Units	Method						
Selenium (tot.unfilt)	<1 µg/l	TM152	1.82	1.74				
			#	#				
Nickel (diss.filt)	<0.4 µg/l	TM152	2.32	1.99				
			#	#				
Phosphorus (diss.filt)	<10 µg/l	TM152	13.4	11.4				
			#	#				
Selenium (diss.filt)	<1 µg/l	TM152	1.44	1.2				
			#	#				
Vanadium (tot.unfilt)	<5 µg/l	TM152	14	11.2				
			#	#				
Zinc (tot.unfilt)	<5 µg/l	TM152	80.8	18.1				
			#	#				
Vanadium (diss.filt)	<1 µg/l	TM152	8.93	7.59				
			#	#				
Zinc (diss.filt)	<1 µg/l	TM152	48.1	1.07				
			#	#				
Lead (tot.unfilt)	<0.001 mg/l	TM152	0.00408	0.00296				
			#	#				
Magnesium (Dis.Filt)	<0.036 mg/l	TM152	7	7.18				
			#	#				
Calcium (Dis.Filt)	<0.2 mg/l	TM152	79.1	80.2				
			#	#				
Iron (Dis.Filt)	<0.019 mg/l	TM152	0.0501	0.024				
			#	#				
Hardness, Total as CaCO3	<0.65 mg/l	TM152	226	230				
Magnesium (Tot. Unfilt.)	<0.05 mg/l	TM152	8.07	7.88				
			#	#				
Calcium (Tot. Unfilt.)	<0.057 mg/l	TM152	102	100				
			#	#				
Iron (Tot. Unfilt.)	<0.024 mg/l	TM152	0.716	0.591				
			#	#				
Naphthalene (diss.filt)	<0.01 µg/l	TM178	0.0775	0.0839				
Acenaphthene (diss.filt)	<0.005 µg/l	TM178	0.0721	0.079				
Acenaphthylene (diss.filt)	<0.005 µg/l	TM178	0.0144	0.0155				
Fluoranthene (diss.filt)	<0.005 µg/l	TM178	0.0222	0.022				
Anthracene (diss.filt)	<0.005 µg/l	TM178	0.00778	0.00667				
Phenanthrene (diss.filt)	<0.005 µg/l	TM178	0.0463	0.0487				
Fluorene (diss.filt)	<0.005 µg/l	TM178	0.0244	0.027				
Chrysene (diss.filt)	<0.005 µg/l	TM178	<0.005	<0.005				
Pyrene (diss.filt)	<0.005 µg/l	TM178	0.0177	0.02				
Benzo(a)anthracene (diss.filt)	<0.005 µg/l	TM178	<0.005	<0.005				
Benzo(b)fluoranthene (diss.filt)	<0.005 µg/l	TM178	<0.005	<0.005				
Benzo(k)fluoranthene (diss.filt)	<0.005 µg/l	TM178	<0.005	<0.005				
Benzo(a)pyrene (diss.filt)	<0.002 µg/l	TM178	<0.002	<0.002				
Dibenzo(a,h)anthracene (diss.filt)	<0.005 µg/l	TM178	<0.005	<0.005				
Benzo(g,h,i)perylene (diss.filt)	<0.005 µg/l	TM178	<0.005	<0.005				
Indeno(1,2,3-cd)pyrene (diss.filt)	<0.005 µg/l	TM178	<0.005	<0.005				
PAH Sum of EPA 16 detected (Diss.filt)	<0.082 µg/l	TM178	0.282	0.303				



CERTIFICATE OF ANALYSIS

Validated

SDG: 201219-61
Location: Llanwern

Client Reference:
Order Number: LLA808

Report Number: 581970
Superseded Report:

SVOC MS (W) - Aqueous

Results Legend			Customer Sample Ref.		ML-N	ML-S				
#	ISO17025 accredited.		Depth (m) Sample Type Date Sampled Sample Time Date Received SDG Ref Lab Sample No.(s) AGS Reference		0.00 - 0.00	0.00 - 0.00				
M	mCERTS accredited.				Surface Water (SW)	Surface Water (SW)				
aq	Aqueous / settled sample.				18/12/2020	18/12/2020				
diss.filt	Dissolved / filtered sample.				00:00	00:00				
tot.unfilt	Total / unfiltered sample.				19/12/2020	19/12/2020				
+	Subcontracted - refer to subcontractor report for accreditation status.				201219-61	201219-61				
**	% recovery of the surrogate standard to check the efficiency of the method. The results of individual compounds within samples aren't corrected for the recovery				23471885	23471904				
(F)	Trigger breach confirmed									
1-4*5@	Sample deviation (see appendix)									
Component	LOD/Units	Method								
1,2,4-Trichlorobenzene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
1,2-Dichlorobenzene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
1,3-Dichlorobenzene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
1,4-Dichlorobenzene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2,4,5-Trichlorophenol (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2,4,6-Trichlorophenol (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2,4-Dichlorophenol (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2,4-Dimethylphenol (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2,4-Dinitrotoluene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2,6-Dinitrotoluene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2-Chloronaphthalene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2-Chlorophenol (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2-Methylnaphthalene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2-Methylphenol (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2-Nitroaniline (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
2-Nitrophenol (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
3-Nitroaniline (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
4-Bromophenylphenylether (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
4-Chloro-3-methylphenol (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
4-Chloroaniline (aq)	<1 µg/l	TM176			<1	<1				
4-Chlorophenylphenylether (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
4-Methylphenol (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
4-Nitroaniline (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
4-Nitrophenol (aq)	<1 µg/l	TM176			<1	<1				
Azobenzene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
bis(2-Chloroethyl)ether (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
bis(2-Chloroethoxy)methane (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
bis(2-Ethylhexyl) phthalate (aq)	<2 µg/l	TM176			<2	<2				
					#	#				
Butylbenzyl phthalate (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
Benzo(k)fluoranthene (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
Carbazole (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
Dibenzofuran (aq)	<1 µg/l	TM176			<1	<1				
					#	#				
n-Dibutyl phthalate (aq)	<1 µg/l	TM176			<1	<1				
					#	#				



CERTIFICATE OF ANALYSIS

Validated

SDG: 201219-61
Location: LlanwernClient Reference:
Order Number: LLA808Report Number: 581970
Superseded Report:

TPH CWG (W)

Results Legend			Customer Sample Ref.		ML-N	ML-S				
#	ISO17025 accredited.		Depth (m) Sample Type Date Sampled Sample Time Date Received SDG Ref Lab Sample No.(s) AGS Reference		0.00 - 0.00	0.00 - 0.00				
M	mCERTS accredited.				Surface Water (SW)	Surface Water (SW)				
aq	Aqueous / settled sample.				18/12/2020	18/12/2020				
diss.filt	Dissolved / filtered sample.				00:00	00:00				
tot.unfilt	Total / unfiltered sample.				19/12/2020	19/12/2020				
*	Subcontracted - refer to subcontractor report for accreditation status.				201219-61	201219-61				
**	% recovery of the surrogate standard to check the efficiency of the method. The results of individual compounds within samples aren't corrected for the recovery				23471885	23471904				
(F)	Trigger breach confirmed									
1-4*5@	Sample deviation (see appendix)									
Component	LOD/Units	Method								
GRO Surrogate % recovery**	%	TM245			98	106				
GRO >C5-C12	<50 µg/l	TM245			<50	<50				
Methyl tertiary butyl ether (MTBE)	<3 µg/l	TM245			#	#				
Benzene	<7 µg/l	TM245			<3	<3				
Toluene	<4 µg/l	TM245			#	#				
Ethylbenzene	<5 µg/l	TM245			<7	<7				
m,p-Xylene	<8 µg/l	TM245			#	#				
o-Xylene	<3 µg/l	TM245			<4	<4				
Sum of detected Xylenes	<11 µg/l	TM245			#	#				
Sum of detected BTEX	<28 µg/l	TM245			<5	<5				
Aliphatics >C5-C6	<10 µg/l	TM245			<8	<8				
Aliphatics >C6-C8	<10 µg/l	TM245			<3	<3				
Aliphatics >C8-C10	<10 µg/l	TM245			#	#				
Aliphatics >C10-C12	<10 µg/l	TM245			<11	<11				
Aliphatics >C12-C16 (aq)	<10 µg/l	TM174			<28	<28				
Aliphatics >C16-C21 (aq)	<10 µg/l	TM174			<10	<10				
Aliphatics >C21-C35 (aq)	<10 µg/l	TM174			<10	<10				
Total Aliphatics >C12-C35 (aq)	<10 µg/l	TM174			<10	<10				
Aromatics >EC5-EC7	<10 µg/l	TM245			<10	<10				
Aromatics >EC7-EC8	<10 µg/l	TM245			<10	<10				
Aromatics >EC8-EC10	<10 µg/l	TM245			<10	<10				
Aromatics >EC10-EC12	<10 µg/l	TM245			<10	<10				
Aromatics >EC12-EC16 (aq)	<10 µg/l	TM174			<10	<10				
Aromatics >EC16-EC21 (aq)	<10 µg/l	TM174			<10	<10				
Aromatics >EC21-EC35 (aq)	<10 µg/l	TM174			<10	<10				
Total Aromatics >EC12-EC35 (aq)	<10 µg/l	TM174			<10	<10				
Total Aliphatics & Aromatics >C5-35 (aq)	<10 µg/l	TM174			<10	42				
Aliphatics >C16-C35 Aqueous	<10 µg/l	TM174			<10	42				



CERTIFICATE OF ANALYSIS

Validated

SDG: 201219-61
Location: Llanwern

Client Reference:
Order Number: LLA808

Report Number: 581970
Superseded Report:

VOC MS (W)

Results Legend			Customer Sample Ref.		ML-N		ML-S					
#	ISO17025 accredited.		Depth (m) Sample Type Date Sampled Sample Time Date Received SDG Ref Lab Sample No.(s) AGS Reference	0.00 - 0.00 Surface Water (SW) 18/12/2020 00:00 19/12/2020 201219-61 23471885	0.00 - 0.00 Surface Water (SW) 18/12/2020 00:00 19/12/2020 201219-61 23471904							
M	mCERTS accredited.											
aq	Aqueous / settled sample.											
diss.filt	Dissolved / filtered sample.											
tot.unfilt	Total / unfilted sample.											
*	Subcontracted - refer to subcontractor report for accreditation status.											
**	% recovery of the surrogate standard to check the efficiency of the method. The results of individual compounds within samples aren't corrected for the recovery											
(F)	Trigger breach confirmed											
1-4*5@	Sample deviation (see appendix)											
Component	LOD/Units	Method										
Dibromofluoromethane**	%	TM208		114	111							
Toluene-d8**	%	TM208		99.2	100							
4-Bromofluorobenzene**	%	TM208		95.1	96.2							
Dichlorodifluoromethane	<1 µg/l	TM208		<1	<1							
Chloromethane	<1 µg/l	TM208		<1	<1							
Vinyl chloride	<1 µg/l	TM208		<1	<1							
Bromomethane	<1 µg/l	TM208		<1	<1							
Chloroethane	<1 µg/l	TM208		<1	<1							
Trichlorofluoromethane	<1 µg/l	TM208		<1	<1							
1,1-Dichloroethene	<1 µg/l	TM208		<1	<1							
Carbon disulphide	<1 µg/l	TM208		<1	<1							
Dichloromethane	<3 µg/l	TM208		<3	<3							
Methyl tertiary butyl ether (MTBE)	<1 µg/l	TM208		<1	<1							
trans-1,2-Dichloroethene	<1 µg/l	TM208		<1	<1							
1,1-Dichloroethane	<1 µg/l	TM208		<1	<1							
cis-1,2-Dichloroethene	<1 µg/l	TM208		<1	<1							
2,2-Dichloropropane	<1 µg/l	TM208		<1	<1							
Bromochloromethane	<1 µg/l	TM208		<1	<1							
Chloroform	<1 µg/l	TM208		<1	<1							
1,1,1-Trichloroethane	<1 µg/l	TM208		<1	<1							
1,1-Dichloropropene	<1 µg/l	TM208		<1	<1							
Carbontetrachloride	<1 µg/l	TM208		<1	<1							
1,2-Dichloroethane	<1 µg/l	TM208		<1	<1							
Benzene	<1 µg/l	TM208		<1	<1							
Trichloroethene	<1 µg/l	TM208		<1	<1							
1,2-Dichloropropane	<1 µg/l	TM208		<1	<1							
Dibromomethane	<1 µg/l	TM208		<1	<1							
Bromodichloromethane	<1 µg/l	TM208		<1	<1							
cis-1,3-Dichloropropene	<1 µg/l	TM208		<1	<1							
Toluene	<1 µg/l	TM208		<1	<1							
trans-1,3-Dichloropropene	<1 µg/l	TM208		<1	<1							
1,1,2-Trichloroethane	<1 µg/l	TM208		<1	<1							
1,3-Dichloropropane	<1 µg/l	TM208		<1	<1							



CERTIFICATE OF ANALYSIS

Validated

SDG: 201219-61
Location: LlanwernClient Reference:
Order Number: LLA808Report Number: 581970
Superseded Report:

VOC MS (W)

Results Legend			Customer Sample Ref.		ML-N	ML-S				
#	ISO17025 accredited.		Depth (m) Sample Type Date Sampled Sample Time Date Received SDG Ref Lab Sample No.(s) AGS Reference		0.00 - 0.00	0.00 - 0.00				
M	mCERTS accredited.				Surface Water (SW)	Surface Water (SW)				
sq	Aqueous / settled sample.				18/12/2020	18/12/2020				
diss.filt	Dissolved / filtered sample.				00:00	00:00				
tot.unfilt	Total / unfiltered sample.				19/12/2020	19/12/2020				
*	Subcontracted - refer to subcontractor report for accreditation status.				201219-61	201219-61				
**	% recovery of the surrogate standard to check the efficiency of the method. The results of individual compounds within samples aren't corrected for the recovery				23471885	23471904				
(F)	Trigger breach confirmed									
1-4+§@	Sample deviation (see appendix)									
Component	LOD/Units	Method								
Tetrachloroethene	<1 µg/l	TM208			<1	<1				
					#	#				
Dibromochloromethane	<1 µg/l	TM208			<1	<1				
					#	#				
1,2-Dibromoethane	<1 µg/l	TM208			<1	<1				
					#	#				
Chlorobenzene	<1 µg/l	TM208			<1	<1				
					#	#				
1,1,1,2-Tetrachloroethane	<1 µg/l	TM208			<1	<1				
					#	#				
Ethylbenzene	<1 µg/l	TM208			<1	<1				
					#	#				
m,p-Xylene	<1 µg/l	TM208			<1	<1				
					#	#				
o-Xylene	<1 µg/l	TM208			<1	<1				
					#	#				
Styrene	<1 µg/l	TM208			<1	<1				
					#	#				
Bromoform	<1 µg/l	TM208			<1	<1				
					#	#				
Isopropylbenzene	<1 µg/l	TM208			<1	<1				
					#	#				
1,1,2,2-Tetrachloroethane	<1 µg/l	TM208			<1	<1				
					#	#				
1,2,3-Trichloropropane	<1 µg/l	TM208			<1	<1				
					#	#				
Bromobenzene	<1 µg/l	TM208			<1	<1				
					#	#				
Propylbenzene	<1 µg/l	TM208			<1	<1				
					#	#				
2-Chlorotoluene	<1 µg/l	TM208			<1	<1				
					#	#				
1,3,5-Trimethylbenzene	<1 µg/l	TM208			<1	<1				
					#	#				
4-Chlorotoluene	<1 µg/l	TM208			<1	<1				
					#	#				
tert-Butylbenzene	<1 µg/l	TM208			<1	<1				
					#	#				
1,2,4-Trimethylbenzene	<1 µg/l	TM208			<1	<1				
					#	#				
sec-Butylbenzene	<1 µg/l	TM208			<1	<1				
					#	#				
4-iso-Propyltoluene	<1 µg/l	TM208			<1	<1				
					#	#				
1,3-Dichlorobenzene	<1 µg/l	TM208			<1	<1				
					#	#				
1,4-Dichlorobenzene	<1 µg/l	TM208			<1	<1				
					#	#				
n-Butylbenzene	<1 µg/l	TM208			<1	<1				
					#	#				
1,2-Dichlorobenzene	<1 µg/l	TM208			<1	<1				
					#	#				
1,2-Dibromo-3-chloropropane	<1 µg/l	TM208			<1	<1				
1,2,4-Trichlorobenzene	<1 µg/l	TM208			<1	<1				
					#	#				
Hexachlorobutadiene	<1 µg/l	TM208			<1	<1				
					#	#				
tert-Amyl methyl ether (TAME)	<1 µg/l	TM208			<1	<1				
					#	#				
Naphthalene	<1 µg/l	TM208			<1	<1				
					#	#				
1,2,3-Trichlorobenzene	<1 µg/l	TM208			<1	<1				
					#	#				
1,3,5-Trichlorobenzene	<1 µg/l	TM208			<1	<1				



CERTIFICATE OF ANALYSIS

Validated

SDG: 201219-61
Location: Llanwern

Client Reference:
Order Number: LLA808

Report Number: 581970
Superseded Report:

Table of Results - Appendix

Method No	Reference	Description
TM022	Method 2540D, AWWA/APHA, 20th Ed., 1999 / BS 2690: Part120 1981;BS EN 872	Determination of total suspended solids in waters
TM045	MEWAM BOD5 2nd Ed.HMSO 1988 / Method 5210B, AWWA/APHA, 20th Ed., 1999; SCA Blue Book 130	Determination of BOD5 (ATU) Filtered by Oxygen Meter on liquids
TM046	Method 4500G, AWWA/APHA, 20th Ed., 1999	Measurement of Dissolved Oxygen by Oxygen Meter
TM090	Method 5310, AWWA/APHA, 20th Ed., 1999 / Modified: US EPA Method 415.1 & 9060	Determination of Total Organic Carbon/Total Inorganic Carbon in Water and Waste Water
TM099	BS 2690: Part 7:1968 / BS 6068: Part2.11:1984	Determination of Ammonium in Water Samples using the Kone Analyser
TM101	Method 4500B & C, AWWA/APHA, 20th Ed., 1999	Determination of Sulphide in soil and water samples using the Kone Analyser
TM104	Method 4500F, AWWA/APHA, 20th Ed., 1999	Determination of Fluoride using the Kone Analyser
TM107	ISO 6060-1989	Determination of Chemical Oxygen Demand using COD Dr Lange Kit
TM110	BS 1377: Part 3 1990	Redox Potential
TM120	Method 2510B, AWWA/APHA, 20th Ed., 1999 / BS 2690: Part 9:1970	Determination of Electrical Conductivity using a Conductivity Meter
TM123	BS 2690: Part 121:1981	The Determination of Total Dissolved Solids in Water
TM152	Method 3125B, AWWA/APHA, 20th Ed., 1999	Analysis of Aqueous Samples by ICP-MS
TM174	Analysis of Petroleum Hydrocarbons in Environmental Media – Total Petroleum Hydrocarbon Criteria	Determination of Speciated Extractable Petroleum Hydrocarbons in Waters by GC-FID
TM176	EPA 8270D Semi-Volatile Organic Compounds by Gas Chromatography/Mass Spectrometry (GC/MS)	Determination of SVOCs in Water by GCMS
TM178	Modified: US EPA Method 8100	Determination of Polynuclear Aromatic Hydrocarbons (PAH) by GC-MS in Waters
TM183	BS EN 23506:2002, (BS 6068-2.74:2002) ISBN 0 580 38924 3	Determination of Trace Level Mercury in Waters and Leachates by PSA Cold Vapour Atomic Fluorescence Spectrometry
TM184	EPA Methods 325.1 & 325.2,	The Determination of Anions in Aqueous Matrices using the Kone Spectrophotometric Analysers
TM195	Colour and Turbidity of water. Methods for the Examination of Waters and Associated Materials. HMSO, 1981, ISBN 0 11 751955 3.	Determination of Turbidity in Waters & Associated Matrices
TM208	Modified: US EPA Method 8260b & 624	Determination of Volatile Organic Compounds by Headspace / GC-MS in Waters
TM227	Standard methods for the examination of waters and wastewaters 20th Edition, AWWA/APHA Method 4500.	Determination of Total Cyanide, Free (Easily Liberatable) Cyanide and Thiocyanate
TM228	US EPA Method 6010B	Determination of Major Cations in Water by iCap 6500 Duo ICP-OES
TM241	Methods for the Examination of Waters and Associated Materials; Chromium in Raw and Potable Waters and Sewage Effluents 1980.	The Determination of Hexavalent Chromium in Waters and Leachates using the Kone Analyser
TM245	By GC-FID	Determination of GRO by Headspace in waters
TM256	The measurement of Electrical Conductivity and the Laboratory determination of pH Value of Natural, Treated and Wastewaters. HMSO, 1978. ISBN 011 751428 4.	Determination of pH in Water and Leachate using the GLpH pH Meter
TM259	by HPLC	Determination of Phenols in Waters and Leachates by HPLC

NA = not applicable.

Chemical testing (unless subcontracted) performed at ALS Life Sciences Ltd Hawarden (Method codes TM) or ALS Life Sciences Ltd Aberdeen (Method codes S).



CERTIFICATE OF ANALYSIS

SDG: 201219-61
Location: Llanwern

Client Reference:
Order Number: LLA808

Report Number: 581970
Superseded Report:

Test Completion Dates

Lab Sample No(s)	23471885	23471904
Customer Sample Ref.	ML-N	ML-S
AGS Ref.		
Depth	0.00 - 0.00	0.00 - 0.00
Type	Surface Water	Surface Water

Ammoniacal Nitrogen	24-Dec-2020	24-Dec-2020
Anions by Kone (w)	24-Dec-2020	24-Dec-2020
BOD True Total	24-Dec-2020	24-Dec-2020
COD Unfiltered	24-Dec-2020	24-Dec-2020
Conductivity (at 20 deg.C)	21-Dec-2020	21-Dec-2020
Cyanide Comp/Free/Total/Thiocyanate	22-Dec-2020	22-Dec-2020
Dissolved Metals by ICP-MS	22-Dec-2020	22-Dec-2020
Dissolved Organic/Inorganic Carbon	22-Dec-2020	21-Dec-2020
Dissolved Oxygen by Probe	23-Dec-2020	23-Dec-2020
EPH CWG (Aliphatic) Aqueous GC (W)	23-Dec-2020	23-Dec-2020
EPH CWG (Aromatic) Aqueous GC (W)	23-Dec-2020	23-Dec-2020
Fluoride	21-Dec-2020	21-Dec-2020
GRO by GC-FID (W)	23-Dec-2020	23-Dec-2020
Hexavalent Chromium (w)	21-Dec-2020	21-Dec-2020
Mercury Dissolved	29-Dec-2020	29-Dec-2020
Mercury Unfiltered	23-Dec-2020	23-Dec-2020
PAH in waters by GC-MS (diss.filt)	22-Dec-2020	22-Dec-2020
PAH Spec MS - Aqueous (W)	23-Dec-2020	23-Dec-2020
pH Value	22-Dec-2020	21-Dec-2020
Phenols by HPLC (W)	23-Dec-2020	21-Dec-2020
Phosphate by Kone (w)	21-Dec-2020	21-Dec-2020
Redox Potential	22-Dec-2020	22-Dec-2020
Sulphide	31-Dec-2020	31-Dec-2020
Sulphur Dissolved by ICP-OES	23-Dec-2020	23-Dec-2020
Suspended Solids	22-Dec-2020	21-Dec-2020
SVOC MS (W) - Aqueous	23-Dec-2020	23-Dec-2020
Total Dissolved Solids	21-Dec-2020	21-Dec-2020
Total Metals by ICP-MS	22-Dec-2020	22-Dec-2020
Total Organic and Inorganic Carbon	22-Dec-2020	22-Dec-2020
TPH CWG (W)	23-Dec-2020	23-Dec-2020
Turbidity in waters	21-Dec-2020	21-Dec-2020
VOC MS (W)	22-Dec-2020	22-Dec-2020



CERTIFICATE OF ANALYSIS

SDG:	201219-61	Client Reference:		Report Number:	581970
Location:	Llanwern	Order Number:	LLA808	Superseded Report:	

Appendix

General

1. Results are expressed on a dry weight basis (dried at 35°C) for all soil analyses except for the following: NRA and CEN Leach tests, flash point LOI, pH, ammonium as NH₄ by the BRE method, VOC TICs and SVOC TICs.

2. If sufficient sample is received a sub sample will be retained free of charge for 30 days after analysis is completed (e-mailed) for all sample types unless the sample is destroyed on testing. The prepared soil sub sample that is analysed for asbestos will be retained for a period of 6 months after the analysis date. All bulk samples will be retained for a period of 6 months after the analysis date. All samples received and not scheduled will be disposed of one month after the date of receipt unless we are instructed to the contrary. Once the initial period has expired, a storage charge will be applied for each month or part thereof until the client cancels the request for sample storage. ALS reserve the right to charge for samples received and stored but not analysed.

3. With respect to turnaround, we will always endeavour to meet client requirements wherever possible, but turnaround times cannot be absolutely guaranteed due to so many variables beyond our control.

4. We take responsibility for any test performed by sub-contractors (marked with an asterisk). We endeavour to use UKAS/MCERTS Accredited Laboratories, who either complete a quality questionnaire or are audited by ourselves. For some determinands there are no UKAS/MCERTS Accredited Laboratories, in this instance a laboratory with a known track record will be utilised.

5. If no separate volatile sample is supplied by the client, or if a headspace or sediment is present in the volatile sample, the integrity of the data may be compromised. This will be flagged up as an invalid VOC on the test schedule and the result marked as deviating on the test certificate.

6. NDP - No determination possible due to insufficient/unsuitable sample.

7. Results relate only to the items tested.

8. LoDs (Limit of Detection) for wet tests reported on a dry weight basis are not corrected for moisture content.

9. **Surrogate recoveries** - Surrogates are added to your sample to monitor recovery of the test requested. A % recovery is reported, results are not corrected for the recovery measured. Typical recoveries for organics tests are 70-130%. Recoveries in soils are affected by organic rich or clay rich matrices. Waters can be affected by remediation fluids or high amounts of sediment. Test results are only ever reported if all of the associated quality checks pass; it is assumed that all recoveries outside of the values above are due to matrix affect.

10. Stones/debris are not routinely removed. We always endeavour to take a representative sub sample from the received sample.

11. In certain circumstances the method detection limit may be elevated due to the sample being outside the calibration range. Other factors that may contribute to this include possible interferences. In both cases the sample would be diluted which would cause the method detection limit to be raised.

12. Mercury results quoted on soils will not include volatile mercury as the analysis is performed on a dried and crushed sample.

13. For leachate preparations other than Zero Headspace Extraction (ZHE) volatile loss may occur.

14. For the BSEN 12457-3 two batch process to allow the cumulative release to be calculated, the volume of the leachate produced is measured and filtered for all tests. We therefore cannot carry out any unfiltered analysis. The tests affected include volatiles GCFID/GCMS and all subcontracted analysis.

15. Analysis and identification of specific compounds using GCFID is by retention time only, and we routinely calibrate and quantify for benzene, toluene, ethylbenzenes and xylenes (BTEX). For total volatiles in the C5-C12 range, the total area of the chromatogram is integrated and expressed as ug/kg or ug/l. Although this analysis is commonly used for the quantification of gasoline range organics (GRO), the system will also detect other compounds such as chlorinated solvents, and this may lead to a falsely high result with respect to hydrocarbons only. It is not possible to specifically identify these non-hydrocarbons, as standards are not routinely run for any other compounds, and for more definitive identification, volatiles by GCMS should be utilised.

16. We are accredited to MCERTS for sand, clay and loam/topsoil, or any of these materials - whether these are derived from naturally occurring soil profiles, or from fill/made ground, as long as these materials constitute the major part of the sample. Other coarse granular material such as concrete, gravel and brick are not accredited if they comprise the major part of the sample.

17. **Tentatively Identified Compounds (TICs)** are non-target peaks in VOC and SVOC analysis. All non-target peaks detected with a concentration above the LoD are subjected to a mass spectral library search. Non-target peaks with a library search confidence of >75% are reported based on the best mass spectral library match. When a non-target peak with a library search confidence of <75% is detected it is reported as "mixed hydrocarbons". Non-target compounds identified from the scan data are semi-quantified relative to one of the deuterated internal standards, under the same chromatographic conditions as the target compounds. This result is reported as a semi-quantitative value and reported as Tentatively Identified Compounds (TICs). TICs are outside the scope of UKAS accreditation and are not moisture corrected.

18. Sample Deviations

If a sample is classed as deviated then the associated results may be compromised.

1	Container with Headspace provided for volatiles analysis
2	Incorrect container received
3	Deviation from method
4	Matrix interference
◆	Sample holding time exceeded in laboratory
@	Sample holding time exceeded due to late arrival of instructions or samples
§	Sampled on date not provided

19. Asbestos

When requested, the individual sub sample scheduled will be analysed in house for the presence of asbestos fibres and asbestos containing material by our documented in house method TM048 based on HSG 248 (2005), which is accredited to ISO17025. If a specific asbestos fibre type is not found this will be reported as "Not detected". If no asbestos fibre types are found all will be reported as "Not detected" and the sub sample analysed deemed to be clear of asbestos. If an asbestos fibre type is found it will be reported as detected (for each fibre type found). Testing can be carried out on asbestos positive samples, but, due to Health and Safety considerations, may be replaced by alternative tests or reported as No Determination Possible (NDP). The quantity of asbestos present is not determined unless specifically requested.

Identification of Asbestos in Bulk Materials & Soils

The results for identification of asbestos in bulk materials are obtained from supplied bulk materials which have been examined to determine the presence of asbestos fibres using ALS (Hawarden) in-house method of transmitted/polarised light microscopy and central stop dispersion staining, based on HSG 248 (2005).

The results for identification of asbestos in soils are obtained from a homogenised sub sample which has been examined to determine the presence of asbestos fibres using ALS (Hawarden) in-house method of transmitted/polarised light microscopy and central stop dispersion staining, based on HSG 248 (2005).

Asbestos Type	Common Name
Chrysotile	White Asbestos
Amosite	Brown Asbestos
Crocidolite	Blue Asbestos
Fibrous Actinolite	-
Fibrous Anthophyllite	-
Fibrous Tremolite	-

Visual Estimation Of Fibre Content

Estimation of fibre content is not permitted as part of our UKAS accredited test other than: - Trace - Where only one or two asbestos fibres were identified.

Respirable Fibres

Respirable fibres are defined as fibres of <3 µm diameter, longer than 5 µm and with aspect ratios of at least 3:1 that can be inhaled into the lower regions of the lung and are generally acknowledged to be most important predictor of hazard and risk for cancers of the lung.
Standing Committee of Analysts, *The Quantification of Asbestos in Soil* (2017).

Further guidance on typical asbestos fibre content of manufactured products can be found in HSG 264.

The identification of asbestos containing materials and soils falls within our schedule of tests for which we hold UKAS accreditation, however opinions, interpretations and all other information contained in the report are outside the scope of UKAS accreditation.