

**SOUTH SIDE
QUEENSWAY WASTE
MANAGEMENT SITE,
LLANWERN STEELWORKS**

**2018 Annual Review of
Environmental
Monitoring**

Report Number 1785r2v1d0219

Commissioned by
Tata Steel UK Limited
Port Talbot Works
Margam
Port Talbot
SA13 2NG

Prepared by
Geotechnology Ltd
Ty Coed
Cefn-yr-Allt
Aberdulais
SA10 8HE



February 2019

Table of Contents

1 INTRODUCTION	1
2 SITE SETTING	2
2.1 Site Location and Extent	2
2.2 Site Setting	3
2.3 Ground Conditions	3
2.3.1 Holocene sediments	3
2.3.2 Bedrock	4
2.3.3 Made Ground	4
2.4 Hydrogeology	4
2.4.1 Aquifer Characteristics	4
2.4.2 Groundwater Flow	5
2.5 Hydrology	6
2.6 Conceptual Site Model	6
3 LAND USE AND CLOSURE PLANNING	7
3.1 Overview	7
3.2 Areas Comprising Slag	7
3.3 Lagoons 12 and 25	8
3.4 Powerline Valley	8
3.5 Other Areas	8
4 MONITORING PROGRAMME	9
4.1 Groundwater and Surface Water	9
4.2 Dust	11
4.3 Waste Stability	11
4.4 Leachate Breakout	11
4.5 Analytical Testwork	11
4.6 Actions required	12
5 GROUNDWATER LEVEL AND QUALITY	13
5.1 Groundwater Flow	13
5.2 Groundwater Chemistry	13
6 SURFACE WATER	16
7 AMENITY ISSUES	17
8 SUMMARY AND RECOMMENDATIONS	18
8.1 Evaluation and Summary	18
8.2 Monitoring Programme	18
8.3 Actions Required	18

List of Tables

Table 4-1	New Monitoring Schedule	9
Table 4-2	Current Analytical Programme	10
Table 5-1	Groundwater Monitoring Wells	13

List of Figures

Figure 1.	Site Location Plan
Figure 2.	Site Plan Showing Permit Boundaries
Figure 3.	Areas of Site Included in Closure Plan
Figure 4.	Conceptual Site Model
Figure 5.	Available Monitoring Network
Figure 6.	Groundwater Contours 2016 and 2017

List of Appendices

Appendix 1.	Groundwater Level and Chemistry Analysis
Appendix 2.	Surface Water Chemistry Analysis

Executive Summary

The landfill area has been an area of industrial waste disposal for many years having initially been developed in the 1970's to accept wastes from the Llanwern steel works. The landfill was one of two landfill sites operated at the Llanwern site, the other being the East Waste Management Site (EWMS). The landfill accepted industrial wastes from the steel making activity whilst the EWMS accepted general wastes, refuse, biodegradable wastes as well as industrial waste.

The 89 Ha occupied by the site was developed in a series of cells, historically termed lagoons. Lagoon 12 was constructed first on the west by raising four large bunds on top of the stabilising slag layer placed over the majority of the 89 Ha. Fine metallic dust (50% iron, 3% zinc) washed from the flues of the BOS plant was suspended in water and pumped from the steel works into Lagoon 12. There it settled and hardened to form the waste deposit seen today. Infilling in Lagoon 12 was completed by the mid 1980's with Lagoon 25 coming on stream as a replacement. Lagoon 25 was also constructed by developing slag bunds onto the stabilising slag layer, with the metallic fines pumped into the Lagoon. Infilling in Lagoon 25 was completed in 2002 with the demise of the steel making plant. There are no lining systems for either the base or side slopes of either Lagoon 12 or 25.

Throughout the duration of disposal activities, steel and iron slag was deposited to the north and east of Lagoons 12 and 25. Deposits of coarse granular slag of up to 7m thickness covered parts of the areas but today approximately 1m remains as the slag has been commercially worked and recovered. Apart from the lagoons the entire area now occupied by SSQ Non-Hazardous Landfill has largely reduced to a 1m thick slag stabilising layer.

Groundwater and surface water sampling around the perimeter of the site reveals that groundwater within the upper layer of made ground is dominated by an elevated pH and alkalinity due to slaking of lime. The concentration of non-hazardous pollutants and hazardous substances is generally low. Some parameters are sometimes detected at increased concentrations, although these are not typically persistent. The elevated pH and alkalinity is likely limiting the mobility of several potential contaminants.

Deeper groundwater within the alluvial sequence also has low concentrations of most non-hazardous pollutants and hazardous substances but has a pH of approximately 8. As this pH is very different from the pH in the overlying made ground there would appear to be little hydraulic connectivity between the groundwater bodies encountered. This is not unexpected due to the sequence of low permeability sediments present.

There is scope for rationalising the monitoring programme, but Tata should first consider the potential impact of any development proposals in the area. NRW should be consulted and agree to any changes to the monitoring programme.

1 INTRODUCTION

The Environment Agency (now Natural Resources Wales) issued a Closure Notice (No. GR/EM4/01) for Llanwern Landfill, South Side of Queensway (SSQ) which specified that the landfill must cease accepting waste for disposal as of 25 February 2008 and that it must be maintained, monitored and controlled as required by the conditions of the authorisation numbered 024/79. In response, Tata commissioned Geotechnology to prepare a Closure Report and Aftercare Monitoring Plan (see Geotechnology Report 664.1/0/0708).

One of the requirements of the Aftercare monitoring period is the production of annual interpretive reports that evaluate the most recent environmental monitoring results. This report reviews the data collected up to December 2018.

2 SITE SETTING

2.1 Site Location and Extent

The Llanwern Landfill is in an area referred to as South Side of Queensway (SSQ) which lies immediately to the south of Llanwern Steelworks to the east of Newport. The centre of the landfill site is at Ordnance Survey Grid Reference ST375 858, as shown on the site location plan (Figure 1). Access to the site is only possible through the steelworks off Queensway Road which runs east to west through the plant, north of the landfill.

Until recently, Queensway was a road entirely within the works boundary, but the road has become a public road as the steelworks boundary has shrunk following closure of the “heavy end”, where iron and steel was produced. The parcel of land to the south of Queensway (known as South Side Queensway or SSQ for short) is now separated from the secure part of the works. Parts of the site can be accessed by members of the public directly from this road.

In the 1970’s, Newport Borough Council, issued a COPA licence for the disposal of waste materials from the works within SSQ. The licence was never surrendered or rescinded and the licence transferred into the Waste Management regime. Various parts of the SSQ Waste Management site were subsequently taken into the IPPC permit for the steelworks, but this permit ceased with the cessation of steelmaking in 2002. Subsequently, several parts of the SSQ Site were taken into the existing steelworks PPC Permit (Permit BS3905). A Non-Hazardous landfill has also been permitted under the PPC regime within SSQ (PPC Permit GP 3331SV). This PPC landfill is referred to as South Side Queensway Non-Hazardous Landfill (SSQNHL) and its location is shown on Figure 2. This landfill has yet to be constructed and has not yet entered its pre-operational phase.

Due to the different waste management activities and changes in regulatory regime, the boundary positions of the currently applicable regulatory regime are complex. To assist with understanding the current situation the position of all relevant boundaries are shown in Figures 2 and 3. The position of key surface water collection ditches within the site boundary are also shown on Figure 3. These ditches collect surface run-off from SSQ which is diverted to the main works treatment plant prior to discharge in accordance with the current discharge consent. The regulatory boundaries shown on Figure 2 are:

- Current Waste Management Licence Boundary No. 024/79
- Boundary of SSQNHL PPC Permit GP 3331SV
- Relevant boundaries of Llanwern Steelworks PPC Permit BS3905

In the context of the areas of SSQ which have now been definitively closed and which are of most relevance to this report, these are distinguished from the other site areas as coloured blocks on Figure 3. On Figure 3, the area which has been definitively closed is outlined with a black dashed line with key sub-areas shaded. The closure plan, therefore, only referred to the areas within the dashed closure boundary and no other areas. The areas bound by the closure plan are:

- Slag Area W
- Slag Area E
- Lagoons 25 and 12 comprising slurry from the BOS and Blast Furnace plants
- Powerline Valley

There are also small areas outside of these distinguished areas although these have not been impacted by waste activities.

2.2 Site Setting

The site lies within an existing industrial area. The northern area of land within SSQ is occupied by Newport Galvanizers Ltd. and Air Products Ltd. North of Queensway road is the steel plant itself. To the west of the site lies an area currently occupied by Multiserv. To the east of the site lies the works effluent treatment reed beds. The steel plant boundary lies some 57m to the south of the site with the land ownership boundary lying further to the south again. Land to the south of Tata's ownership comprises Bowleaze Common which is part of the Wentloog levels, an area of ecological interest benefiting from statutory protection with a SSSI (Site of Special Scientific Interest) designation. This land comprises flat, low lying, sparsely populated and reclaimed grazing land.

The landfill site is partly located within the path of a proposed relief road which is to be constructed between junctions 23 and 29 of the M4. The relief road will run between Magor and Congleton.

2.3 Ground Conditions

The geology of the site has been determined from published information and several phases of site investigations.

The site is located on a Holocene sequence of low permeability sediments that overlie Mercia Mudstone. The mudstones, exposed to the north of the site, show a shallow dip to the SSW.

2.3.1 Holocene sediments

A Holocene sequence of clays and peat overlie bedrock at the site. This sequence of clays and peats are typically 10 to 15 meters thick across the Gwent levels and were formed within the last 10,000 years or so. At the site, these sediments have been found to be locally up to 17 meters thick and to comprise an upper and lower clay layer separated by a peat horizon.

The upper clay layer varies in thickness from 3.1m (borehole 18) and 7m (borehole 21) across the site and has been found in all site investigation boreholes. Laboratory testing of 4 undisturbed samples of the upper clay layer have established permeabilities in the range 1.4×10^{-10} and $9.2 \times 10^{-10} \text{ ms}^{-1}$.

A peat layer has been encountered, below the upper clay, in all the boreholes at the site and has been found to be between 1 and 2 m thick. Six variable head permeability tests have been undertaken in boreholes completed within the peat which have established a range of permeabilities between $4.8 \times 10^{-7} \text{ ms}^{-1}$ and $7.2 \times 10^{-6} \text{ ms}^{-1}$. The peat, in relative terms, is the "most permeable" unit within the Holocene sediments beneath the site.

The lower clay layer has been found to vary in thickness between 1 metre (borehole 21) and 8.9 metres (borehole 23) and once again has been identified in all the site investigation boreholes. Whilst no sampling and testing for permeability has been undertaken from this unit, lithologically it is closely related to the upper clay unit and, as such, it would be expected to have a permeability of $5 \times 10^{-10} \text{ ms}^{-1}$.

There is some evidence that limited thin lenses of gravel occur between the lower clay and the weathered Mercia Mudstone.

2.3.2 Bedrock

The bedrock found below the Holocene sediments at the site is Mercia Mudstone (formally known as Keuper Marl). The Mercia Mudstones of the area are documented to consist of red or chocolate fine silty mudstones with conchoidal fractures.

From site investigation boreholes, the Mercia Mudstone has been found to have a weathered surface of approximately 1 to 2 meters in thickness. Falling head tests have been carried out in four piezometers completed within this weathered horizon. Borehole 23 on site, as well as 3 boreholes adjacent to the site, have established permeabilities of around $1 \times 10^{-5} \text{ ms}^{-1}$.

The un-weathered Mercia Mudstone, which has very low matrix permeability and extremely limited secondary fracture permeability, is an important unit in terms of groundwater flow at the site, in that it is considered to provide the impermeable base to the groundwater “flow” system within the overlying Holocene sediments.

Rockhead below the Holocene sediments of the Gwent Levels is between -5m and -7.5 m below OD.

2.3.3 Made Ground

The area is currently covered with a blanket of fill materials comprising mainly steelmaking BOS slag (steel slag) which was deposited under the terms of a COPA licence in the 1970's. This layer is approximately 1m thick.

2.4 Hydrogeology

2.4.1 Aquifer Characteristics

There are no Source Protection Zones (SPZ) near the site, the nearest SPZ is that for the Great Spring which at its nearest point is more than 5km away from the site and is hydraulically isolated from the site by the intervening geology.

The strata below and near the site is considered by Natural Resources Wales as a non-aquifer (as shown on the Agency's published Vulnerability Maps). Both the Holocene sediments and the underlying Mercia Mudstone are of low to extremely low permeability, which supports the Agency's classification of the area as a Non-Aquifer. There is no known licensed or unlicensed groundwater abstraction from strata underlying the Caldicot Levels.

The upper clay, with proven permeabilities in the range of 4×10^{-10} and $9.2 \times 10^{-10} \text{ ms}^{-1}$ and with a thickness of between 3.1 meters (borehole 18) and 7 meters (borehole 21) is a natural geological barrier that prevents vertical flow from the ground surface to the water table. Both the smaller drainage ditches around the site and the larger reens such as Hundred Perch Reen are founded within and do not pass through the upper clay layer.

Permeability values for the upper clay were acquired from testing undisturbed samples (U100's) in the laboratory and can, therefore, be relied upon to reflect field conditions. Uncertainty in the quality of the permeability results is reduced when all samples are considered, thus giving a narrow range and the fact that one of results comes from testing during the Site Investigation carried out by Enviro in 2002.

The lower clay, having a thickness across the site of between 1 meter (borehole 21) and 8.9 meters (borehole 23) has the same lithological and sedimentological characteristics as the upper clay. Whilst its permeability has not been directly tested, it is considered to have permeabilities in a narrow range centred around $5 \times 10^{-10} \text{ ms}^{-1}$, similar to that of the upper clay. As such the lower clay, like the upper clay, likely presents a significant barrier to vertical flow.

The peat horizon that has been identified across the site has permeabilities in the range of $4.8 \times 10^{-7} \text{ ms}^{-1}$ and $7.2 \times 10^{-6} \text{ ms}^{-1}$ and a thickness varying between 1 and 2 meters. It can be considered permeable in a relative sense, when compared to the upper and lower clays. Its position below the site, sandwiched between two layers of low permeability clay results in it becoming a credible route for the horizontal movement of limited volumes of groundwater. This is not because the peat is particularly permeable, or that it represents an aquifer but simply that it represents a "permeability contrast" when considering its location between two very low permeability clays. No significant amount of groundwater can be extracted from the peat.

There are possible localised lenses of gravels between the lower clay and the weathered Mercia Mudstone. The evidence for these gravels comes from samples taken at the depth of the weathered mudstone and there is a potential for some confusion between the two. However, with respect to groundwater flow, were there gravels in such circumstances, they would have a permeability like that attributed to the weathered mudstone which is considered contiguous across the site, so in hydrogeological terms their presence or absence is irrelevant.

The weathered layer of Mercia Mudstone, located below the lower clay and above the un-weathered Mercia Mudstone has similar hydrogeological significance as the peat layer, in that its permeability, as established from variable head tests, is of the order of $1 \times 10^{-5} \text{ ms}^{-1}$. As with the peat layer, this provides opportunity for horizontal movement of groundwater.

The significance of the underlying un-weathered Mercia Mudstone is that it is the impermeable base above which the limited groundwater movement occurring in this geological setting, takes place.

The absence of any groundwater abstractions from this hydrogeological setting, in an area where mains supply requires significant investment in infrastructure, supports the assertion that groundwater is not a viable resource in this low permeability setting.

2.4.2 Groundwater Flow

Historical hydrographs developed from the collection of groundwater level data show a variation between summer and winter groundwater levels of less than 0.5 meters. The small variation in groundwater levels over a 12-month period demonstrates that the amounts of recharge reaching the groundwater system within the peat and weathered mudstone horizon are very limited, particularly when considering the low specific yield of each formation.

Groundwater below the site has been encountered solely within the made ground, peat and weathered mudstone (bedrock) layers. Rest groundwater levels within the peat and bedrock units are observed as being almost identical suggesting that the peat and weathered mudstone horizons are in hydraulic continuity with one another. There is no lithological evidence for linkage between these two units directly below the site as all boreholes demonstrate the presence of the lower clay layer.

The historical groundwater gradient within the low permeability Holocene sediments has been previously found to be approximately 0.0033 towards the east-southeast, that is Hundred Perch Reen. Groundwater gradients are very shallow, reflecting extremely low rates of recharge to the peat due to the overlying low permeability upper clay layer and the frequency of reens which groundwater within the peat discharges to.

2.5 Hydrology

The site is located close to the boundary of the Caldicot Levels which are part of the larger Gwent Levels. The Gwent Levels are an extensive low-lying area of estuarine alluvium located on the north side of the Severn estuary in Southeast Wales between Cardiff and the River Rhymney in the west and Chepstow on the River Wye in the east.

The Levels were created through the enclosing and draining of tidal saltmarshes and their continued existence requires the ongoing management of seawalls which prevent their frequent inundation by the sea. To manage runoff from the low permeability sediments that make up the levels and to transport runoff from adjacent areas of higher ground a complex system of channels has been constructed. The channels make up a hierarchical network, smaller ditches discharging into larger water courses known as reens, which in turn discharge into the sea via pumps and tidal gates. This network is the key feature of the Levels, both in terms of their ecological importance and the historic landscape. The minor ditches around the site are completed above the water table whilst the deeper reens around the site are completed within the Upper Clay, just below the water table. The drainage network and flows within it are managed by the Caldicot and Wentloog Drainage Board (an IDB).

Almost all the annual recharge falling on the site leaves via surface runoff due to the low permeability nature of the sites soils and the underlying low permeability Holocene sediments.

The closest water courses to the site which are not part of the sites own drainage infrastructure, are the Elver Pill Reen and the Hundred Perches Reen, some 359 meters to the ESE of the site. Due to their managed nature, flows within the reens can be variable and flow data is limited. Previous spot gauging of Hundred Perches Reen taken at the point where Queensway crosses the reen to the north of the site, shows flows to be in the order of 78 litres per second.

The Caldicot Levels are a SSSI, primarily as they are representative of a grazing marsh/reen habitat and also due to their invertebrate assemblages, plant species, otters, water voles and breeding birds. The nearest SAC to the site is the River Usk some 4 kilometres to the west of the site. There is no hydraulic connection between the site and the River Usk with all surface water from the levels draining directly into the Severn Estuary.

2.6 Conceptual Site Model

To enable the risks posed to groundwater and surface water to be evaluated, a conceptual hydrogeological model was developed as part of the closure process. The diagrammatic representation of the model is provided in Figure 4.

3 LAND USE AND CLOSURE PLANNING

3.1 Overview

The landfill area has been an area of industrial waste disposal for many years, initially developing in the 1970's to accept wastes from the Llanwern Steel Works. The landfill was one of two landfill sites operated at the Llanwern site, the other being the East Waste Management Site (EWMS). The landfill accepted industrial wastes from the steel making activity whilst the EWMS accepted general wastes, refuse, biodegradable wastes as well as industrial waste.

The 89 Ha occupied by the site was developed in a series of cells, historically termed lagoons. Lagoon 12 was constructed first on the west by raising four large bunds on top of the stabilising slag layer placed over the majority of the 89 Ha. Fine metallic dust (50% iron, 3% zinc) washed from the flues of the BOS plant was suspended in water and pumped from the steel works into Lagoon 12. There it settled and hardened to form the waste deposit seen today. Infilling in Lagoon 12 was completed by the mid 1980's with Lagoon 25 coming on stream as a replacement. Lagoon 25 was also constructed by developing slag bunds onto the stabilising slag layer, with the metallic fines pumped into the Lagoon. Infilling in Lagoon 25 was completed in 2002 with the demise of the steel making plant. There are no lining systems for either the base or side slopes of either Lagoon 12 or 25.

Throughout the duration of disposal activities, steel and iron slag was deposited to the north and east of Lagoons 12 and 25. Deposits of coarse granular slag of up to 7m thickness covered the areas indicated on Figure 3 as Slag Area W, Slag Area E and the SSQ Non-Hazardous Landfill. Since its deposition, both steel slag and blast furnace slag have become commercially viable for a variety of applications and most of the deposit has now been removed. The entire area now occupied by SSQ Non-Hazardous Landfill has, therefore, been reduced to a 1m thick slag stabilising layer.

Lagoon 27 is divided into four equal quarters and has accepted wastes from the Hot Mill under an IPC and now a PPC Permit. This area lay outside the scope of the closure report for the areas in SSQ. Similarly, the water treatment lagoons in the NE of the site now fall under the works PPC Permit and therefore did not form part of the closure report.

Some of the activities in these areas have been carried out by Tata and its predecessors (Corus and British Steel) whilst some have been carried out by contractors (such as Harsco and Multiserv) and others by third parties (such as Air Products, Newport Galvanisers, and Tarmac).

3.2 Areas Comprising Slag

These areas have been re-worked by Multiserv and Tarmac. Multiserv first recovered the steel from the material to enable excavation of secondary aggregate by Tarmac. This recovery operation went on for several years but is now largely complete. The recovery process worked from east to west, from the area of SSQ NHL towards Slag Area W. To enable the continued tracking of vehicles, a foundation layer of weathered slag approximately 1m thick is all that remains following removal of the workable slag.

3.3 Lagoons 12 and 25

Lagoons 12 and 25 are very similar in terms of their site position, construction and deposit. Lagoon 12, however, is approximately 20 years old whilst Lagoon 25 is 10 years old.

Assessments completed as part of the closure report demonstrated that the lagoons did not pose a significant risk to controlled waters due to the chemical stability of the stored material, the lack of sensitivity of the hydrogeological setting and the collection of surface run-off by the sites' surface water drainage system. Further, the stability assessment demonstrated that there were no concerns over their long-term stability.

As the lagoons pose no risk to the aquatic environment and have been shown to be stable, the restoration plan focussed on preventing the release of dust during dry conditions, improving the overall site aesthetics and ensuring that the surface water collection ditches are regularly maintained. As can be seen from Figure 2, both lagoons are partially vegetated, with the vegetation at Lagoon 12 more advanced than Lagoon 25. Consequently, there have been no recorded issues regarding dust blow events. Therefore, there is no intention to disturb this habitat currently. Rather, the occurrence of dust release at both lagoons will be monitored and only, if necessary, will additional soil cover be placed. Such an approach will also benefit the appraisal of recovery operations, which is ongoing.

3.4 Powerline Valley

No specific restoration plans were planned for this area as no waste activities have occurred within the area.

3.5 Other Areas

No specific restoration plans were planned for these areas at this stage as no waste activities have occurred within these areas.

4 MONITORING PROGRAMME

The current available monitoring network is illustrated in Figure 5.

4.1 Groundwater and Surface Water

The AMP set out the determinants to be examined in groundwater and surface water. During 2014 and 2015, Tata commissioned more frequent monitoring than required by the AMP and implemented most of the characterisation suite. Following the completion of the first 12 months of monitoring, the AMP suggested that the analytical data should be reviewed to identify parameters from the characterisation suite that should be included in the indicator suite. This review was presented in the 2014 Annual Monitoring Report and the monitoring programme, summarised in Tables 4-1 and 4-2 started to be implemented during 2016.

Table 4-1 New Monitoring Schedule

Monitoring Parameter	Monitoring Location	Frequency	Type of Monitoring Point
Groundwater	BH13 to BH19, BH24 (already installed), BH201 - BH205	Quarterly	50mm diameter piezometer wells
Surface water	SW1, SW2 and SW3	Quarterly	Surface water body comprising reens
Leachate	Lagoon 12 and 25 embankments	Six Monthly	Visual observation and physical measurement
Dust and Particulates	As required	As required	Dust gauges as required
Odour	As required	As required	Subjective assessment area
Stability	Lagoon 12 embankment	Annual	Visual observation and physical measurement

Table 4-2 Current Analytical Programme

Measurement	Groundwater and Surface Water Suite	
Monitoring Positions	All surface water and groundwater locations	
Frequency	Annually	All other times
Suite Reference	Characterisation Suite	Indicator Suite
Water Level	•	•
Temperature	•	•
Ph	•	•
Electrical Conductivity	•	•
Dissolved Oxygen	•	•
Ammoniacal Nitrogen	•	•
Total Oxidised Nitrogen	•	
Total Suspended Solids	• (surface water only)	• (surface water only)
BOD	•	
COD	•	
Total Organic Carbon	•	
Aluminium	•	
Arsenic	•	
Antimony	•	•
Boron	•	
Cadmium	•	•
Chromium	•	•
Chromium (vi)	•	
Copper	•	•
Iron	•	
Lead	•	•
Manganese	•	
Mercury	•	
Molybdenum	•	
Nickel	•	
Phosphate	•	•
Silica	•	
Titanium	•	
Tin	•	
Vanadium	•	
Zinc	•	
Calcium	•	•
Magnesium	•	
Nitrate	•	
Nitrite	•	
Sodium	•	•
Potassium	•	
Selenium	•	
Sulphate	•	
Total Alkalinity	•	•
Chloride	•	•
Total hydrocarbons	•	
Polyaromatic hydrocarbons	•	
VOC and SVOC compounds	•	

The monitoring network is, overall, performing as designed. There are, however, several aspects that require consideration:

-
- Samples cannot always be collected from the surface water sample monitoring locations due to dense vegetation growth.
 - During 2017, samples could only be retrieved from BH16 in January. On subsequent visits the position could not be located as the surrounding area had been levelled. In 2018, Geotechnology re-located the position but the headworks require repair.
 - New sample tubing is required for BH17.
 - Samples cannot always be recovered from BH203D, which has a well screen in the peat, as there was insufficient water.
 - Buddleia growth along the southern boundary is limiting access and monitoring, particularly during the summer months.

The reader should also be aware that the laboratory is currently reporting pH values above 12 as >12 pH units as they do not appear to have the ability to accurately define pH values above this level.

4.2 Dust

The AMP details the dust monitoring programme to be implemented.

4.3 Waste Stability

The previous assessment of the stability of the waste mass, its containment bunds and the surrounding ground did not reveal the possibility of slope failure with even the most pessimistic model parameters. Waste settlement is not expected as the site has received biodegradable wastes, simply hydraulically placed industrial wastes that are now becoming cemented by mineral precipitation. Accordingly, waste settlement monitoring and waste/bund stability monitoring is not required by the AMP.

However, in recognising that there is a possibility that part of the eastern bund of Lagoon 12 is not cemented and could have an inadequate FOS (though failure is not indicated) there should be an annual walk-over each springtime to look for evidence of shallow translational slips.

4.4 Leachate Breakout

The AMP suggested leachate breakout monitoring should comprise six monthly site walkovers, particularly around the embankments of Lagoons 12 and 25.

4.5 Analytical Testwork

All aspects of the analytical and monitoring programme are directly managed by Tata Environment Department. Under the direction of the Environment Department, Geotechnology and Testing Solutions Wales (the analytical laboratory) undertake several aspects of the sampling and analysis. These include surface water and groundwater laboratory analysis and measurement of groundwater levels. Tata Environmental Department undertakes all other monitoring aspects when required. All analysis is undertaken by Testing Solutions Wales based at the Engineering Centre for Manufacturing and Materials (ECM) in Margam, adjacent to the Port Talbot steelworks.

4.6 Actions required

- Safe access to the surface water sampling points needs to be improved. Given that vegetation growth is inevitable, routine maintenance and signage would be beneficial.
- The headworks at monitoring position BH16 should be excavated and inspected as it was flattened during site clearance works in 2017.
- New sample tubing is required for BH17.
- Buddleia growth along the southern boundary is limiting access and monitoring. The vehicular access route and monitoring positions should be routinely maintained.
- Consideration could be given to preventing public access to the site and wider SSQ area.

5 GROUNDWATER LEVEL AND QUALITY

5.1 Groundwater Flow


Figure 6 presents groundwater levels encountered in the shallow made ground and peat layer during 2017. These plans have been developed from measurements of water level at the piezometers summarised in Table 5-1.


Table 5-1 Groundwater Monitoring Wells

ID	Monitoring Interval
BH13S	Made Ground
BH16S	Made Ground
BH18S	Made Ground
BH201S	Made Ground
BH203S	Made Ground
BH13D	Peat
BH16D	Peat
BH17	Peat
BH18D	Peat
BH19	Peat
BH201D	Peat
BH202D	Peat
BH203D	Peat
BH205D	Peat

5.2 Groundwater Chemistry

Appendix 1 contains a summary of the groundwater chemistry data gathered to date. The data is presented as a series of hydrochemical contour plans and time series charts. To help understand the differences in groundwater chemistry between the shallow made ground, peat and underlying bedrock a series of scatter plots are also presented in the appendix and presented in the text (see below).






groundwater from the made ground through the intervening clay as several parameters are at higher concentration in the peat (e.g. chloride, sodium, chromium) and pH is significantly lower. The cause of the increased mineralisation is suspected to be due to processes within and possibly below the peat, including the potential influence of sub-artesian groundwater in the underlying bedrock and a potential saline contribution. There are variations in the hydrochemistry in the peat, but these are not considered to be related to the passage of groundwater from the overlying made ground.

Groundwater in the Mercia mudstone is only monitored at BH24, to the south of Lagoon 25. Like the groundwater found in the peat, the groundwater in the bedrock has a circumneutral pH and elevated electrical conductivity (4000-6000 microS/cm in 2017). During 2017, the mineralisation was increasing due, in part, to sustained increases in chloride and ammonia. In 2018, mineralisation has been stable. The levels currently observed are similar to those observed previously. The precise cause of these variations is unclear.

6 SURFACE WATER

The results of the surface water monitoring are presented in Appendix 2. The data gathered during the past 12 months is similar to that collected several years ago suggesting a large degree of stability in the water chemistry.



Surface water is circumneutral, moderately mineralised with low levels of non-hazardous substances. As surface water progress from east to west, the mineralisation decreases from ~ 800 microS/cm to less than 600 microS/cm. The main reason for this change is decreasing alkalinity although most parameters are lower downgradient of SW1. Apart from a few short-term breaches, all data is typically within Environmental Quality Standards. Phosphate was detected at increased concentrations in 2017. In 2018, concentrations were low / below detection limit for most of year apart from September when 27 mg/l was detected at SW3, 43 mg/l at SW2 and 77 mg/l at SW1. Phosphate was not detected in the made ground or peat and the source is unclear at this stage.

7 AMENITY ISSUES

There have been no requirements for any dust, noise or odour monitoring or investigations.

The site can, however, be readily accessed by members of the public.

8 SUMMARY AND RECOMMENDATIONS

8.1 Evaluation and Summary

Monitoring of groundwater and surface water has revealed conditions like those previously observed. Shallow groundwater chemistry is dominated by the leaching of slag-based wastes with elevated pH and alkalinity. Such chemistry is not widely evident in the underlying peat as the made ground and peat are separated by low permeability clays. Mineralised groundwater within the peat is not considered to be a consequence of downwards percolation from the overlying made ground. Increased concentrations of cadmium in made ground, peat and the underlying bedrock were previously noted but such trends have not persisted.

Like the groundwater in the peat, surface water on the southern, downgradient edge of the site is circumneutral. With low levels of non-hazardous substances, the quality tends to meet Environmental Quality Standards.

8.2 Monitoring Programme


As noted previously, the monitoring programme could be rationalised as the current datasets reveal that groundwater gradients are low, and conditions are relatively stable. For instance, the frequency of groundwater monitoring could be reduced to six monthly and monitoring at BH203, BH16 and BH24 stopped. This latter suggestion is on the basis that BH203 is close to BH13, BH16 (which has been buried) is close to BH18 and BH24 monitors the bedrock.

Before requesting NRW to evaluate this suggestion, Geotechnology suggests that Tata first considers the potential impact of any development proposed for the site and immediate area e.g. M4 relief road, and the potential benefit of the current monitoring programme.

8.3 Actions Required

- Check integrity of the site boundary to ensure members of the public cannot gain access.
- Conduct six monthly walkovers around embankments of Lagoons 12 and 25 to check for leachate breakout.
- Conduct annual walk-over each springtime to look for evidence of shallow translational slips along the embankment of Lagoon 12.
- Improve year-round access to the surface water monitoring positions.
- Locate and expose BH16 to assess condition of headworks.
- Purchase of new sample tubing is required for BH17.
- Manage buddleia growth along the southern boundary as it is limiting access and monitoring.

Figure 1 Site Location Plan



Reproduced from the Ordnance Survey Land Ranger Map
with the permission of The Controller of Her Majesty's Stationery Office
© Crown Copyright. Geotechnology SA10 8HE Licence No AL50598A

Figure 2 Site Plan Showing Permit Boundaries




Figure 3 Areas of Site Included in Closure Plan





Figure 4 Conceptual Site Model




Figure 5 Available Monitoring Network









Figure 6 Groundwater Contours 2016 and 2017





April 2016 Shallow




September 2017 Shallow



April 2016 Deep



September 2017 Deep





**SOUTH SIDE
QUEENSWAY WASTE
MANAGEMENT SITE,
LLANWERN
STEELWORKS**


**2018 Annual Review of
Environmental
Monitoring**


**Appendix 1
Groundwater Level and
Chemistry Analysis**


Report Number 1785r2v1d0219














































































































































pH in Shallow Groundwater




Alkalinity in Shallow Groundwater (mg/l CaCO₃)




pH in Deep Groundwater




Alkalinity in in Deep Groundwater (mg/l CaCO₃)







EC in Shallow Groundwater (microS/cm)



Chloride in Shallow Groundwater (mg/l)



EC in Deep Groundwater (microS/cm)




Chloride in Deep Groundwater (mg/l)




**SOUTH SIDE
QUEENSWAY WASTE
MANAGEMENT SITE,
LLANWERN
STEELWORKS**




**2018 Annual Review of
Environmental
Monitoring**


**Appendix 2
Surface Water
Chemistry Analysis**

Report Number 1785r2v1d0219





Arsenic**Chromium****Copper**





Geotechnical &
Environmental Services

Ty Coed
Cefn-yr-Allt
Aberdulais
Neath SA10 8HE

T 01639 775293
F 01639 779173

enquiries@geotechnology.net
www.geotechnology.net